

ELKO RGNL (EKO)(KEKO) 1 W UTC-8(-7DT) N40°49.50' W115°47.48'

5140 B TPA—See Remarks Class I, ARFF Index A NOTAM FILE EKO

RWY 06-24: H7455X150 (ASPH-GRVD) S-78, D-105, 2S-133,

2D-170 PCN 63 F/B/X/T MIRL 0.3% up NE

RWY 06: PAPI(P4L)—GA 3.0° TCH 41'. Road. Rgt tfc.

RWY 24: MALSR. PAPI(P4L)—GA 3.25° TCH 51'. Thld dsplcd 1038'. Pole.

RWY 12-30: H3012X60 (ASPH) S-12 PCN 4 F/B/Y/T 2.0% up NW

RWY 12: Thld dsplcd 906'. Pole. Rgt tfc.

RWY 30: Thld dsplcd 140'. Pole.

RUNWAY DECLARED DISTANCE INFORMATION

RWY 06: TORA-7217 TODA-7217 ASDA-7217 LDA-7217

RWY 12: TORA-3012 TODA-3012 ASDA-3012 LDA-2106

RWY 24: TORA-7457 TODA-8457 ASDA-7457 LDA-6419

RWY 30: TORA-3012 TODA-3012 ASDA-3012 LDA-2871

SERVICE: S4 FUEL 100LL, JET A ~~OX~~ 1, 2 LGT ACTIVATE MALSR Rwy 24, MIRL Rwy 06-24—CTAF. PAPI Rwy 06 and Rwy 24 opr continuously. PAPI Rwy 24 does not provide obstruction clearance byd 6.5 NM from thld.

AIRPORT REMARKS: Attended 1300-0300Z±. Sfc conditions not monitored 0530-1130Z±. Fuel 100LL, A avbl 24/7. Tkf only on Rwy 12. Land only on Rwy 30. Touch and go Rwy 30 only. Rwy 24 designated calm wind rwy. Steep slope/gradient Rwy 30 upward. PPR for all acft operations over 100,000 pounds call 775-777-7190. TPA-6140(1000), jet acft 6640(1500). Cold temperature rstd arpt. Alt correction required at or blo -20°C/-4°F.

AIRPORT MANAGER: 775-777-7192

WEATHER DATA SOURCES: AWOS-3PT 119.275 (775) 778-9639.

COMMUNICATIONS: CTAF/UNICOM 123.0

RCO 122.6 (RENO RADIO)

® SALT LAKE CENTER APP/DEP CON 132.25

RADIO AIDS TO NAVIGATION: NOTAM FILE EKO.

BULLION (L) VOR/DME 114.5 BQU Chan 92 N40°45.58' W115°45.68' 324° 4.1 NM to fld. 6464/17E.

VOR unusable:

088°-110° byd 20 NM blo 12,900'

111°-130° byd 32 NM blo 12,900'

DME unusable:

088°-110° byd 20 NM

111°-130° byd 32 NM

LDA/DME 108.5 I-EKO Chan 22 Rwy 24. LDA offset angle 5° 58 min. DME unusable byd 13 NM blo 9,000'.

