

# FORMS

---





# FORMS FOR PROJECT AND IA

## TABLE OF CONTENTS NUMERICAL SEQUENCE FORM NUMBERS

<u>Nev. Form No.</u>	<u>Nev. Form Name</u>
020-016 Rev. 2/10	Transmittal for Asphalt Samples
020-017 Rev. 3/08	Transmittal for Concrete Samples
020-018 Rev. 7/12	Transmittal for Test Samples and Certifications
040-003 Rev. 7/14	Nuclear Gauge / Sand Cone Check Test Form (Proctor)
040-006 Rev. 11/07	Field Sand Equivalent Worksheet
040-007 Rev. 7/14	Nuclear Compaction Report for Soils and Aggregates (Proctor)
040-010 Rev. 2/09	Daily Report of Tests Made in Field
040-011 Rev. 10/17	Daily Plant Report of Asphalt Mixtures
040-013 Rev. 11/10	Field Material Sieve Sheet
040-014 Rev. 10/16	Field L.L. and P.I. Worksheet
040-016 Rev. 11/10	Report of Tests of Portland Cement Concrete Pavement
040-017 Rev. 9/20	Nuclear Thin Layer Compaction Report for Plantmix Bituminous Pavements
040-017A Rev. 11/19	Nuclear Thin Lift Correction Factor Worksheet
040-017B Rev. 9/13	Bulk Specific Gravity and Density of Compacted Bituminous Mixtures
040-018 Rev. 8/06	Compaction Report for Plantmix Bituminous Pavements (Drilled Core Data)
040-021 Rev. 8/20	Striping Paint Thickness Report
040-023A Rev. 11/08	Absorption and Specific Gravity for Fine Aggregate
040-023B Rev. 2/09	Absorption and Specific Gravity for Coarse Aggregates
040-026 Rev. 7/14	Nuclear Gauge / Sand Cone Correlation Form (Proctor)

# FIELD TESTING FOR PROJECT AND IA

## TABLE OF CONTENTS NUMERICAL SEQUENCE FORM NUMBERS

<u>Nev. Form No.</u>	<u>Nev. Form Name</u>
040-030 Rev. 8/10	Theoretical Maximum Specific Gravity of Bituminous Paving Mixtures (Field Method)
040-032 Rev. 7/07	Emulsion Viscosity Worksheet
040-035 Rev. 10/09	Report of Field Tests of Coarse and Fine Aggregate for Concrete
040-041 Rev. 3/05	Retroreflectivity Measurements
040-047 Rev. 7/07	Pavement Marking Film Adhesion Test (Section 634)
040-048 Rev. 12/05	Nuclear Gauge Operator's Worksheet for Control Strip Density Part 1 and Part 2
040-050 Rev. 11/10	Field Material Sieve Test / Bituminous Ration by Ignition Method
040-053 Rev. 10/20	Report of Calibration Factor (Including Weekly Checks) Using the Ignition Furnace Method
040-067 Rev. 5/09	Water Volume Calculations for Sand Cone Apparatus and Measuring Vessel (Hat)
040-068 Rev. 3/09	Sand Density Calculation – T102
040-069 Rev. 8/20	Moisture-Density Determination, Compaction Report Part 1 and Part 2 (Proctor Form)
040-078 Rev. 1/14	Concrete Field Summary Report
040-081 Rev. 10/16	Calibration of Unit Weight Measure

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION  
**TRANSMITTAL FOR ASPHALT SAMPLES**

Contract No. .... Project No.....Field No.....

County .....Highway .....Milepost.....

Type of Asphalt .....Producer .....

Shipping Point ..... Actual Tonnage .....

Refinery Ticket No.....Weight Ticket No. ....

Tank Car/Truck/Trailer No. ....Contractor .....

Sampled by ..... Date Sampled .....

Observed by .....

District No. ....APO No.....

Emulsion Field Viscosity .....Tested by .....

**TRANSMITTAL TO BE FASTENED TO SAMPLE CONTAINER WITH MASKING TAPE**

NDOT 020-016 ( Rev. 2-10)

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION  
**TRANSMITTAL FOR ASPHALT SAMPLES**

**A.** Contract No. ...**3925**..... **B.** Project No. ....**SI-0035(119)**..... **C.** Field No.....**1**.....  
**D.** County .....**Washoe**..... **E.** Highway .....**I-80**..... **F.** Milepost...**10.50**.....  
**G.** Type of Asphalt .....**PG64-28NV**..... **H.** Producer .....**Paramount Fernley**.....  
**I.** Shipping Point .....**Fernley Nevada**..... **J.** Actual Tonnage .....**20.55**.....  
**K.** Refinery Ticket No. .........**N/A**..... **L.** Weight Ticket No. .........**N/A**.....  
**M.** Tank Car/Truck/Trailer No. .........**N/A**..... **N.** Contractor ...**Granite Construction**.....  
**O.** Sampled by ....**Fred Grimes - Contractor**..... **P.** Date Sampled .....**06/06/2020**.....  
**Q.** Observed by .....**Joe Bob**.....

<b>R.</b> District No..... <b>N/A</b> .....	<b>S.</b> APO No. ......... <b>N/A</b> .....
<b>T.</b> Emulsion Field Viscosity ..... <b>N/A</b> .....	<b>U.</b> Tested by ..... <b>N/A</b> .....

**TRANSMITTAL TO BE FASTENED TO SAMPLE CONTAINER WITH MASKING TAPE**

**020-016 Rev. 02/10**

**TRANSMITTAL FOR ASPHALT SAMPLES**

<b><u>LINE</u></b>	<b><u>EXPLANATION OF NEEDED INFORMATION</u></b>
<b>A -</b>	Contract number for the material being tested, found in the Contract Plans or Special Provisions (EX. 3925)
<b>B -</b>	Project number for the material being tested, found in the Contract Plans or Special Provisions (EX. SI-0035(119))
<b>C -</b>	Field number for this particular sample in numerical order (EX. 1)
<b>D -</b>	County in which the sample is being used (EX. Washoe)
<b>E -</b>	Highway where the sample is being used (EX. I. 80)
<b>F -</b>	Milepost where the sample is being used (EX. 10.50)
<b>G -</b>	Type of asphalt being sampled (EX.PG64-28NV)
<b>H -</b>	Producer that is actually manufacturing the asphalt (EX. Paramount Fernley) NOTE: Not where the material is stored
<b>I -</b>	Shipping point where the asphalt was produced (EX. Fernley Nevada)
<b>J -</b>	Actual tonnage that this sample represents (EX. 20.55 tons) NOTE: Asphalt samples will be taken every 25 tons. Actual sample size will be determined by total wet tons. Depending on how many asphalt samples were taken for that day, determines the tons per sample:  From the Job-Mix Formula: Bitumen ratio = 5.0%, Mineral filler = 1.28%, RAP = 0.8%; therefore, $1 + (.05 + .0128 + .008) = 1.0708$ Total wet tons for day = $2200.00 \div 1.0708 = 2054.54$ Dry tons PG for the day = $2054.54 \times 0.05 = 102.73$ tons Samples taken for the day = 5 Tons per sample = $102.73 \div 5 = 20.55$ 20.55 tons will represent each sample for that day.
<b>K -</b>	Refinery ticket number, not applicable to hotplant asphalt samples (EX. N/A)
<b>L -</b>	Weight Ticket number, not applicable to hotplant asphalt samples (EX. N/A)
<b>M -</b>	Tank Car/Truck/Trailer Number, not applicable to hotplant asphalt samples (EX. N/A)

**020-016 Rev. 02/10**

**TRANSMITTAL FOR ASPHALT SAMPLES**

**LINE**

**EXPLANATION OF NEEDED INFORMATION**

- N -** Prime contractor awarded the contract (EX. Granite Construction)
- O -** Name of the contractor's representative that sampled the asphalt at the hotplant (Ex. Fred Grimes - Contractor)
- P -** Date the sample was taken (EX. 06/06/2020)
- Q -** NDOT representative who observed the sample being taken (EX. Joe Bob)  
NOTE: If you did not observe the sampling being taken, write "Not observed"
- R -** Not applicable to hotplant asphalt samples
- S -** Not applicable to hotplant asphalt samples
- T -** Not applicable to hotplant asphalt samples
- U -** Not applicable to hotplant asphalt samples

**NOTES:**

- 1.** Fold transmittal in half with the writing inside and attach with 2 small strips of masking tape. Seal transmittal in plastic envelope in case of inclement weather.
- 2.** Make sure outside of sample container is clean, DO NOT use any chemicals to clean the sample container. If sample container is not clean, have contractor take another sample.
- 3.** Samples should be submitted ASAP to the Materials Lab, but no longer that 7 days.



STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION  
**TRANSMITTAL FOR ASPHALT SAMPLES**

Contract No. .... Project No.....Field No.....

County .....Highway .....Milepost.....

Type of Asphalt .....Producer .....

Shipping Point ..... Actual Tonnage .....

Refinery Ticket No.....Weight Ticket No. ....

Tank Car/Truck/Trailer No. ....Contractor .....

Sampled by ..... Date Sampled .....

Observed by .....

District No. ....APO No.....

Emulsion Field Viscosity .....Tested by .....

**TRANSMITTAL TO BE FASTENED TO SAMPLE CONTAINER WITH MASKING TAPE**

NDOT 020-016 ( Rev. 2-10)

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION  
**TRANSMITTAL FOR ASPHALT SAMPLES**

**A.** Contract No. ...**3925**..... **B.** Project No. ....**SI-0035(119)**..... **C.** Field No.....**1**.....  
**D.** County .....**Washoe**..... **E.** Highway .....**I-80**..... **F.** Milepost.....**10.50**.....  
**G.** Type of Asphalt .....**LMCRS-2h**..... **H.** Producer .....**Idaho Asphalt**.....  
**I.** Shipping Point .....**Nampa Idaho**..... **J.** Actual Tonnage .....**35.7**.....  
**K.** Refinery Ticket No. ....**00125695**..... **L.** Weight Ticket No....**6526108**.....  
**M.** Tank Car/Truck/Trailer No. ...**456/456B**..... **N.** Contractor ....**Granite Construction**....  
**O.** Sampled by ....**Sam Weist - Truck Driver**..... **P.** Date Sampled .....**06/06/2014**.....  
**Q.** Observed by .....**Joe Bob**.....

<b>R.</b> District No..... <b>2</b> .....	<b>S.</b> APO No. .... <b>N/A</b> .....
<b>T.</b> Emulsion Field Viscosity ..... <b>254</b> .....	<b>U.</b> Tested by ..... <b>Joe Bob</b> .....

**TRANSMITTAL TO BE FASTENED TO SAMPLE CONTAINER WITH MASKING TAPE**

**020-016 Rev. 02/10**

**TRANSMITTAL FOR ASPHALT SAMPLES**

<b><u>LINE</u></b>	<b><u>EXPLANATION OF NEEDED INFORMATION</u></b>
<b>A -</b>	Contract number for the material being tested, found in the Contract Plans or Special Provisions (EX. 3925)
<b>B -</b>	Project number for the material being tested, found in the Contract Plans or Special Provisions (EX. SI-0035(119))
<b>C -</b>	Field number for this particular sample in numerical order (EX. 1)
<b>D -</b>	County in which the sample is being used (EX. Washoe)
<b>E -</b>	Highway where the sample is being used (EX. I-80)
<b>F -</b>	Milepost where the sample is being used (EX. 10.50)
<b>G -</b>	Type of asphalt being sampled (EX. LMCRS-2h)
<b>H -</b>	Producer that is actually manufacturing the asphalt (EX. Idaho Asphalt) NOTE: Not where the material is stored
<b>I -</b>	Shipping Point where the asphalt was produced and is being shipped from (EX. Nampa Idaho)
<b>J -</b>	Actual tonage that this sample represents (EX. 35.7 tons) NOTE: Obtain a sample from the truck and trailer, test both the truck and trailer then submit one sample (either truck or trailer) to the Materials Lab for further testing
<b>K -</b>	Same as Bill of Lading Number provided by the delivery driver or contractor (EX. 00125695)
<b>L -</b>	Found on weigh scale certificate provided by the delivery driver or contractor (EX. 6526108)
<b>M -</b>	Found on the Bill of Lading provided by the delivery driver or contractor (EX. 456/456B)
<b>N -</b>	Prime contractor awarded the contract (EX. Granite Construction)
<b>O -</b>	Name of the certified truck driver who sampled the oil from the truck (Ex. Sam Weist - Truck Driver)
<b>P -</b>	Date the sample was taken (EX. 6/6/2014)

**020-016 Rev. 02/10**

**TRANSMITTAL FOR ASPHALT SAMPLES**

**LINE**

**EXPLANATION OF NEEDED INFORMATION**

- Q -** Person who observed the sample being taken (EX. Joe Bob)  
NOTE: If you did not observe the sampling being taken, write not observed
- R -** District where the sample is being used (EX. 2)
- S -** Maintenance Division to fill out
- T -** Emulsion field viscosity from Test Method Nev. T759 performed before the truck driver offloads the material on the jobsite (EX. 254)  
NOTE: Use the viscosity number for the same sample that is being submitted to the Materials Division
- U -** Printed first and last name of the certified tester who completed the test (EX. Joe Bob)

**NOTES:**

- 1.** When submitting a sample of diluted emulsion, you must indicate dilution ratio on Line G (EX. 60/40)
- 2.** Fold transmittal in half with the writing inside and attach with 2 small strips of masking tape. Seal transmittal in plastic envelope in case of inclement weather.
- 3.** Make sure outside of sample container is clean, DO NOT use any chemicals to clean the sample container. If sample container is not clean, have contractor take another sample.
- 4.** Samples shall be submitted ASAP to the Materials Lab. Samples must be tested within 14 days of sample date. If samples are received after the 14 days they can not be tested since they have exceeded their shelf life.

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION  
**TRANSMITTAL FOR CONCRETE SAMPLES**  
*(circle all units used)*

County \_\_\_\_\_ Contract \_\_\_\_\_  
Station / Structure No. / Item Constructed \_\_\_\_\_

\_\_\_\_\_  
\_\_\_\_\_  
Date placed \_\_\_\_\_ Time placed \_\_\_\_\_  
Mix Design No.(s) \_\_\_\_\_ Class of concrete \_\_\_\_\_  
Project specified strength \_\_\_\_\_ psi (Mpa) Mix design strength \_\_\_\_\_ psi (Mpa)  
Cylinder Set No. \_\_\_\_\_  
Brand of cement \_\_\_\_\_ Type \_\_\_\_\_  
Source of water \_\_\_\_\_  
Source of fine aggregate \_\_\_\_\_  
Source of coarse aggregate \_\_\_\_\_  
Source of fly ash \_\_\_\_\_  
lbs (kg) of cement as batched \_\_\_\_\_ per yd<sup>3</sup> (m<sup>3</sup>)  
lbs (kg) of fly ash as batched \_\_\_\_\_ per yd<sup>3</sup> (m<sup>3</sup>)  
lbs (kg) of fine agg. as batched \_\_\_\_\_ per yd<sup>3</sup> (m<sup>3</sup>)  
lbs (kg) of coarse agg. as batched \_\_\_\_\_ per yd<sup>3</sup> (m<sup>3</sup>)  
Total mixing water gals (L) \_\_\_\_\_ per yd<sup>3</sup> (m<sup>3</sup>)  
Water cement ratio as batched \_\_\_\_\_ Concrete temp \_\_\_\_\_ °F (°C)  
Slump \_\_\_\_\_ inches (mm) Unit weight \_\_\_\_\_ lbs/ft<sup>3</sup> (kg/m<sup>3</sup>)  
Slump \_\_\_\_\_ inches (mm) after addition of super plasticizer % Air \_\_\_\_\_  
Brand of air entraining agent used \_\_\_\_\_  
Brand of water reducer used \_\_\_\_\_  
Brand of super plasticizer \_\_\_\_\_  
Other additive(s) used \_\_\_\_\_  
Break at \_\_\_\_\_  
Sampled by \_\_\_\_\_  
Concrete supplied by \_\_\_\_\_  
Remarks \_\_\_\_\_

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION  
**TRANSMITTAL FOR CONCRETE SAMPLES**

*(circle all units used)*

A. County Lyon B. Contract 3925  
 C. Station / Structure No. / Item Constructed  
Sta "X" 7 + 22 rt. - N/A - Barrier Rail

---

D. Date placed 7/12/2010 E. Time placed 7:00 am  
 F. Mix Design No.(s) SDA145 G. Class of concrete DA Mod  
 H. Project specified strength 4000 (psi)(Mpa) I. Mix design strength 4000 (psi)(Mpa)  
 J. Cylinder Set No. 30  
 K. Brand of cement Lehigh Southwest L. Type Nevada Type II  
 M. Source of water Domestic  
 N. Source of fine aggregate Spanish Springs Pit  
 O. Source of coarse aggregate Spanish Springs Pit  
 P. Source of fly ash Bridger  
 Q. (lbs)(kg) of cement as batched 553 per(yd<sup>3</sup>)(m<sup>3</sup>)  
 R. (lbs)(kg) of fly ash as batched 160 per(yd<sup>3</sup>)(m<sup>3</sup>)  
 S. (lbs)(kg) of fine agg. as batched 1347 per(yd<sup>3</sup>)(m<sup>3</sup>)  
 T. (lbs)(kg) of coarse agg. as batched 1627 per(yd<sup>3</sup>)(m<sup>3</sup>)  
 U. Total mixing water gals (L) 30 per(yd<sup>3</sup>)(m<sup>3</sup>)  
 V. Water cement ratio as batched .35 W. Concrete temp 77 (°F)(°C)  
 X. Slump 4 (inches)(mm) Y. Unit weight 142.0 (lbs/ft<sup>3</sup>)(kg/m<sup>3</sup>)  
 Z. Slump N/A inches (mm) after addition of super plasticizer AA. % Air 6.0  
 BB. Brand of air entraining agent used MBAE90  
 CC. Brand of water reducer used Polyheed 997  
 DD. Brand of super plasticizer N/A  
 EE. Other additive(s) used Delvo  
 FF. Break at 1 @ 7, 1 @ 14 and 3 @ 28  
 GG. Sampled by Dexter Grant  
 HH. Concrete supplied by American Ready Mix  
 II. Remarks Field tests meet specs.

NDOT 020-017 (Rev. 3/08)

**TRANSMITTAL FOR CONCRETE SAMPLES**

**LINE**

**EXPLANATION OF NEEDED INFORMATION**

- A -** County in which the sample was taken (EX. Lyon)
- B -** Contract number for the material being tested, found in the Contract Plans or Special Provisions etc. (EX. 3925)
- C -** Station/Structure No./Item Constructed, approximate sample location found in the Contract Plans or jobsite survey stakes (EX. "X" 7 + 22 RT.); the number of the structure that is being worked on, found in the Contract Plans (EX. N/A); item being constructed, (found in the Contract Plans) (EX. Barrier Rail)
- D -** Date the sample was taken (EX. 07/12/2010)
- E -** Time the sample was taken (EX. 7:00 am)
- F -** Mix Design number that the sample represents (mix design approved by the Materials Division) (EX. SDA145)
- G -** Class of Concrete, found in the Standard Specifications, Special Provisions, or Contract Plans (EX. DA Mod)
- H -** Project specified strength, found in the Standard Specifications, Special Provisions, or Contract Plans and is written in Mpa if the contract is metric or psi if the contract is english (EX. 4000 psi) **NOTE:** If the mix design specifies 4000 psi then the specified strength has to meet 4000 psi even if the barrier rail only has to meet a 3000 psi
- I -** Mix design strength specified on the mix design (EX. 4000 psi)
- J -** Set number and the number of cylinders in the set (EX. Set 30, 5 of 5 cylinders) **NOTE:** Cylinders are consecutively numbered by mix design
- K -** Brand of cement, found on the approved mix design (EX. Lehigh Southwest)
- L -** Type of cement, found on the approved mix design (EX. Nevada Type II)
- M -** Source of water, found on the approved mix design (EX. Domestic) normally domestic or city, however the mix design should be checked in case a selected source is being used

**TRANSMITTAL FOR CONCRETE SAMPLES**

**LINE**

**EXPLANATION OF NEEDED INFORMATION**

- N -** Source of fine aggregate, found on the approved mix design from Materials Division (EX. Spanish Springs Pit)
- O -** Source of coarse aggregate, found on the approved mix design from Materials Division (EX. Spanish Springs Pit)
- P -** Source of fly ash, found on the approved mix design from Materials Division (EX. Bridger)
- Q -** Total weight of cement (found on delivery ticket) divided by  $m^3$  or  $yds^3$  of total concrete batched (found on delivery ticket) (EX.  $5530 \text{ lbs} / 10 \text{ yds}^3 = 553 \text{ lbs per yd}^3$ )
- R -** Total weight of fly ash (found on delivery ticket) divided by  $m^3$  or  $yds^3$  of total concrete batched (found on delivery ticket) (EX.  $1600 \text{ lbs} / 10 \text{ yds}^3 = 160 \text{ lbs per yd}^3$ )
- S -** Total weight of fine aggregate (found on delivery ticket) divided by  $m^3$  or  $yds^3$  of total concrete batched (found on delivery ticket) (EX.  $13470 \text{ lbs} / 10 \text{ yds}^3 = 1347 \text{ lbs per yds}^3$ )
- T -** Total weight of coarse aggregate (found on delivery ticket) divided by  $m^3$  or  $yds^3$  of total concrete batched (found on delivery ticket) (EX.  $16270 \text{ lbs} / 10 \text{ yds}^3 = 1627 \text{ lbs per yd}^3$ )
- U -** Total weight of water (found on delivery ticket) divided by  $m^3$  or  $yds^3$  of total concrete batched, (found on delivery ticket) **NOTE:** If water has been indicated in lbs on delivery ticket, divide by 8.33 (weight of one gallon of water) then divide by the total  $m^3$  or  $yds^3$  of concrete batched (EX.  $1999 \text{ lbs} / 8.33 = 240 / 10 \text{ yds}^3 = 24 \text{ gals per yd}^3$ )
- V -** Water cement ratio, Line U (Total weight of water: which includes any water measured into the batch plus any free water on the aggregate) x 8.33 (weight of 1 gallon of water) = 249.9 lbs of water; Line U (Total weight of water) / (Line Q (lbs of cement batched) + Line R (lbs of fly ash batched)) = water cement ratio (EX.  $30 \times 8.33 = 249.9 \text{ lbs}$ ,  $(249.9 / (553 + 160)) = .35$ ) **NOTE:** Refer to the Standard Specifications, Special Provisions, and mix design for the allowable tolerances on the water cement ratio
- W -** Temperature of the concrete, per Test Method Nev. T440 (EX.  $77^\circ\text{F}$ )
- X -** Slump results from Test Method Nev. T438 performed at time of sampling **NOTE:** Perform slump prior to the addition of plasticizer, if applicable (EX. 4)
- Y -** Unit weight results from Test Method Nev. T435, performed at time of sampling **NOTE:** Perform unit weight test after the addition of plasticizer, if applicable (EX. 142.0)



**TRANSMITTAL FOR CONCRETE SAMPLES**

**LINE**

**EXPLANATION OF NEEDED INFORMATION**

- Z -** Slump after plasticizer, results from Test Method Nev. T438, performed at time of sampling **NOTE:** Perform slump test after the addition of plasticizer, if applicable (EX. N/A)
- AA -** Air results from Test Method Nev. T435, performed at time of sampling (EX. 6.0) **NOTE:** Perform air test performed after the addition of plasticizer, if applicable
- BB -** Air entraining agent, found on mix design approved by Materials Division (EX. MBAE90)
- CC -** Water reducer, found on mix design approved by Materials Division (EX. Polyheed 997)
- DD -** Super plasticizer, found on mix design approved by Materials Division **NOTE:** Total of liters or ounces used divided by the m<sup>3</sup> or yds<sup>3</sup> of total concrete batched (EX. N/A)
- EE -** Other additives, found on mix design approved by Materials Division (EX. Delvo)
- FF -** Cylinder break schedule, check the Special Provisions for the correct days to break (usually 1 @ 7days, 1 @ 14 days and 3 @ 28 days)
- GG -** Sampled by, print first and last name of the tester or testers who actually fabricated the cylinders (EX. Dexter Grant)
- HH -** Concrete supplier that supplies the actual concrete being tested (EX. American Ready Mix)
- II -** Remarks, anything that needs to be documented (EX. Field tests meet specs.)

**NOTES:**

- 1.** Line F (Mix Design No.) - Prior to any concrete placement, review the Mix Design approved by the Materials Division.
- 2.** Line X (Slump before plasticizer) - If you have additives which are introduced in the field, you need to have a slump prior to the addition of those additives.

**TRANSMITTAL FOR CONCRETE SAMPLES**

**LINE**

**EXPLANATION OF NEEDED INFORMATION**

- 4.** Line Z (Slump after plasticizer) - If additives are not introduced in the field, this line will be N/A.
- 5.** Line FF ( Break at) - The break days must be reported or the strength tests will not be performed.

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION  
MATERIAL DIVISION

**TRANSMITTAL FOR TEST SAMPLES AND CERTIFICATIONS**

E.A. or Contract No.....Test No. or Sample No.....  
 Material description.....Batch No.....  
 Location or source of sample.....  
 Primary contractor.....  
 Producer.....  
 Limits of work represented by sample.....  
 .....  
 Quantity and Depth represented.....  
 Material is to be used for.....  
 .....  
 Tests needed on this material.....  
 Type and grade of asphalt to be used.....  
 Asphalt producer.....  
 Bin percentages.....  
 Bitumen Ratio (Target).....(Actual).....Lab mix design No. (BF).....  
 Remarks.....  
 .....  
 Sampled by (*Please Print*).....  
 Date sampled.....Date Shipped.....

Resident Engineer signature for mix design submittal:  
..... Signed.....

Distribution: White and Canary, to be inserted in plastic envelope and submitted with sample; Pink, sender's copy

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION  
MATERIAL DIVISION

**TRANSMITTAL FOR TEST SAMPLES AND CERTIFICATIONS**

A. E.A. of Contract No.....**3925**..... B. Test No. or Sample No.....**T-1-1**.....  
 C. Material description.....**Type 1B Aggregate Base**..... D. Batch No.....**N/A**.....  
 E. Location or source of sample.....**Granite Lockwood Stockpile**.....  
 F. Primary contractor.....**Granite Construction**.....  
 G. Producer.....**Granite Construction**.....  
 H. Limits of work represented by sample.....**As Per Plans**.....  
 .....  
 I. Quantity and Depth represented.....**25,000 tons**.....  
 J. Material is to be used for.....**Type 1B Aggregate Base**.....  
 .....  
 K. Tests needed on this material.....**Source Requirement Tests**.....  
 L. Type and grade of asphalt to be used.....**N/A**.....  
 M. Asphalt producer.....**N/A**.....  
 N. Bin Percentages.....**N/A**.....  
 O. Bitumen Ratio (Target).....**N/A**.....(Actual).....**N/A**..... P. Lab mix design No. (BF).....**N/A**.....  
 Q. Remarks.....**Tests meet specs for Sieve, P.I., L.L.**.....  
**James Fred (Granite Construction Co.) and Jerry Pine (NDOT R.E.) notified of results**.....  
 .....  
 R. Sampled by (*Please Print*).....**John Jones**.....  
 S. Date sampled.....**12/16/13**..... T. Date Shipped.....**12/17/13**.....  
 .....  
 U. Resident Engineer signature for mix design submittal:  
 .....**N/A**..... V. Signed.....*John Jones*.....

Distribution: White and Canary, to be inserted in plastic envelope and submitted with sample; Pink, sender's copy

**TRANSMITTAL FOR TEST SAMPLES AND  
CERTIFICATIONS**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>A -</b>	Contract number for the material being tested, found in the Contract Plans or Special Provisions (Ex. 3925)
<b>B -</b>	Acceptance test number for that particular test (Ex.T-1-1 T= Acceptance 1 = test, first acceptance test of the day, 1 = number of days material has been tested) <b>NOTE:</b> This is not the working day number
<b>C -</b>	Material type as specified in Standard Specifications, Contract Plans or Special Provisions (Ex. Type 1B Base Aggregate)
<b>D -</b>	N/A
<b>E -</b>	Location (Station) where sample was obtained. Or if sample was taken from the pit name of pit and from area taken. (Ex. Granite Lockwood Stockpile.)
<b>F -</b>	Prime Contractor awarded the contract. (Ex. Granite Construction)
<b>G -</b>	Contractor who produced and/or crushed the material. (Ex. Granite Construction)
<b>H-</b>	Limits of work represented by sample (Ex. As per plans)
<b>I -</b>	Total quantity of material that will be represented by this submittal (Ex. 25,000 tons)
<b>J -</b>	Whatever the contractor will be using the material for. (Ex. Type 1B Aggregate Base)
<b>K -</b>	Stated in the Standard Specifications, or Special Provisions (Ex. Source requirement tests)
<b>L -</b>	N/A
<b>M -</b>	N/A
<b>N -</b>	N/A
<b>O -</b>	N/A

**TRANSMITTAL FOR TEST SAMPLES AND  
CERTIFICATIONS**

<b><u>LINE</u></b>	<b><u>EXPLANATION OF NEEDED INFORMATION</u></b>
<b>P -</b>	N/A
<b>Q -</b>	Remarks, anything that needs to be documented (Ex. Tests meet specs. for sieve, P.I., L.L. James Fred (Granite Construction Co.) and Jerry Pine (NDOT R.E.) notified of results.
<b>R -</b>	Sampled By, print first and last name of the tester or testers who sampled the material (Ex. John Jones)
<b>S -</b>	Date the sample was taken (Ex. 12/16/2013)
<b>T-</b>	Date the sample left your possession (Ex. 12/17/2013)
<b>U -</b>	N/A
<b>V -</b>	Signature of person responsible for sampling, testing and submitting the sample (Ex. John Jones)

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION  
MATERIAL DIVISION

**TRANSMITTAL FOR TEST SAMPLES AND CERTIFICATIONS**

E.A. or Contract No.....Test No. or Sample No.....  
 Material description.....Batch No.....  
 Location or source of sample.....  
 Primary contractor.....  
 Producer.....  
 Limits of work represented by sample.....  
 .....  
 Quantity and depth represented.....  
 Material is to be used for.....  
 .....  
 Tests needed on this material.....  
 Type and grade of asphalt to be used.....  
 Asphalt producer.....  
 Bin percentages.....  
 Bitumen Ratio (Target).....(Actual).....Lab mix design No. (BF).....  
 Remarks.....  
 .....  
 Sampled by (*Please Print*).....  
 Date sampled.....Date Shipped.....

Resident Engineer signature for mix design submittal:  
..... Signed.....

Distribution: White and Canary, to be inserted in plastic envelope and submitted with sample; Pink, sender's copy

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION  
MATERIAL DIVISION

**TRANSMITTAL FOR TEST SAMPLES AND CERTIFICATIONS**

A. E.A. of Contract No.....**3925**..... B. Test No. or Sample No.....**T-1-2**.....  
 C. Material description.....**PBS Type 2C with RAP**..... D. Batch No.....**N/A**.....  
 E. Location or source of sample.....**"L"~155+25, #2 Lane, 1st Lift**.....  
 F. Primary contractor.....**Granite Construction**.....  
 G. Producer.....**Granite Construction**.....  
 H. Limits of work represented by sample.....**As Per Plans**.....  
 .....  
 I. Quantity and Depth represented.....**10,000 tons**.....  
 J. Material is to be used for.....**Mainline Paving of PBS Type 2C W/Rap**.....  
 .....  
 K. Tests needed on this material.....**Stability and Air Voids**.....  
 L. Type and grade of asphalt to be used.....**PG64-28NV**.....  
 M. Asphalt producer.....**Paramount Fernley**.....  
 N. Bin Percentages...**1"=25%, 1/2"=12%, 3/8"=10%, crushed fines=28%, Wads. Sand=10%, R.A.P.=15%**.....  
 O. Bitumen Ratio (Target).....**5.2%**.....(Actual).....**5.0%**..... P. Lab mix design No. ....**BF10-15**.....  
 Q. Remarks...**Sieve was out of spec on #10 sieve. James Fred (Granite Construction) and Jerry Pine ...**  
**(NDOT R.E.) notified of results**.....  
 .....  
 R. Sampled by (*Please Print*).....**John Jones**.....  
 S. Date sampled.....**12/16/13**..... T. Date Shipped.....**12/17/13**.....  
 .....  
 U. Resident Engineer signature for mix design submittal:  
 .....**N/A**..... V. Signed.....*John Jones*.....

Distribution: White and Canary, to be inserted in plastic envelope and submitted with sample; Pink, sender's copy



**TRANSMITTAL FOR TEST SAMPLES AND  
CERTIFICATIONS**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>A -</b>	Contract number for the material being tested, found in the Contract Plans or Special Provisions (Ex. 3925)
<b>B -</b>	Acceptance test number for that particular test (Ex.T-1-2 T= Acceptance test, 1 = first acceptance test of the day, 2 = number of days material has been tested) <b>NOTE:</b> This is not the working day number
<b>C -</b>	Material type as specified in the Standard Specifications, Contract Plans or Special Provisions (Ex. PBS Type 2C with Rap)
<b>D -</b>	N/A
<b>E -</b>	Location (Station) where sample was obtained from; route and milepost, station, etc.. (Ex. "L"~ 155+25, #2 lane, 1st lift)
<b>F -</b>	Prime Contractor awarded the contract (Ex. Granite Construction)
<b>G -</b>	Contractor producing the Plantmix (Ex. Granite Construction)
<b>H -</b>	Limits of work represented by sample (Ex. As per plans)
<b>I -</b>	Total quantity of material that will be represented by this submittal (Ex. 10,000 tons)
<b>J -</b>	Whatever the contractor will be using the material for (Ex. Mainline Paving PBS Type 2C/W Rap)
<b>K -</b>	Stated in the Standard Specifications, or Special Provisions (Ex. Stability and Air Voids)
<b>L -</b>	As stated in the Standard Specifications, Special Provisions, or mix design (Ex. PG64-28NV)
<b>M -</b>	Company that is actually producing the asphalt (Ex. Paramount Fernley) <b>NOTE:</b> Not where it is stored

**TRANSMITTAL FOR TEST SAMPLES AND  
CERTIFICATIONS**

<b><u>LINE</u></b>	<b><u>EXPLANATION OF NEEDED INFORMATION</u></b>
<b>N -</b>	Percentages of each stockpile should be taken from the most current JMF or Mix Design (Ex. 1"=25%, 1/2"=12%, 3/8"=10%, crushed fines = 28%, Wads. Sand=10%, RAP=15%)
<b>O -</b>	(Target) bitumen ratio from Mix Design or JMF (Ex. 5.2%) (Actual) bitumen ratio are results from Test Method Nev. T761
<b>P -</b>	Mix design number found on the mix design from the Materials Lab (Ex. BF10-15)
<b>Q -</b>	Anything that needs to be documented (Ex. Sieve was out of spec on the #10 sieve. James Fred (Granite Construction) and Jerry Pine (NDOT R.E.) notified of results.
<b>R -</b>	Sampled by, print first and last name of the tester or testers who completed the test (Ex. John Jones)
<b>S -</b>	Date the sample was taken (Ex. 12/16/13)
<b>T-</b>	Date the sample left your possession (Ex. 12/17/2013)
<b>U -</b>	N/A (NOTE: Only needed when submitting a mix design)
<b>V -</b>	Signature of person responsible for sampling, testing and submitting the sample (Ex. John Jones)

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION

**NUCLEAR GAUGE / SAND CONE CHECK TEST FORM**

Date \_\_\_\_\_  
Material Type \_\_\_\_\_  
Material Source \_\_\_\_\_

Contract No. \_\_\_\_\_  
Nuclear Set No. \_\_\_\_\_

**CORRELATION DATA**

Correlation Date	
Moisture Offset (MCF)	
Wet Density Offset	

**SINGLE CHECK TEST**      *(Every 25 Acceptance Tests with Offsets Enabled)*

Test No.	Sand Cone Wet Density	Nuclear Gauge Wet Density	Difference (±)

Maximum Deviation:  
(± 0.032 Mg/m<sup>3</sup> or ± 2.0 lb/ft<sup>3</sup> Allowable) \_\_\_\_\_

**MODIFIED PROCTOR COMPACTION TEST RESULTS**      *(Every 25 Acceptance Tests)*

Test No.	
Maximum Dry Density = (d) Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )	
Optimum Moisture %	

*(if applicable)*

Corr. Max. Dry Density = (D) Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )	
Corr. Optimum Moisture %	

Remarks: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Tested By: \_\_\_\_\_ Resident Engineer: \_\_\_\_\_

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION

**NUCLEAR GAUGE / SAND CONE CHECK TEST FORM**

A. Date 7/12/2010  
 B. Material Type Granular Backfill  
 C. Material Source Cinderlite - Goni Pit

D. Contract No. 3925  
 E. Nuclear Set No. 33

**CORRELATION DATA**

F. Correlation Date	<u>7/1/2010</u>
G. Moisture Offset (MCF)	<u>+ 6.55</u>
H. Wet Density Offset	<u>+ 2.3</u>

**SINGLE CHECK TEST** (Every 25 Acceptance Tests with Offsets Enabled)

I. Test No.	J. Sand Cone Wet Density	K. Nuclear Gauge Wet Density	L. Difference (±)
<b>60-SB-90</b>	<b>129.2</b>	<b>141.9</b>	<b>- 12.7 pcf</b>

M. Maximum Deviation:  
 (± 0.032 Mg/m<sup>3</sup> or ± 2.0 lb/ft<sup>3</sup> Allowable) - 12.7 pcf

**MODIFIED PROCTOR COMPACTION TEST RESULTS** (Every 25 Acceptance Tests)

N. Test No.	<b>60-SB-90</b>
O. Maximum Dry Density = (d) Mg/m <sup>3</sup> ( <u>lb/ft<sup>3</sup></u> )	<b>118.2</b>
P. Optimum Moisture %	<b>12.1</b>

*(if applicable)*

Q. Corr. Max. Dry Density = (D) Mg/m <sup>3</sup> ( <u>lb/ft<sup>3</sup></u> )	<b>124.3</b>
R. Corr. Optimum Moisture %	<b>10.9</b>

S. Remarks: **Check test failed to meet the maximum deviation tolerances and is no longer valid.**  
**Re-correlation of the moisture density gauge will be necessary. RE and Contractor notified**

T. Tested By: Leonard Cooper U. Resident Engineer: Howard Koothrappali

**NUCLEAR GAUGE / SAND CONE CHECK TEST FORM**

**LINE**

**EXPLANATION OF NEEDED INFORMATION**

- A -** Date the sample was taken (ex. 7/12/2010)
- B -** Material Type, as specified in the Contract Plans, or Special Provisions (ex. Granular Backfill)
- C -** Material Source, where the material was produced (ex. Cinderlite - Goni Pit)
- D -** Contract number for the material being tested, found in the Contract Plans or Special Provisions (ex. 3925)
- E -** Gauge Set number, assigned to the moisture density gauge that is used for testing the material (ex. 33)  
**NOTE:** Consultants shall use the serial number found on the back of the gauge
- F -** Correlation Date, will be the original date that the moisture density gauge correlation was performed on this material (ex. 07/1/2010)
- G -** Moisture Offset (MCF), that was established during the original moisture density gauge correlation (ex. + 6.55)
- H -** Wet Density Offset, that was established during the original moisture density gauge correlation (ex. + 2.3)
- I -** Test No., actual test number for this particular test. 60 is the number of tests ran on that material, SB represents the material being tested (refer to the Field Testing Guide - Part 1, for coding) and 90 is the minimum percent compaction required (Standard Specifications or Special Provisions) (ex. 60-SB-90)
- J -** Sand Cone Wet Density, determined per Test Method Nev. T102, from NDOT form 040-069 (ex. 129.2)
- K -** Nuclear Gauge Wet Density, determined per Test Method Nev. T103, from NDOT form 040-007, average of wet density (ex. 141.9)
- L -** Difference ( $\pm$ ), Line J (Sand Cone Wet Density) - Line K (Nuclear Gauge Wet Density) = Line L (Difference ( $\pm$ )) (ex. 129.2 - 141.9 = - 12.7 pcf)
- M -** Maximum Deviation, place Line L (Difference ( $\pm$ )) in this location, if the number is within  $\pm 0.032$  Mg/m<sup>3</sup> ( $\pm 2.0$  pcf), continue to use this moisture density gauge correlation (ex. - 12.7 pcf) If tolerances exceed, re-correlation shall be required

**NUCLEAR GAUGE / SAND CONE CHECK TEST FORM**

**LINE**

**EXPLANATION OF NEEDED INFORMATION**

- N -** Test No., actual test number for this particular test. 60 is the number of tests ran on that material, SB represents the material being tested (refer to the Field Testing Guide - Part 1, for coding) and 90 is the minimum percent compaction required (Standard Specifications or Special Provisions) (ex. 60-SB-90)
- O -** Maximum Dry Density = (d) Mg/m<sup>3</sup> (lb/ft<sup>3</sup>), the highest dry density as established per Test Method Nev. T108 from NDOT form 040-069 (ex. 118.2)
- P -** Optimum Moisture %, as established per Test Method Nev. T108 from NDOT form 040-069 (ex. 12.1)
- Q -** Corr. Max. Dry Density = (D) Mg/m<sup>3</sup> (lb/ft<sup>3</sup>), as established per test Method Nev. T108 from NDOT form 040-069 (ex. 124.3)
- R -** Corr. Optimum Moisture %, as established per Test Method Nev. T108 from NDOT form 040-069 (ex. 10.9)
- S-** Remarks, anything that needs to be documented (ex. Check test failed to meet the maximum deviation tolerances and is no longer valid. Re-correlation of the moisture density gauge will be necessary. RE and Contractor notified)
- T -** Tested By, printed first and last name of the tester or testers who completed the test (ex. Leonard Cooper)
- U -** Resident Engineer, or Assistant Resident Engineer signature on that specific crew verifying the accuracy of the reported results. (ex. Howard Koothrappali)

**NOTES:**

- 1.** If the maximum deviation specification is within tolerances, continue to use the gauge correlation using the new Proctor Curve Compaction and Check Test results.  
If the maximum deviation specification exceeds tolerances, re-correlation shall be required or use the referee method using Test Method Nev. T102.
- 2.** If the Check Test exceeds the maximum deviation specification and a new correlation is to be determined, it is permissible to use the failing Check Test as part of the new correlation process.
- 3.** Even though the Check Tests are required every twenty-five acceptance test, this is a minimum only and if anything is suspect additional Check Tests may be required.

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION

FIELD SAND EQUIVALENT WORKSHEET

DATE: \_\_\_\_\_

CONTRACT: \_\_\_\_\_

TESTER: \_\_\_\_\_

MATERIAL TYPE: \_\_\_\_\_

TEST NO. \_\_\_\_\_

CLAY READING \_\_\_\_\_ S.E.

SAND READING \_\_\_\_\_ S.E.

CLAY READING \_\_\_\_\_ S.E.

SAND READING \_\_\_\_\_ S.E.

CLAY READING \_\_\_\_\_ S.E.

SAND READING \_\_\_\_\_ S.E.

AVERAGE VALUES: \_\_\_\_\_ S.E.

TEST NO. \_\_\_\_\_

CLAY READING \_\_\_\_\_ S.E.

SAND READING \_\_\_\_\_ S.E.

CLAY READING \_\_\_\_\_ S.E.

SAND READING \_\_\_\_\_ S.E.

CLAY READING \_\_\_\_\_ S.E.

SAND READING \_\_\_\_\_ S.E.

AVERAGE VALUES: \_\_\_\_\_ S.E.

TEST NO. \_\_\_\_\_

CLAY READING \_\_\_\_\_ S.E.

SAND READING \_\_\_\_\_ S.E.

CLAY READING \_\_\_\_\_ S.E.

SAND READING \_\_\_\_\_ S.E.

CLAY READING \_\_\_\_\_ S.E.

SAND READING \_\_\_\_\_ S.E.

AVERAGE VALUES: \_\_\_\_\_ S.E.

TEST NO. \_\_\_\_\_

CLAY READING \_\_\_\_\_ S.E.

SAND READING \_\_\_\_\_ S.E.

CLAY READING \_\_\_\_\_ S.E.

SAND READING \_\_\_\_\_ S.E.

CLAY READING \_\_\_\_\_ S.E.

SAND READING \_\_\_\_\_ S.E.

AVERAGE VALUES: \_\_\_\_\_ S.E.

Resident Engineer: \_\_\_\_\_

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION

**FIELD SAND EQUIVALENT WORKSHEET**

A. DATE: 07/12/2010

C. CONTRACT: 3925

B. TESTER: Joe Tester

D. MATERIAL TYPE: Concrete Sand

E. TEST NO. T-1-113

TEST NO. \_\_\_\_\_

F. CLAY READING 4.6 H.  
82.6 83 S.E.

CLAY READING \_\_\_\_\_ S.E.

G. SAND READING 3.8

SAND READING \_\_\_\_\_ S.E.

I. CLAY READING 4.4 K.  
81.8 82 S.E.

CLAY READING \_\_\_\_\_ S.E.

J. SAND READING 3.6

SAND READING \_\_\_\_\_ S.E.

L. CLAY READING 4.3 N.  
81.4 82 S.E.

CLAY READING \_\_\_\_\_ S.E.

M. SAND READING 3.5

SAND READING \_\_\_\_\_ S.E.

O. AVERAGE VALUES: 82.3 83 S.E.

AVERAGE VALUES: \_\_\_\_\_ S.E.

TEST NO. \_\_\_\_\_

TEST NO. \_\_\_\_\_

CLAY READING \_\_\_\_\_ S.E.

CLAY READING \_\_\_\_\_ S.E.

SAND READING \_\_\_\_\_ S.E.

SAND READING \_\_\_\_\_ S.E.

CLAY READING \_\_\_\_\_ S.E.

CLAY READING \_\_\_\_\_ S.E.

SAND READING \_\_\_\_\_ S.E.

SAND READING \_\_\_\_\_ S.E.

CLAY READING \_\_\_\_\_ S.E.

CLAY READING \_\_\_\_\_ S.E.

SAND READING \_\_\_\_\_ S.E.

SAND READING \_\_\_\_\_ S.E.

AVERAGE VALUES: \_\_\_\_\_ S.E.

AVERAGE VALUES: \_\_\_\_\_ S.E.

P. Resident Engineer: Bob Resident



FIELD SAND EQUIVALENT WORKSHEET

LINE

EXPLANATION OF NEEDED MATERIAL

- A -** Date the sample was taken (EX. 07/12/2010)
- B -** Print first and last name of the tester or testers who completed the test (EX. Joe Tester)
- C -** Contract number for the material being tested, found in the Contract Plans or Special Provisions (EX. 3925)
- D -** Material Type as specified, found in the Contract Plans or Special Provisions (EX. Concrete Sand)
- E -** Test number for this particular test (EX. T-1-113, T = acceptance test; 1 = first acceptance test of the day; 113 = number of days the material has been tested  
**NOTE:** Test number shall correlate to the sieve being performed
- F -** Clay reading, level of clay suspension at the end of test specimen no. 1, per Test per Test Method Nev. T227 (EX. 4.6)
- G -** Sand reading, level of sand using the weighted foot assembly, for test specimen no. 1 per Test Method Nev. T227 (EX. 13.8 (reading) - 10" (per Test Method Nev. T227) = 3.8 (sand reading)
- H -** S.E., (Line G (sand reading) / Line F (clay reading)) x 100 = Line H (S.E.)  
(EX. (3.8 / 4.6) x 100 = 82.6 = 83.0) **NOTE:** Always round this number up to the next whole number
- I-** Clay reading, level of clay suspension at the end of test specimen no. 2, per Test Method Nev. T227 (EX. 4.4)
- J -** Sand reading, level of sand using the weighted foot assembly, for test specimen no. 2 per Test Method Nev. T227 (EX. 13.6 (reading) - 10" (per Test Method Nev. T227) = 3.6 (sand reading)
- K -** S.E., (Line J (sand reading) / Line I (clay reading)) x 100 = Line K (S.E.)  
(EX. (3.6 / 4.4) x 100 = 81.8 = 82.0) **NOTE:** Always round this number up to the next whole number
- L -** Clay reading, level of clay suspension at the end of test specimen, per Test Method Nev. T227 (EX. 4.3)

**FIELD SAND EQUIVALENT WORKSHEET**

**LINE**

**EXPLANATION OF NEEDED MATERIAL**

- M -** Sand reading, level of sand using the weighted foot assembly for test specimen no. 3, per Test Method Nev. T227 (EX. 13.5 (reading) - 10" (per Test Method Nev. T227) = 3.5 (sand reading)
- N -** S.E., (Line M (sand reading) / Line L (clay reading)) x 100 = Line N (S.E.)  
(EX. (3.5 / 4.3) x 100 = 81.4 = 82.0) **NOTE:** Always round this number up to the next whole number
- O -** Average value is the average of the three whole S.E. numbers recorded to the tenth. Cross out and record to the whole number. Line H (S.E.)+ Line K (S.E.) + Line N (S.E.) = Line O (Average Values) (EX. (83 + 82 + 82) / 3 = 82.3 = 83.0) **NOTE:** Always round this number up to the next whole number
- P -** Resident Engineer or the Assistant Resident Engineer signature on that specific crew (EX. Bob Resident)

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION

**NUCLEAR COMPACTION REPORT FOR SOILS AND AGGREGATES**

Daily Standard Counts	
Density	Moisture

Contract No. \_\_\_\_\_  
 Date \_\_\_\_\_  
 Nuclear Set No. \_\_\_\_\_  
 Correlation Date \_\_\_\_\_

Test No. (code)			
Station			
Distance to Centerline			
Embankment Depth			
Type of Material			
Compaction Equipment			

**WET DENSITY**

Probe Depth			
<b>Counts</b>	—	—	—
Wet Density #1 Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )			
Wet Density #2 Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )			
Wet Density #3 Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )			
Wet Density #4 Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )			
Average Wet Density Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )			

**MOISTURE AND MOISTURE %**

<b>Counts</b>	—	—	—
Moisture #1 Mg/m <sup>3</sup> (lb/ft <sup>3</sup> ) / M %			
Moisture #2 Mg/m <sup>3</sup> (lb/ft <sup>3</sup> ) / M %			
Moisture #3 Mg/m <sup>3</sup> (lb/ft <sup>3</sup> ) / M %			
Moisture #4 Mg/m <sup>3</sup> (lb/ft <sup>3</sup> ) / M %			
Avg. Moisture Mg/m <sup>3</sup> (lb/ft <sup>3</sup> ) / Avg. M %			

**CORRELATION DATA**

Moisture Offset (MCF)			
Wet Density Offset			

**MODIFIED PROCTOR COMPACTION TEST RESULTS**

Test No.			
Maximum Dry Density = (d) Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )			
Optimum Moisture %			

*(if applicable)*

Corr. Max. Dry Density = (D) Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )			
Corr. Optimum Moisture %			

**DRY DENSITY**

Dry Density #1 Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )			
Dry Density #2 Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )			
Dry Density #3 Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )			
Dry Density #4 Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )			
Average Dry Density Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )			
% Compaction Average			
Accepted or Rejected			

Remarks: \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

Tested By: \_\_\_\_\_ Resident Engineer: \_\_\_\_\_

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION

**NUCLEAR COMPACTION REPORT FOR SOILS AND AGGREGATES**

Daily Standard Counts	
Density	Moisture
<b>2202</b>	<b>B. 1070</b>

C. Contract No.	<u>3925</u>
D. Date	<u>7/12/2010</u>
E. Nuclear Set No.	<u>33</u>
F. Correlation Date	<u>7/1/2010</u>

G.	Test No. (code)	<b>60-SB-90</b>		
H.	Station	<b>"X" 7 + 22</b>		
I.	Distance to Centerline	<b>3.0' Lt</b>		
J.	Embankment Depth	<b>2.0' below finish grade</b>		
K.	Type of Material	<b>Granular Backfill</b>		
L.	Compaction Equipment	<b>Wacker</b>		

**WET DENSITY**

M.	Probe Depth	<b>4 in.</b>		
N.	Counts	<b>2164</b>	<b>2205</b>	<b>—</b>
O.	Wet Density #1 Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )	<b>141.9</b>		
P.	Wet Density #2 Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )	<b>141.8</b>		
Q.	Wet Density #3 Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )			
R.	Wet Density #4 Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )			
S.	Average Wet Density Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )	<b>141.9</b>		

**MOISTURE AND MOISTURE %**

T.	Counts	<b>231</b>	<b>241</b>	<b>—</b>	<b>—</b>
U.	Moisture #1 Mg/m <sup>3</sup> (lb/ft <sup>3</sup> ) / M %	<b>13.6</b>	<b>12.4</b>		
V.	Moisture #2 Mg/m <sup>3</sup> (lb/ft <sup>3</sup> ) / M %	<b>13.8</b>	<b>13.0</b>		
W.	Moisture #3 Mg/m <sup>3</sup> (lb/ft <sup>3</sup> ) / M %				
X.	Moisture #4 Mg/m <sup>3</sup> (lb/ft <sup>3</sup> ) / M %				
Y.	Avg. Moisture Mg/m <sup>3</sup> (lb/ft <sup>3</sup> ) / Avg. M %	<b>13.7</b>	<b>12.7</b>		

**CORRELATION DATA**

Z.	Moisture Offset (MCF)	<b>+ 6.55</b>		
AA.	Wet Density Offset	<b>+ 2.3</b>		

**MODIFIED PROCTOR COMPACTION TEST RESULTS**

BB.	Test No.	<b>60-SB-90</b>		
CC.	Maximum Dry Density = (d) Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )	<b>118.2</b>		
DD.	Optimum Moisture %	<b>12.1</b>		
	<i>(if applicable)</i>			
EE.	Corr. Max. Dry Density = (D) Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )	<b>124.3</b>		
FF.	Corr. Optimum Moisture %	<b>10.9</b>		

**DRY DENSITY**

GG.	Dry Density #1 Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )	<b>120.5</b>		
HH.	Dry Density #2 Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )	<b>121.2</b>		
II.	Dry Density #3 Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )			
JJ.	Dry Density #4 Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )			
KK.	Average Dry Density Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )	<b>120.9</b>		
LL.	% Compaction Average	<b>97</b>		
MM.	Accepted or Rejected	<b>A</b>		

NN. Remarks: Inspector and Contractor notified of passing results

---



---

OO. Tested By: Leonard Cooper PP. Resident Engineer: Howard Koothrappali

**NUCLEAR COMPACTION REPORTS FOR SOILS AND AGGREGATES**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>A -</b>	Density Standard Counts, (ex. 2202) <b>NOTE:</b> Standard gauge counts as determined at the beginning of each shift
<b>B -</b>	Moisture Standard Counts (ex. 1070) <b>NOTE:</b> Standard gauge counts as determined at the beginning of each shift
<b>C -</b>	Contract number for the material being tested, found in the Contract Plans or Special Provisions (ex. 3925)
<b>D -</b>	Date the test was performed (ex. 7/12/2010)
<b>E -</b>	Gauge Set number, assigned to the moisture density gauge that is used for testing the material (ex. 33) <b>NOTE:</b> Consultants shall use the serial number found on the back of the gauge
<b>F -</b>	Correlation Date, will be the original date that the moisture density gauge correlation was performed on this material (ex. 07/1/2010)
<b>G -</b>	Test No. (code), actual test number for this particular test. 60 is the number of tests ran on that material, SB represents the material being tested (refer to the Field Testing Guide - Part 1, for coding) and 90 is the minimum percent compaction required (Standard Specifications or Special Provisions) (ex. 60-SB-90)
<b>H -</b>	Station, approximate sample location, found in the Contract Plans or on the jobsite survey stakes (ex. "X" 7 + 22)
<b>I -</b>	Distance to Centerline, distance right or left of centerline that the compaction test was performed (ex. 3.0' Lt)
<b>J -</b>	Embankment Depth, depth at which the compaction test was taken (ex. 2.0' below finish grade) (Depth may also be found on the slope stakes or by using the elevation markers)
<b>K -</b>	Type of Material, as specified and found in the Contract Plans or Special Provisions (ex. Granular Backfill)
<b>L -</b>	Compaction Equipment, type of equipment used to compact the material (ex. Wacker)

**NUCLEAR COMPACTION REPORTS FOR SOILS AND  
AGGREGATES**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>M -</b>	Probe Depth, depth at which the gauge probe was set when the test was performed. (ex. 4 in.)
<b>N -</b>	Counts, wet density counts for first and second reading (ex. 2164 - 2205) <b>NOTE:</b> If the difference between the two counts is greater than 6% of the average, two additional 1 minute tests shall be immediately performed per Test Method Nev. T103
<b>O -</b>	Wet Density #1, reading obtained from the gauge (ex. 141.9)
<b>P -</b>	Wet Density #2, reading obtained from the gauge (ex. 141.8)
<b>Q -</b>	Wet Density #3, reading obtained from the gauge (Only necessary if the density counts exceed 6% per Test Method Nev. T103)
<b>R -</b>	Wet Density #4, reading obtained from the gauge (Only necessary if the density counts exceed 6% per Test Method Nev. T103)
<b>S -</b>	Avg. Wet Density, average of all wet density readings from the gauge Line O (Wet Density) + Line P (Wet Density) / 2 = Line S (Average Wet Density) (ex. $141.9 + 141.8 = 283.7 / 2 = 141.85 = 141.9$ )
<b>T -</b>	Counts, moisture and moisture % counts for first and second reading (ex. 231 - 241) <b>NOTE:</b> If the difference between the two counts is greater than 6% of the average, two additional 1 minute tests shall be immediately performed per Test Method Nev. T103
<b>U -</b>	Moisture #1, with two moisture numbers obtained from the gauge, the first value is the moisture reading the second value is the moisture %. (ex. 13.6 is the moisture reading and 12.4 is the moisture percent)
<b>V -</b>	Moisture #2, with two moisture numbers obtained from the gauge, the first value is the moisture reading the second value is the moisture %. (ex. 13.8 is the moisture reading and 13.0 is the moisture percent)
<b>W -</b>	Moisture #3, with two moisture readings obtained from the gauge (Only necessary if the moisture counts exceed 6% per Test Method Nev. T103)
<b>X -</b>	Moisture #4, with two moisture readings obtained from the gauge (Only necessary if the moisture counts exceed 6% per Test Method Nev. T103)

**NUCLEAR COMPACTION REPORTS FOR SOILS AND  
AGGREGATES**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>Y -</b>	Average Moisture, average of the moisture readings and % moistures. (Line U (Moisture) + Line V (Moisture)) / 2 = Line Y (Avg. Moisture) (ex. $13.6 + 13.8 = 27.4 / 2 = 13.7$ and $12.4 + 13.0 = 25.4 / 2 = 12.7$ )
<b>Z -</b>	Moisture Offset (MCF), number established from the gauge correlation, completed on NDOT form 040-026 (ex. + 6.55)
<b>AA -</b>	Wet Density Offset, number established from the gauge correlation, completed on NDOT form 040-026 (ex. + 2.3)
<b>BB -</b>	Test No., actual test number for this particular test. 60 is the number of tests ran on that material, SB represents the material being tested (refer to the Field Testing Guide - Part 1, for coding) and 90 is the minimum percent compaction required (Standard Specifications or Special Provisions) (ex. 60-SB-90)
<b>CC -</b>	Maximum Dry Density = (d) Mg/m <sup>3</sup> (lb/ft <sup>3</sup> ), the highest dry density as established per Test Method Nev. T108 from NDOT form 040-069 (ex. 118.2)
<b>DD -</b>	Optimum Moisture %, as established per Test Method Nev. T108 from NDOT form 040-069 (ex. 12.1)
<b>EE -</b>	Corr. Max. Dry Density = (D) Mg/m <sup>3</sup> (lb/ft <sup>3</sup> ), as established per test Method Nev. T108 from NDOT form 040-069 (ex. 124.3)
<b>FF -</b>	Corr. Optimum Moisture %, as established per Test Method Nev. T108 from NDOT form 040-069 (ex. 10.9)
<b>GG -</b>	Dry Density #1, reading obtained from the gauge. (ex. 120.5)
<b>HH -</b>	Dry Density #2, reading obtained from the gauge. (ex. 121.2)
<b>II -</b>	Dry Density #3, reading obtained from the gauge. (Only necessary if the density counts exceed 6% per Test Method Nev. T103)
<b>JJ -</b>	Dry Density #4, reading obtained from the gauge. (Only necessary if the density counts exceed 6% per Test Method Nev. T103)

**NUCLEAR COMPACTION REPORTS FOR SOILS AND AGGREGATES**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>KK -</b>	Average of Dry Density, Line GG (Dry Density) + Line HH (Dry Density) / 2 = Line KK (Average Dry Density) (ex. $120.5 + 121.2 = 241.7 / 2 = 120.9$ )
<b>LL -</b>	% Compaction Average, (Line KK (Average Dry Density) / Line EE (Corr. Max. Dry Density)) x 100 = Line LL (% Compaction Average) ex. $(120.9 / 124.3) \times 100 = 97\%$ Compaction) <b>NOTE:</b> If its been determined that per Test Method Nev. T108 a corrected maximum dry density is not applicable, Line KK / Line CC shall be used to determine % compaction.
<b>MM -</b>	Accepted or Rejected, if material passes compaction spec. write an "A" for accept, If material does not pass spec. write "R" for reject
<b>NN -</b>	Remarks, anything that needs to be documented (ex. Inspector and Contractor notified of passing results)
<b>OO -</b>	Tested by, printed first and last name of the tester or testers who completed the test (ex. Leonard Cooper)
<b>PP -</b>	Resident Engineer, or Assistant Resident Engineer signature on that specific crew verifying the accuracy of the reported results. (ex. Howard Koothrappali)

**NOTES:**

1. Any vertical edge over 6 inches is considered a trench as per the manufacturer. The trench correction factor offset should be used per the gauge operation manual.
2. All failures shall be circled in red.
3. If the compaction test fails to meet the minimum percent compaction a re-test shall be completed on the material per Test Method Nev. T103.



Date \_\_\_\_\_  
 Page \_\_\_\_\_ of \_\_\_\_\_ Pages  
 Report No. \_\_\_\_\_  
 Material Covered By Report \_\_\_\_\_  
 \_\_\_\_\_

STATE OF NEVADA  
 DEPARTMENT OF TRANSPORTATION  
**DAILY REPORT OF TESTS MADE IN THE FIELD**

Contract No. \_\_\_\_\_  
 Contractor \_\_\_\_\_  
 Spec. Reference \_\_\_\_\_  
 \_\_\_\_\_

Roadway Line									Specification Limit
Station									
Course (Lift)									
Source of Sample									
Acceptance Test No.									
Information Test No.									
SIEVE SIZES	% Passing	% Passing	% Passing	% Passing	% Passing	% Passing	% Passing	% Passing	
75 mm (3")									
63 mm (2 1/2")									
50 mm (2")									
37.5 mm (1 1/2")									
31.5 mm (1 1/4")									
25 mm (1")									
19 mm (3/4")									
12.5 mm (1/2")									
9.5 mm (3/8")									
4.75 mm (No. 4)									
2.36 mm (No. 8)									
2.00 mm (No. 10)									
1.18 mm (No. 16)									
600 µm (No. 30)									
425 µm (No. 40)									
150 µm (No. 100)									
75 µm (No. 200)									
Liquid Limit									
Plasticity Index									
% Fractured Face									
% Absorption									

**Please check box if sieve results are informational**

Quantity of Material Represented By Each Test: \_\_\_\_\_

Remarks: \_\_\_\_\_

Source of Materials: \_\_\_\_\_

Sampled By: \_\_\_\_\_

Tested By: \_\_\_\_\_

Resident Engineer: \_\_\_\_\_

A. Date 7/21/2010  
 B. Page 1 of 3 Pages  
 C. Report No. 1  
 D. Material Covered By Report \_\_\_\_\_  
Type I Class B Base

STATE OF NEVADA  
 DEPARTMENT OF TRANSPORTATION

E. Contract No. 3925  
 F. Contractor Granite Construction Co.  
 G. Spec. Reference \_\_\_\_\_  
704.03.03 and 704.02.03

**DAILY REPORT OF TESTS MADE IN THE FIELD**

H. Roadway Line	"X"								X. Specification Limit
I. Station	7 + 22								
J. Course (Lift)	1 <sup>ST</sup> Lift								
K. Source of Sample	Windrow								
L. Acceptance Test No.	T-1-1								
M. Information Test No.									
<b>N. SIEVE SIZES</b>	<b>% Passing</b>	<b>% Passing</b>	<b>% Passing</b>	<b>% Passing</b>	<b>% Passing</b>	<b>% Passing</b>	<b>% Passing</b>	<b>% Passing</b>	
75 mm (3")									
63 mm (2 1/2")									
50 mm (2")									
37.5 mm (1 1/2")	100								100
31.5 mm (1 1/4")	99								80 - 100
25 mm (1")									
19 mm (3/4")									
12.5 mm (1/2")									
9.5 mm (3/8")									
4.75 mm (No. 4)	46								30 - 65
2.36 mm (No. 8)									
2.00 mm (No. 10)									
1.18 mm (No. 16)	22								15 - 40
600 µm (No. 30)									
425 µm (No. 40)									
150 µm (No. 100)									
75 µm (No. 200)	7								2 - 12
O. Liquid Limit	27								35 MAX
P. Plasticity Index	4								6 MAX
Q. % Fractured Face	90								15% MIN
R. % Absorption									

S.  Please check box if sieve results are informational

T. Quantity of Material Represented By Each Test: 2000 Tons

Y. Remarks: Test met specs. James Fred (Granite Construction Co.)

U. Source of Materials: Cinderlite - Goni Pit

and Jerry Pine (NDOT R.E.) notified of results.

V. Sampled By: Jane Doe

W. Tested By: Jon Doe

Z. Resident Engineer: Jerry Pine

**040-010 Rev. 02/09**

**DAILY REPORT OF TESTS MADE IN THE FIELD**

**LINE**

**EXPLANATION OF NEEDED INFORMATION**

- A-** Date the sample was taken (EX. 7/21/2010)
- B-** Page, total number of all pages turned in together for this material being tested (EX. 1 of 3) Includes NDOT forms 040-010, 040-013 and 040-014
- C-** Report No., consecutive numbering starting at 1 and continuing through the last report for this material (EX. 1) Refer to the Field Testing Guide - Part 1, for the correct numbering procedures for a particular material or deposit
- D-** Material Covered by Report, material type as specified, found in the Contract Plans or Special Provisions. (EX. Type I Class B Base)
- E-** Contract number for the material being tested, found in the Contract Plans or Special Provisions (EX. 3925)
- F-** Prime Contractor awarded the contract (EX. Granite Construction Co.)
- G-** Specification Reference, all of the specifications that apply to the material being tested, refer to the Standard Specifications and Special Provisions (EX. 704.03.03 and 704.02.03)
- H-** Roadway Line designation found in the Contract Plans (EX. "X")
- I-** Station, approximate sample location, found in the Contract Plans or on jobsite survey stakes (EX. 7 + 22)
- J-** Course or Lift of the sample being taken (EX. 1<sup>st</sup> Lift)
- K-** Source of sample, exact area the sample was taken from (EX. Windrow)
- L-** Acceptance test number for that particular test (EX. T-1-1 T = Acceptance Test, 1 = first acceptance test of the day, 1 = number of days material has been tested)  
NOTE: This is not the working day number
- M-** Informational Test Number, identified the same as acceptance test but with an ( I ) for informational. (EX. N/A)
- N -** Sieve sizes % passing, number representing the % passing for each appropriate sieve, taken from NDOT form 040-013 and reported to the whole number on this form. (EX. 100, 99, 46, 22, 7)

**040-010 Rev. 02/09**

**DAILY REPORT OF TESTS MADE IN THE FIELD**

<b><u>LINE</u></b>	<b><u>EXPLANATION OF NEEDED INFORMATION</u></b>
<b>O-</b>	Liquid Limit, number achieved by the completion of Test Method Nev. T210 reported on NDOT form 040-014 and reported to the whole number on this form (EX. 27)
<b>P-</b>	Plasticity Index, number achieved by the completion of Test Method Nev. T212 reported on NDOT form 040-014 and reported to the whole number on this form (EX. 4)
<b>Q-</b>	% Fractured Face, number achieved by the completion of Test Method Nev. T230 reported on NDOT form 040-013 and reported to the whole number on this form (EX. 90)
<b>R -</b>	% Absorption, number achieved by the completion of Test Method Nev. T111 or T493 and reported on NDOT form 040-023 and reported to nearest 0.1 (EX. N/A)
<b>S -</b>	Check this box if the sieve is an informational test but, the liquid limit, plasticity index, % fractured face, and absorption are acceptance tests, Line L will be used for the acceptance test number <b>NOTE:</b> Used primarily for plantmix aggregates
<b>T -</b>	Quantity of material represented by this sample. Refer to the Minimum Required Samples and Tests Project in the Field Testing Guide - Part 2 (EX. 2000 Tons)
<b>U -</b>	Source of Materials, name of the source where the material was produced (EX. Cinderlite - Goni Pit)
<b>V -</b>	Sampled By, print first and last name of the tester or testers who sampled the material (EX. Jane Doe)
<b>W -</b>	Tested By, print first and last name of the tester or testers who completed the test (EX. Jon Doe)
<b>X -</b>	Specification Limit requirements of the material being tested, found in the Standard Specifications or Special Provisions
<b>Y -</b>	Remarks, anything that needs to be documented (EX. Test met specs. James Fred (Granite Construction Co.) and Jerry Pine (NDOT R.E.) notified of results)
<b>Z -</b>	Resident Engineer or Assistant Resident Engineer signature on that specific crew (EX. Jerry Pine)

**040-010 Rev. 02/09**

**DAILY REPORT OF TESTS MADE IN THE FIELD**

**LINE**

**EXPLANATION OF NEEDED INFORMATION**

**NOTE:**

- 1.** All failures shall be circled in red.

A. Date 7/21/2010  
 B. Page 1 of 9 Pages  
 C. Report No. 1  
 D. Material Covered By Report \_\_\_\_\_  
Type 2C PBS Aggregates

STATE OF NEVADA  
 DEPARTMENT OF TRANSPORTATION

E. Contract No. 3925  
 F. Contractor Granite Construction Co.  
 G. Spec. Reference \_\_\_\_\_  
705.03.01

**DAILY REPORT OF TESTS MADE IN THE FIELD**

H. Roadway Line								X. Specification Limit
I. Station								
J. Course (Lift)	1" Rock	3/4" Rock	Crusher Fines	Washed Sand				
K. Source of Sample	Stockpile	Stockpile	Stockpile	Stockpile				
L. Acceptance Test No.	T-1-1	T-1-1	T-1-1	T-1-1				
M. Information Test No.								
N. SIEVE SIZES	% Passing	% Passing	% Passing	% Passing	% Passing	% Passing	% Passing	
75 mm (3")								
63 mm (2 1/2")								
50 mm (2")								
37.5 mm (1 1/2")	100							
31.5 mm (1 1/4")								
25 mm (1")	99	100	100	100				
19 mm (3/4")	68	100	100	100				
12.5 mm (1/2")	10	82	100	100				
9.5 mm (3/8")	3	46	100	100				
4.75 mm (No. 4)	2	4	86	100				
2.36 mm (No. 8)								
2.00 mm (No. 10)	2	2	45	98				
1.18 mm (No. 16)	2	2	33	80				
600 µm (No. 30)								
425 µm (No. 40)	2	2	20	39				
150 µm (No. 100)	1	2	11	9				
75 µm (No. 200)	1	1	8	3				
O. Liquid Limit	26	25	19	N/A			35 Max	
P. Plasticity Index	7	5	1	NP			10 Max	
Q. % Fractured Face	100	100	N/A	N/A			80% Min	
R. % Absorption	0.9	1.2	N/A	N/A			4% Max	

S.  Please check box if sieve results are informational

T. Quantity of Material Represented By Each Test: 5000 Tons

Y. Remarks: Tests for liquid limit, plasticity, % fractured face

U. Source of Materials: Hunewill Pit Stockpile, Thomas Canyon

and % absorption met specs. R.E. and Contractor

V. Sampled By: Fred Flintstone

notified of results.

W. Tested By: Wilma Flintstone

Z. Resident Engineer: Royce James

**040-010 Rev. 02/09**

**DAILY REPORT OF TESTS MADE IN THE FIELD**

<b><u>LINE</u></b>	<b><u>EXPLANATION OF NEEDED INFORMATION</u></b>
<b>A-</b>	Date the sample was taken (EX. 7/21/2010)
<b>B-</b>	Page, total number of all pages turned in together for this material being tested (EX. 1 of 9) includes NDOT forms 040-010, 040-013, 040-014 and 040-023
<b>C-</b>	Report No., consecutive numbering starting at 1 and continuing through the last report for this material (EX. 1) Refer to the Field Testing Guide - Part 1, for the correct numbering procedures for a particular material or deposit
<b>D-</b>	Material Covered By Report, material type as specified, found in the Contract Plans or Special Provisions (EX. Type 2C PBS Aggregates)
<b>E-</b>	Contract number for the material being tested, found in the Contract Plans or Special Provisions (EX. 3925)
<b>F-</b>	Prime Contractor awarded the contract (EX. Granite Construction Co.)
<b>G-</b>	Specification Reference, all of the specifications that apply to the material being tested, refer to the Standard Specifications and Special Provisions (EX. 705.03.01)
<b>H-</b>	Roadway Line designation found in the Contract Plans (EX. N/A)
<b>I-</b>	Station, approximate sample location, found in the contract plans or on jobsite survey stakes (EX. N/A)
<b>J-</b>	Course or Lift of the sample being taken (Note: For plantmix aggregates put the material type (EX. 1" Rock, 3/4" Rock, Crusher Fines, Washed Sand)
<b>K-</b>	Source of Sample, exact area the sample was taken from (EX. Stockpile)
<b>L-</b>	Acceptance test number for that particular test (EX. T-1-1 T = Acceptance Test, 1 = first acceptance test of the day, 1 = number of days material has been tested) <b>NOTE:</b> This is not the working day number
<b>M-</b>	Informational Test Number, identified the same as acceptance test but with an ( I ) for informational. (EX. N/A)
<b>N -</b>	Sieve Sizes % Passing, number representing the % passing for each sieve, taken from NDOT form 040-013 and reported to the whole number (EX. 100, 99, 68, 10, 3, 2, 2, 2, 1, 1)

**040-010 Rev. 02/09**

**DAILY REPORT OF TESTS MADE IN THE FIELD**

<b><u>LINE</u></b>	<b><u>EXPLANATION OF NEEDED INFORMATION</u></b>
<b>O-</b>	Liquid Limit, number achieved by the completion of Test Method Nev. T210 reported on NDOT form 040-014 and reported to the whole number on this form (EX. 26, 25, 19, N/A)
<b>P-</b>	Plasticity Index, number achieved by the completion of Test Method Nev. T212 reported on NDOT form 040-014 and reported to the whole number on this form (EX. 7, 5, 1, NP)
<b>Q-</b>	% Fractured Face, number achieved by the completion of Test Method Nev. T230 reported on NDOT form 040-013 and reported to the whole number on this form (EX. 100, 100, N/A, N/A)
<b>R -</b>	% Absorption, number achieved by the completion of Test Method Nev. T111 and reported on NDOT form 040-023 and reported to nearest 0.1 (EX. 0.9, 1.2, N/A, N/A)
<b>S -</b>	Check this box if the sieve is an informational test but the liquid limit, plasticity index, % fractured face, and absorption are acceptance tests, Line L will be used for the acceptance test number <b>NOTE:</b> Used primarily for plantmix aggregates
<b>T -</b>	Quantity of material represented by this sample. Refer to the Minimum Required Samples and Tests - Project in the Field Testing Guide - Part 2 (EX. 5000 Tons)
<b>U -</b>	Source of Materials, name of the source where the material was produced (EX. Hunewill Pit Stockpile, Thomas Canyon)
<b>V -</b>	Sampled By, Print first and last name of the tester or testers who sampled the material (EX. Fred Flintstone)
<b>W -</b>	Tested By, print first and last name of the tester or testers who completed the test (EX. W. Flintstone)
<b>X -</b>	Specification Limit requirements of the material being tested, found in the Standard Specifications or Special Provisions
<b>Y -</b>	Remarks, anything that needs to be documented (EX. Tests for liquid limit, plasticity limit, % fractured face and % absorption met specs. R.E. and contractor notified of results)
<b>Z -</b>	Resident Engineer or Assistant Resident Engineer signature on that specific crew (EX. Royce James)







**040-011 Rev. 10/17**

**DAILY PLANT REPORT OF ASPHALT MIXTURES**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>A -</b>	Page, total number of pages turned in together for this material being tested (EX. Page 1 of 3) NDOT forms 040-011, 040-013 and 040-050
<b>B -</b>	Report No., consecutive numbering starting with 1 and continuing on for every day plantmix is produced and placed on the jobsite (EX. 1) NOTE: Number sequence will start over with a new source and with a different material, such as PBS Type III, 3/8" Opengrade etc.
<b>C -</b>	Contract number for the material being tested, found in the Contract Plans or Special Provisions (EX. 3925)
<b>D -</b>	Contractor awarded the contract (EX. Granite Construction)
<b>E -</b>	Date the sample was taken (EX. 10/2/2017)
<b>F -</b>	Tested by, Print name of the tester(s) who sampled and/or completed the tests (EX. Stew Simon)
<b>G -</b>	Specification References, all of the specifications that apply to the material being tested, refer to the Standard Specifications and Special Provisions etc. (EX. 705.03.01, 401.03.09, 401.02.02)
<b>H -</b>	Mix Design Number assigned by the Materials Division for this specific material. (Example: BF 17-01)
<b>I -</b>	Type of mix, material being tested (EX. Type 2 PBS)
<b>J -</b>	Job-Mix Formula No., The number of the most current job-mix formula, written by the Resident Engineer. (EX.: 2)
<b>K -</b>	Job-Mix bitumen ratio, found on the current job-mix formula (EX. 5.3%)
<b>L -</b>	Sample Number, actual test number for this particular test (EX. T-1-1 T = test, 1 = first acceptance test, 1 = first acceptance test of the day, 1 = number of days the material has been tested) NOTE: This is not the working day number
<b>M -</b>	Bitumen Ratio from the results of the ignition furnace (from the printed ticket), per Test Method Nev. T761 (EX. 5.5), reported to the nearest 0.1.

**040-011 Rev. 10/17**

**DAILY PLANT REPORT OF ASPHALT MIXTURES**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>N -</b>	% Moisture (belt), taken from the cold feed sample, from the belt at the hotplant, during plantmix production. Reported on NDOT form 040-011 and 040-013 (EX. 4.1)
<b>O -</b>	% Moisture (mix), from the complete mix, taken from behind the paver, per Test Method Nev. T306 (EX. 0.18)
<b>P -</b>	Percent passing the 1" sieve to the nearest whole number from NDOT form 040-050 (EX. 100)
<b>Q -</b>	Percent passing the 3/4" sieve to the nearest whole number from NDOT form 040-050 (EX. 93)
<b>R -</b>	Percent passing the 1/2" sieve to the nearest whole number from NDOT form 040-050 (EX. N/A)
<b>S -</b>	Percent passing the 3/8" sieve to the nearest whole number from NDOT form 040-050 (EX. 66)
<b>T -</b>	Percent passing the No. 4 sieve to the nearest whole number from NDOT form 040-050 (EX. 48)
<b>U -</b>	Percent passing the No. 10 sieve to the nearest whole number from NDOT form 040-050 (EX. 32)
<b>V -</b>	Percent passing the No. 16 sieve to the nearest whole number from NDOT form 040-050 (EX. N/A)
<b>W -</b>	Percent passing the No. 40 sieve to the nearest whole number from NDOT form 040-050 (EX. 15)
<b>X -</b>	Percent passing the No. 200 sieve to the nearest whole number from NDOT form 040-050 (EX. 6)
<b>Y -</b>	Job-Mix Range, allowable tolerances for the bitumen ratio and individual sieves, found on the Job-mix formula (EX. 4.9 - 5.7 job-mix range for the Bitumen Ratio and the job-mix range for the sieves)
<b>Z -</b>	Specification Limits, allowable tolerances for the bitumen ratio, percent moisture of the complete mix and the sieve analysis, found in the Standard Specifications or the Special Provisions

**040-011 Rev. 10/17**

**DAILY PLANT REPORT OF ASPHALT MIXTURES**

**LINE**

**EXPLANATION OF NEEDED INFORMATION**

**AA -** Remarks, anything that needs to be documented that pertains to the testing of this sample (EX. Tests meet specs, Resident Engineer, Inspector and Contractor notified.)

**BB -** Resident Engineer or Assistant Resident Engineer signature on that specific crew (EX. R. John)

**NOTES:**

- 1.** Circle all applicable units
- 2.** Line L - There are no re-tests for plantmix, a failure is a failure
- 3.** Line AA - Write down what transpires with a failing test (EX. left in place, contractor removed etc.) have the Resident Engineer initial the remark.

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION  
**FIELD MATERIAL SIEVE SHEET**

CONTRACT NO. \_\_\_\_\_  
MATERIAL \_\_\_\_\_  
DATE \_\_\_\_\_

Test No.					Test No.					Test No.					Checked By	
Size or Type		Mix %			Size or Type		Mix %			Size or Type		Mix %				
Sampled by					Sampled by					Sampled by					_____	
Tested by					Tested by					Tested by						
Source					Source					Source					_____	
Weights-Moisture	Weights-Wash	Weights-Frac. Face			Weights-Moisture	Weights-Wash	Weights-Frac. Face			Weights-Moisture	Weights-Wash	Weights-Frac. Face				
Moisture %		Frac. Face %			Moisture %		Frac. Face %			Moisture %		Frac. Face %				
LL		PI			LL		PI			LL		PI				
Sieve Sizes	Weight Ret.	% Ret.	% Pass	Specs. Or % Pass	Sieve Sizes	Weight Ret.	% Ret.	% Pass	Specs. Or % Pass	Sieve Sizes	Weight Ret.	% Ret.	% Pass	Specs. Or % Pass	Sum of %'s used	Specs. Or % Pass
75 mm (3")					75 mm (3")					75 mm (3")						
63 mm (2½")					63 mm (2½")					63 mm (2½")						
50 mm (2")					50 mm (2")					50 mm (2")						
37.5 mm (1½")					37.5 mm (1½")					37.5 mm (1½")						
31.5 mm (1¼")					31.5 mm (1¼")					31.5 mm (1¼")						
25 mm (1")					25 mm (1")					25 mm (1")						
19 mm (¾")					19 mm (¾")					19 mm (¾")						
12.5 mm (½")					12.5 mm (½")					12.5 mm (½")						
9.5 mm (⅜")					9.5 mm (⅜")					9.5 mm (⅜")						
4.75 mm (No. 4)					4.75 mm (No. 4)					4.75 mm (No. 4)						
2.36 mm (No. 8)					2.36 mm (No. 8)					2.36 mm (No. 8)						
2.00 mm (No. 10)					2.00 mm (No. 10)					2.00 mm (No. 10)						
1.18 mm (No. 16)					1.18 mm (No. 16)					1.18 mm (No. 16)						
600 µm (No. 30)					600 µm (No. 30)					600 µm (No. 30)						
425 µm (No. 40)					425 µm (No. 40)					425 µm (No. 40)						
300 µm (No. 50)					300 µm (No. 50)					300 µm (No. 50)						
150 µm (No.100)					150 µm (No.100)					150 µm (No.100)						
75 µm (No. 200)					75 µm (No. 200)					75 µm (No. 200)						
Pan					Pan					Pan						
Wash					Wash					Wash						

Remarks: \_\_\_\_\_

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION  
FIELD MATERIAL SIEVE SHEET

Z. CONTRACT NO 3925

AA. MATERIAL Type I Class B Base Agg.

BB. DATE 7/21/2010

<b>A. Test No. T-1-1</b>					Test No.					Test No.						
<b>B. Size or Type Type IB</b>			<b>C. Mix %</b>		Size or Type			Mix %		Size or Type			Mix %			
<b>D. Sampled by Jane Doe</b>					Sampled by					Sampled by						
<b>E. Tested by Jon Doe</b>					Tested by					Tested by						
<b>F. Source Processed Windrow</b>					Source					Source						
Weights-Moisture		Weights-Wash		Weights-Frac. Face	Weights-Moisture		Weights-Wash		Weights-Frac. Face	Weights-Moisture		Weights-Wash		Weights-Frac. Face		
<b>G. 2661</b>		<b>K. 2411</b>		<b>N. 1303</b>												
<b>H. 2411</b>		<b>L. 2251</b>		<b>O. 1172</b>												
<b>I. 250</b>		<b>M. 160</b>		<b>P. 131</b>												
<b>J. Moisture 10.4 %</b>			<b>Q. Frac. Face 89.9 %</b>		Moisture %			Frac. Face %		Moisture %			Frac. Face %			
<b>R. LL 26.7</b>			<b>S. PI 4.4</b>		LL			PI		LL			PI			
Sieve	Weight	%	%	Specs. Or	Sieve	Weight	%	%	Specs. Or	Sieve	Weight	%	%	Specs. Or	Sum of	Specs. Or
T. Sizes	U. Ret.	V. Ret.	W. Pass	X. % Pass	Sizes	Ret.	Ret.	Pass	% Pass	Sizes	Ret.	Ret.	Pass	% Pass	%s used	% Pass
75 mm (3")					75 mm (3")					75 mm (3")						
63 mm (2½")					63 mm (2½")					63 mm (2½")						
50 mm (2")					50 mm (2")					50 mm (2")						
37.5 mm (1½")	0	0.0%	100.0%	100	37.5 mm (1½")					37.5 mm (1½")						
31.5 mm (1¼")	0	0.0%	100.0%		31.5 mm (1¼")					31.5 mm (1¼")						
25 mm (1")	34	1.4%	98.6%	80 - 100	25 mm (1")					25 mm (1")						
19 mm (¾")	103	4.3%	94.3%		19 mm (¾")					19 mm (¾")						
12.5 mm (½")	415	17.2%	77.1%		12.5 mm (½")					12.5 mm (½")						
9.5 mm (⅜")	225	9.3%	67.8%		9.5 mm (⅜")					9.5 mm (⅜")						
4.75 mm (No. 4)	526	21.9%	24.8%	46.0%	30 - 65	4.75 mm (No. 4)				4.75 mm (No. 4)						
2.36 mm (No. 8)	358	14.8%	31.1%		2.36 mm (No. 8)					2.36 mm (No. 8)						
2.00 mm (No. 10)					2.00 mm (No. 10)					2.00 mm (No. 10)						
1.18 mm (No. 16)	222	9.2%	21.9%	15 - 40	1.18 mm (No. 16)					1.18 mm (No. 16)						
600 µm (No. 30)	126	5.2%	16.7%		600 µm (No. 30)					600 µm (No. 30)						
425 µm (No. 40)					425 µm (No. 40)					425 µm (No. 40)						
300 µm (No. 50)	96	4.0%	12.7%		300 µm (No. 50)					300 µm (No. 50)						
150 µm (No.100)	81	3.4%	9.3%		150 µm (No.100)					150 µm (No.100)						
75 µm (No. 200)	56	2.3%	7.0%	2 - 12	75 µm (No. 200)					75 µm (No. 200)						
Pan	9	0.4%	6.6%		Pan					Pan						
Wash	160	6.6%			Wash					Wash						

CC. Checked By

378

Y. Remarks: **Test met specs. RE and Contractor notified of results.**

**040-013 Rev. 11/10**

**FIELD MATERIAL SIEVE SHEET**

**LINE**

**EXPLANATION OF NEEDED MATERIAL**

- A -** Test number for this particular test. (EX. T-1-1 T = Acceptance Test, 1 = first acceptance test of the day, 1 = number of days the material has been tested)  
NOTE: If informational, test would be I-1-1 I = Informational Test, 1 = first informational test of the day, 1 = number of days the material has been tested
- B -** Size or Type of material being tested (EX. Type 1B)
- C -** Mix %, percentage of material used for plantmix aggregate or concrete aggregates (EX. N/A)
- D -** Print first and last name of the tester or testers who sampled the material (EX. Jane Doe)
- E -** Print first and last name of the tester or testers who completed the test (EX. Jon Doe)
- F -** Source, name of the location where the sample was taken (EX. Processed Windrow)
- G -** Weights - Moisture, wet weight of the material after the sample has been split, per Test Method Nev. T203, weighed to the nearest whole number in grams (EX. 2661)
- H -** Total dry weight of the material after drying per Test Method Nev. T112, weighed to nearest whole number (EX. 2411)
- I -** Line G (wet weight) - Line H (dry weight) = Line I ((EX. 2661 - 2411 = 250)
- J -** Moisture, Line G (wet weight) - Line H (dry weight) / Line H (dry weight) x 100 = Line J (moisture %) (EX. (2661 - 2411) / 2411 x 100 = 10.4)
- K -** Weights - Wash, total dry weight of the material after drying per Test Method Nev. T112 (weighed to the nearest whole number) (EX. 2411) NOTE: This number will be the same as Line H
- L -** Dry weight of the material after it has been washed, per Test Method Nev. T206 (weighed to the nearest whole number) (EX. 2251)
- M -** Line K (dry weight) - Line L (washed dry weight) = Line M (minus No. 200 wash weight) (EX. 2411 - 2251 = 160 washed through the No. 200 sieve) NOTE: The total dry weight in the pan after shaking should not exceed 1% of the total dry weight or the test is invalid



**040-013 Rev. 11/10**

**FIELD MATERIAL SIEVE SHEET**

**LINE**

**EXPLANATION OF NEEDED MATERIAL**

- N -** Weights - Frac. Face, weight of the material retained on the No. 4 sieve and larger screens, per Test Method Nev. T230, weighed to the nearest whole number (EX. 1303)
- O -** Weight of the fractured aggregate per Test Method Nev. T230 (EX. 1172)
- P -** Line N (total weight of all No. + 4 and up material) - Line O (weight of fractured material) = Line P (weight of unfractured material) (EX. 1303 - 1172 = 131)
- Q -** Frac. Face %, Line O (weight of the fractured aggregate) / Line N (total weight of all No. + 4 material and up) x 100 = Line Q (percent fractured face) (EX. 1172 / 1303 x 100 = 89.9%) Refer to the Special Provisions or Standard Specifications to see if the fractured face is required
- R -** Liquid Limit result that was reported on NDOT form 040-014, per Test Method Nev. T210 (EX. 26.7)
- S -** Plasticity Index result that was reported on NDOT form 040-014, per Test Method Nev. T212 (EX. 4.4)
- T -** Sieves that are on the stack. Refer to the Special Provisions and Standard Specifications for the required specifications of the material being tested
- U -** Weight Ret., weight retained on each sieve in the stack weighed to the nearest whole number **NOTE:** All of column U (Weight Ret.) shall add up to Line K (dry weight), if it does not, adjust the highest weight retained in column U (Weight Ret.) so it equals Line K (dry weight)
- V -** % Ret., Line U (Weight Retained) / Line K (total dry weight) x 100 = Line V (% Ret.) (EX. Line U (No. 200 sieve is 56) / Line K (2411) x 100 = Line V (2.3%) **NOTE:** All of Column V shall add up to 100%, if it does not, adjust the highest percent retained to equal 100%, if its more than 0.3 this test is considered invalid and a new sieve shall be ran (EX. Line V (% Ret.) for the No. 4 Sieve was 21.8% and the total for column V is 99.9%, the % retained No. 4 sieve adjusted to 21.9% to allow column V to equal 100%)
- W -** % Pass, Line W (% pass) + Line V (% Ret.) = Line W (% Pass) (EX. For the percent passing on the No. 200 sieve 6.6 + 0.4 = 7.0%)
- X -** Specs. Or % Pass, specifications for the material or percent passing by mix design, (Refer to the Special Provisions or Standard Specifications)

**040-013 Rev. 11/10**

**FIELD MATERIAL SIEVE SHEET**

**LINE**

**EXPLANATION OF NEEDED MATERIAL**

- Y -** Sum of % used, add Line X, horizontally added together for the percent used when combining sieves
- Z -** Specs. Or % Pass, specifications found in the Special Provisions or Standard Specifications
- AA -** Contract number for the material being tested, found in the Contract Plans or Special Provisions (EX. 3925)
- BB -** Material type as specified, found in the Contract Plans or Special Provisions (EX. Type 1 Class B Base Agg.)
- CC -** Date the sample was taken (EX. 07/21/2010)
- DD -** Checked By, initials of the person who checked the math, verified the specifications and accuracy of the test report (EX. STP)
- EE -** Remarks, anything that needs to be documented (EX. Test met specs. RE and Contractor notified of results)

**GENERAL INFORMATION:**

<b>Maximum Allowable Quantity of Material Retained on a Sieve, g</b>		
Sieve Opening Size	Nominal Dimensions of Sieve	
	203.2 mm (8 in.)	304.8 mm (12 in.)
75 mm (3 in.)	'-	'12600
63 mm (2 1/2 in.)	'-	'10600
50 mm (2 in.)	'3600	'8400
37.5 mm (1 1/2 in.)	'2700	'6300
25.0 (1 in.)	'1800	'4200
19.0 mm (3/4 in.)	'1400	'3200
12.5 mm (1/2 in.)	'890	'2100
9.5 mm (3/8 in.)	'670	'1600
4.75 mm (No. 4)	'330	'800
All sieves with openings smaller than 4.75 (No. 4)	'200	'450

040-013 Rev. 11/10

**FIELD MATERIAL SIEVE SHEET**

LINE

EXPLANATION OF NEEDED MATERIAL

**GENERAL INFORMATION:**

Coarse Series	
4"	100 mm
3 - 1/2"	90 mm
3"	75 mm
2 - 1/2"	63 mm
2.12"	53 mm
2"	50 mm
1-3/4"	45 mm
1-1/2"	37.5 mm
1-1/4"	31.5 mm
1.06"	26.5 mm
1"	25.0 mm
7/8"	22.4 mm
3/4"	19.0 mm
5/8"	16.0 mm
0.530"	13.2 mm
1/2"	12.5 mm
7/16"	11.2 mm
3/8"	9.5 mm
5/16"	8.0 mm
0.265"	6.7 mm
1/4"	6.3 mm
No. 3-1/2	5.6 mm
No. 4	4.75 mm

Fine Series	
No. 5	4.0 mm
No. 6	3.35 mm
No. 7	2.80 mm
No. 8	2.36 mm
No. 10	2.00 mm
No. 12	1.70 mm
No. 14	1.40 mm
No. 16	1.18 mm
No. 18	1.00 mm
No. 20	850 µm
No. 25	710 µm
No. 30	600 µm
No. 35	500 µm
No. 40	425 µm
No. 45	355 µm
No. 50	300 µm
No. 60	250 µm
No. 70	212 µm
No. 80	180 µm
No. 100	150 µm
No. 120	125 µm
No. 140	106 µm
No. 170	90 µm
No. 200	75 µm
No. 230	63 µm
No. 270	53 µm
No. 325	45 µm
No. 400	38 µm
No. 450	32 µm
No. 500	25 µm
No. 635	20 µm
Regular Pan	
Extended Rim Pan	
Regular Cover	
Cover with Ring	

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION  
FIELD MATERIAL SIEVE SHEET

AA. CONTRACT NO. 3925  
BB. MATERIAL PBS Type 2C Aggregate  
CC. DATE 7/21/2010

<b>A. Test No. T-1-1</b>					<b>Test No. T-1-1</b>					<b>Test No. T-1-1</b>					<b>DD. Checked By</b>  	
<b>B. Size or Type 1" Rock C. Mix % 28</b>					<b>Size or Type 3/4" Rock Mix % 12</b>					<b>Size or Type Crusher Fines Mix % 55</b>						
<b>D. Sampled by Fred Flinstone</b>					<b>Sampled by Fred Flinstone</b>					<b>Sampled by Fred Flinstone</b>						
<b>E. Tested by Wilma Flinstone</b>					<b>Tested by Wilma Flinstone</b>					<b>Tested by Wilma Flinstone</b>						
<b>F. Source Hunewill Pit Stockpile</b>					<b>Source Hunewill Pit Stockpile</b>					<b>Source Hunewill Pit Stockpile</b>						
Weights-Moisture		Weights-Wash		Weights-Frac. Face	Weights-Moisture		Weights-Wash		Weights-Frac. Face	Weights-Moisture		Weights-Wash		Weights-Frac. Face		
<b>G. 2887</b>	<b>K. 2880</b>		<b>N. 2825</b>		<b>2634</b>		<b>2625</b>		<b>2531</b>	<b>596</b>		<b>588</b>		<b>0</b>		
<b>H. 2880</b>	<b>L. 2864</b>		<b>O. 2825</b>		<b>2625</b>		<b>2601</b>		<b>2531</b>	<b>588</b>		<b>543</b>		<b>0</b>		
<b>I. 7</b>	<b>M. 16</b>		<b>P. 0</b>		<b>9</b>		<b>24</b>		<b>0</b>	<b>8</b>		<b>45</b>		<b>0</b>		
<b>J. Moisture 0.2 %</b>			<b>Q. Frac. Face 100 %</b>		<b>Moisture 0.3 %</b>			<b>Frac. Face 100 %</b>		<b>Moisture 1.4 %</b>			<b>Frac. Face N/A %</b>			
<b>R. LL 26.2</b>			<b>S. PI 6.5</b>		<b>LL 24.6</b>			<b>PI 5.2</b>		<b>LL 19.1</b>			<b>PI 1.4</b>			
Sieve T. Sizes	Weight U. Ret.	% V. Ret.	% W. Pass	Specs. Or X. % Pass	Sieve Sizes	Weight Ret.	% Ret.	% Pass	Specs. Or % Pass	Sieve Sizes	Weight Ret.	% Ret.	% Pass	Specs. Or % Pass	Sum of Y. % used	Specs. Or Z. % Pass
75 mm (3")					75 mm (3")					75 mm (3")						
63 mm (2½")					63 mm (2½")					63 mm (2½")						
50 mm (2")					50 mm (2")					50 mm (2")						
37.5 mm (1½")	<b>0</b>	<b>0.0%</b>	<b>100.0%</b>	<b>28.0 %</b>	37.5 mm (1½")					37.5 mm (1½")						
31.5 mm (1¼")	<b>0</b>	<b>0.0%</b>	<b>100.0%</b>	<b>28.0 %</b>	31.5 mm (1¼")					31.5 mm (1¼")						
25 mm (1")	<b>26</b>	<b>0.9%</b>	<b>99.1%</b>	<b>27.7 %</b>	25 mm (1")	<b>0</b>	<b>0.0%</b>	<b>100.0%</b>	<b>12.0%</b>	25 mm (1")	<b>0</b>	<b>0.0%</b>	<b>100.0%</b>	<b>55.0%</b>		
19 mm (¾")	<b>889</b>	<b>30.9%</b>	<b>68.2%</b>	<b>19.1 %</b>	19 mm (¾")	<b>0</b>	<b>0.0%</b>	<b>100.0%</b>	<b>12.0%</b>	19 mm (¾")	<b>0</b>	<b>0.0%</b>	<b>100.0%</b>	<b>55.0%</b>		
12.5 mm (½")	<b>1672</b>	<b>58.1%</b>	<b>10.2%</b>	<b>2.9%</b>	12.5 mm (½")	<b>482</b>	<b>18.4%</b>	<b>81.6%</b>	<b>9.8%</b>	12.5 mm (½")	<b>0</b>	<b>0.0%</b>	<b>100.0%</b>	<b>55.0%</b>		
9.5 mm (⅜")	<b>208</b>	<b>7.2%</b>	<b>3.0%</b>	<b>0.8%</b>	9.5 mm (⅜")	<b>937</b>	<b>35.7%</b>	<b>45.9%</b>	<b>5.5%</b>	9.5 mm (⅜")	<b>0</b>	<b>0.0%</b>	<b>100.0%</b>	<b>55.0%</b>		
4.75 mm (No. 4)	<b>30</b>	<b>1.0%</b>	<b>2.0%</b>	<b>0.6%</b>	4.75 mm (No. 4)	<b>1112</b>	<b>42.3%</b>	<b>42.4%</b>	<b>3.6%</b>	4.75 mm (No. 4)	<b>81</b>	<b>13.8%</b>	<b>86.2%</b>	<b>47.4%</b>		
2.36 mm (No. 8)					2.36 mm (No. 8)					2.36 mm (No. 8)						
2.00 mm (No. 10)	<b>5</b>	<b>0.2%</b>	<b>1.8%</b>	<b>0.5%</b>	2.00 mm (No. 10)	<b>42</b>	<b>1.6%</b>	<b>2.0%</b>	<b>0.2%</b>	2.00 mm (No. 10)	<b>244</b>	<b>41.4%</b>	<b>41.5%</b>	<b>44.8%</b>	<b>24.6%</b>	
1.18 mm (No. 16)	<b>2</b>	<b>0.1%</b>	<b>1.7%</b>	<b>0.5%</b>	1.18 mm (No. 16)	<b>3</b>	<b>0.1%</b>	<b>1.9%</b>	<b>0.2%</b>	1.18 mm (No. 16)	<b>68</b>	<b>11.6%</b>	<b>33.2%</b>	<b>18.3%</b>		
600 µm (No. 30)					600 µm (No. 30)					600 µm (No. 30)						
425 µm (No. 40)	<b>4</b>	<b>0.1%</b>	<b>1.6%</b>	<b>0.4%</b>	425 µm (No. 40)	<b>4</b>	<b>0.2%</b>	<b>1.7%</b>	<b>0.2%</b>	425 µm (No. 40)	<b>80</b>	<b>13.6%</b>	<b>19.6%</b>	<b>10.8%</b>		
300 µm (No. 50)					300 µm (No. 50)					300 µm (No. 50)						
150 µm (No.100)	<b>6</b>	<b>0.2%</b>	<b>1.4%</b>	<b>0.4%</b>	150 µm (No.100)	<b>6</b>	<b>0.2%</b>	<b>1.5%</b>	<b>0.2%</b>	150 µm (No.100)	<b>48</b>	<b>8.2%</b>	<b>11.4%</b>	<b>6.3%</b>		
75 µm (No. 200)	<b>8</b>	<b>0.3%</b>	<b>1.1%</b>	<b>1.3%</b>	75 µm (No. 200)	<b>7</b>	<b>0.3%</b>	<b>1.2%</b>	<b>0.1%</b>	75 µm (No. 200)	<b>19</b>	<b>3.2%</b>	<b>8.2%</b>	<b>4.5%</b>		
Pan	<b>14</b>	<b>0.5%</b>	<b>0.6%</b>	<b>0.2%</b>	Pan	<b>8</b>	<b>0.3%</b>	<b>0.9%</b>	<b>0.1%</b>	Pan	<b>3</b>	<b>0.5%</b>	<b>7.7%</b>	<b>4.2%</b>		
Wash	<b>16</b>	<b>0.6%</b>			Wash	<b>24</b>	<b>0.9%</b>			Wash	<b>45</b>	<b>7.7%</b>				

**EE. Remarks:** Test met specs. RE and Contractor notified of the results.

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION  
FIELD MATERIAL SIEVE SHEET

AA. CONTRACT NO. 3925  
BB. MATERIAL PBS Type 2C Aggregate  
CC. DATE 7/21/2010

<b>A. Test No. T-1-1</b>					Test No.					Test No.									
<b>B. Size or Type Washed Sand C. Mix % 5</b>					Size or Type Mix %					Size or Type Mix %									
<b>D. Sampled by Fred Flinstone</b>					Sampled by					Sampled by									
<b>E. Tested by Wilma Flinstone</b>					Tested by					Tested by									
<b>F. Source Hunewill Pit Stockpile</b>					Source					Source									
Weights-Moisture		Weights-Wash		Weights-Frac. Face		Weights-Moisture		Weights-Wash		Weights-Frac. Face		Weights-Moisture		Weights-Wash		Weights-Frac. Face		DD. Checked By  <u>                    </u>	
<b>G. 1260</b>		<b>K. 1169</b>		<b>N. 0</b>															
<b>H. 1169</b>		<b>L. 1141</b>		<b>O. 0</b>															
<b>I. 91</b>		<b>M. 28</b>		<b>P. 0</b>															
<b>J. Moisture 7.8 %</b>			<b>Q. Frac. Face N/A %</b>			Moisture %			Frac. Face %			Moisture %			Frac. Face %				
<b>R. LL N/A</b>			<b>S. PI N/P</b>			LL			PI			LL			PI				
Sieve	Weight	%	%	Specs. Or	Sieve	Weight	%	%	Specs. Or	Sieve	Weight	%	%	Specs. Or	Sum of	Specs. Or			
<b>T. Sizes</b>	<b>U. Ret.</b>	<b>V. Ret.</b>	<b>W. Pass</b>	<b>X. % Pass</b>	<b>Sizes</b>	<b>Ret.</b>	<b>Ret.</b>	<b>Pass</b>	<b>% Pass</b>	<b>Sizes</b>	<b>Ret.</b>	<b>Ret.</b>	<b>Pass</b>	<b>% Pass</b>	<b>Y. % used</b>	<b>Z. % Pass</b>			
75 mm (3")					75 mm (3")					75 mm (3")									
63 mm (2½")					63 mm (2½")					63 mm (2½")									
50 mm (2")					50 mm (2")					50 mm (2")									
37.5 mm (1½")					37.5 mm (1½")					37.5 mm (1½")									
31.5 mm (1¼")					31.5 mm (1¼")					31.5 mm (1¼")									
25 mm (1")	<b>0</b>	<b>0.0%</b>	<b>100.0%</b>	<b>5.0%</b>	25 mm (1")					25 mm (1")					<b>99.7%</b>	<b>100</b>			
19 mm (¾")	<b>0</b>	<b>0.0%</b>	<b>100.0%</b>	<b>5.0%</b>	19 mm (¾")					19 mm (¾")					<b>91.1%</b>	<b>88 - 95</b>			
12.5 mm (½")	<b>0</b>	<b>0.0%</b>	<b>100.0%</b>	<b>5.0%</b>	12.5 mm (½")					12.5 mm (½")					<b>72.7%</b>	<b>70 - 85</b>			
9.5 mm (⅜")	<b>0</b>	<b>0.0%</b>	<b>100.0%</b>	<b>5.0%</b>	9.5 mm (⅜")					9.5 mm (⅜")					<b>66.3%</b>	<b>60 - 78</b>			
4.75 mm (No. 4)	<b>0</b>	<b>0.0%</b>	<b>100.0%</b>	<b>5.0%</b>	4.75 mm (No. 4)					4.75 mm (No. 4)					<b>53.4%</b>	<b>43 - 60</b>			
2.36 mm (No. 8)					2.36 mm (No. 8)					2.36 mm (No. 8)									
2.00 mm (No. 10)	<b>29</b>	<b>2.5%</b>	<b>97.5%</b>	<b>4.9%</b>	2.00 mm (No. 10)					2.00 mm (No. 10)					<b>30.2%</b>	<b>30 - 44</b>			
1.18 mm (No. 16)	<b>203</b>	<b>17.4%</b>	<b>80.1%</b>	<b>4.0%</b>	1.18 mm (No. 16)					1.18 mm (No. 16)									
600 µm (No. 30)					600 µm (No. 30)					600 µm (No. 30)									
425 µm (No. 40)	<b>483</b>	<b>41.2%</b>	<b>41.3%</b>	<b>38.9%</b>	425 µm (No. 40)					425 µm (No. 40)					<b>13.3%</b>	<b>12 - 22</b>			
300 µm (No. 50)					300 µm (No. 50)					300 µm (No. 50)									
150 µm (No.100)	<b>353</b>	<b>30.2%</b>	<b>8.7%</b>	<b>0.4%</b>	150 µm (No.100)					150 µm (No.100)									
75 µm (No. 200)	<b>70</b>	<b>6.0%</b>	<b>2.7%</b>	<b>0.1%</b>	75 µm (No. 200)					75 µm (No. 200)					<b>5.0%</b>	<b>3 - 8</b>			
Pan	<b>3</b>	<b>0.3%</b>	<b>2.4%</b>	<b>0.1%</b>	Pan					Pan									
Wash	<b>28</b>	<b>2.4%</b>			Wash					Wash									

**EE. Remarks:** Test met specs. RE and Contractor notified of the results.

**040-013 Rev. 11/10**

**FIELD MATERIAL SIEVE SHEET**

**LINE**

**EXPLANATION OF NEEDED MATERIAL**

- A -** Test number for this particular test. (EX. T-1-1 T = Acceptance Test, 1 = first acceptance test of the day, 1 = number of days the material has been tested) NOTE: If informational test would be I-1-1 I = Informational Test, 1 = first informational test of the day, 1 = number of days the material has been tested
- B -** Size or Type of material being tested (EX. 1" Rock)
- C -** Mix %, percentage of material used for plantmix aggregate or concrete aggregates (EX. 1" Rock = 28%, you would find this information from the approved mix design, job mix Formula or from the Contractor)
- D -** Print first and last name of the tester or testers who sampled the material (EX. Fred Flinstone)
- E -** Print first and last name of the tester or testers who completed the test (EX. Wilma Flinstone)
- F -** Source, name of the location where the material was produced (EX. Hunewill Pit Stockpile)
- G -** Weights-Moisture, wet weight of the material after sample has been split, per Test Method Nev. T203, weighed to the nearest whole number in grams (EX. 2887)
- H -** Total dry weight of the material per Test Method Nev. T112, weighed to nearest whole number (EX. 2880)
- I -** Line G (wet weight) - Line H (dry weight) = Line I (weight in moisture)  
(EX. 2887 - 2880 = 7)
- J -** Moisture, Line G (wet weight) - Line H (dry weight) / Line H (dry weight) x 100 = Line J (moisture %) (EX. (2887 - 2880) / 2880 X 100 = 0.2)
- K -** Weights - Wash, total dry weight of the material per Test Method Nev. T112 (weighed to the nearest whole number) (EX. 2880). NOTE: This number will be the same as Line H
- L -** Dry weight of the material after it has been washed, per Test Method Nev. T206 (weighed to the nearest whole number) (EX. 2864)

**040-013 Rev. 11/10**

**FIELD MATERIAL SIEVE SHEET**

**LINE**

**EXPLANATION OF NEEDED MATERIAL**

- M -** Line K (dry weight) - Line L (washed dry weight) = Line M (minus No. 200 wash weight) (EX. 2880 - 2864 = 16 washed through the No. 200 sieve) NOTE: The total weight in the pan after shaking should not exceed 1% of the total dry weight or the test is invalid
- N -** Weights - Frac. Face, weight of the material retained on the No. 4 sieve and larger screens, per Test Method Nev. T230, weighed to the nearest whole number (EX. 2825)
- O -** Weight of the fractured aggregate per Test Method Nev. T230 (EX. 2825)
- P -** Line N (total weight of all No. + 4 and up material) - Line O (weight of fractured material) = Line P (weight of unfractured material) (EX. 2825 - 2825 = 0)
- Q -** Frac. Face %, Line O (weight of the fractured aggregate) / Line N (total weight of all No. + 4 and up material) x 100 = Line Q (percent fractured face) (EX. 2825 / 2825 x 100 = 100%). Refer to the Special Provisions and the Standard Specifications to see if fractured face is required
- R -** Liquid Limit number that was determined on NDOT form 040-014, per Test Method Nev. T210 (EX. 26.2)
- S -** Plasticity Index that was determined on NDOT form 040-014, per Test Method Nev. T212 (EX. 6.5)
- T -** Sieves that are on the stack. Refer to the Special Provisions and the Standard Specifications for the required specifications on the material being tested
- U -** Weight Ret., weight retained on each sieve in the stack, reported to the nearest whole number **NOTE:** All of Column U (Weight Ret.) shall add up to Line K (dry weight), if it does not, adjust the highest weight retained in Column U (Weight Ret.) so it equals Line K (Dry Weight)
- V -** % Ret., Line U (Weight Ret.) / Line K (dry weight) x 100 = Line V (% Ret.) (EX. Line U (No. 200 sieve is 8) / Line K (2880) x 100 = Line V (0.3%)) **NOTE:** All of Column V shall add up to 100%, if it does not, adjust the highest percent retained, to equal 100%, if its more than 0.3, this sieve is invalid and a new sieve shall be ran (EX. Line V (% Ret.) for the 1/2" Sieve = 58.1%, and the total for column V is 100.1%, therefore the % retained for the 1/2" sieve will need to be adjusted to 58.0% to allow Column V to equal 100%)

**040-013 Rev. 11/10**

**FIELD MATERIAL SIEVE SHEET**

**LINE**

**EXPLANATION OF NEEDED MATERIAL**

- W -** % Pass, Line W (% Pass) + Line V (% Ret.) = Line W (% Pass) (EX. For the percent passing on the No. 200 sieve  $0.6 + 0.5 = 1.1\%$ )
- X -** Specs. or % Pass, specifications for the material or the percent passing by mix design, (refer to the Special Provisions or the Standard Specifications) Line W (% Passing) x Line C (Mix % decimal equivalent) = Line X (Specs or % Passing) (EX. Using the No. 200 sieve  $1.1\% \times 0.28\% = 0.3\%$  passing)
- Y -** Sum of % used, add Line X (mix design % pass), horizontally added together for each individual sieve size and each individual material to get the sum of the % used. (EX. Using the No. 200 sieve, add all Line X's up horizontally for each individual material  $0.3 + 0.1 + 4.5 + 0.1 = 5.0$ )
- Z -** Specs. Or % Pass, specifications found in the Special Provisions or Standard Specifications
- AA -** Contract number for the material being tested, found in the Contract Plans or Special Provisions (EX. 3925)
- BB -** Material Type, as specified, found in the Contract Plans or Special Provisions (EX. PBS Type 2C Aggregate)
- CC -** Date the sample was taken. (EX. 7/21/2010)
- DD -** Checked By, initials of the person who checked the math, verified the specifications and accuracy of the test report
- EE -** Remarks, anything that needs to be documented (EX. Test met specs. RE and Contractor notified of the results.)

**NOTES:**

- 1.** This example is used for submitting material to Materials Division for a Bituminous Mix Design.
- 2.** When completing the weekly checks of the stockpiles for plantmix aggregates, the next test number would be T-1-2 with the informational box checked on NDOT form 040-010.



**FIELD MATERIAL SIEVE SHEET**

**LINE**

**EXPLANATION OF NEEDED MATERIAL**

**NOTES:**

- 3. The 0.3 rule comes from AASHTO T27, if the amounts differ by more than 0.3% based on the original dry mass, the results are invalid.
- 4. Do not deduct lime from the original sample, run the sieve as is.

**GENERAL INFORMATION:**

<b>Maximum Allowable Quantity of Material Retained on a Sieve, g</b>		
Sieve Opening Size	Nominal Dimensions of Sieve	
	203.2 mm (8 in.)	304.8 mm (12 in.)
75 mm (3 in.)	-	12600
63 mm (2 1/2 in.)	-	10600
50 mm (2 in.)	3600	8400
37.5 mm (1 1/2 in.)	2700	6300
25.0 (1 in.)	1800	4200
19.0 mm (3/4 in.)	1400	3200
12.5 mm (1/2 in.)	890	2100
9.5 mm (3/8 in.)	670	1600
4.75 mm (No. 4)	330	800
All sieves with openings smaller than 4.75 (No. 4)	200	450

**FIELD MATERIAL SIEVE SHEET**

LINE

EXPLANATION OF NEEDED MATERIAL

**NOTES:**

**5.**

Coarse Series	
4"	100 mm
3 - 1/2"	90 mm
3"	75 mm
2 - 1/2"	63 mm
2.12"	53 mm
2"	50 mm
1-3/4"	45 mm
1-1/2"	37.5 mm
1-1/4"	31.5 mm
1.06"	26.5 mm
1"	25.0 mm
7/8"	22.4 mm
3/4"	19.0 mm
5/8"	16.0 mm
0.530"	13.2 mm
1/2"	12.5 mm
7/16"	11.2 mm
3/8"	9.5 mm
5/16"	8.0 mm
0.265"	6.7 mm
1/4"	6.3 mm
No. 3-1/2	5.6 mm
No. 4	4.75 mm

Fine Series	
No. 5	4.0 mm
No. 6	3.35 mm
No. 7	2.80 mm
No. 8	2.36 mm
No. 10	2.00 mm
No. 12	1.70 mm
No. 14	1.40 mm
No. 16	1.18 mm
No. 18	1.00 mm
No. 20	850 µm
No. 25	710 µm
No. 30	600 µm
No. 35	500 µm
No. 40	425 µm
No. 45	355 µm
No. 50	300 µm
No. 60	250 µm
No. 70	212 µm
No. 80	180 µm
No. 100	150 µm
No. 120	125 µm
No. 140	106 µm
No. 170	90 µm
No. 200	75 µm
No. 230	63 µm
No. 270	53 µm
No. 325	45 µm
No. 400	38 µm
No. 450	32 µm
No. 500	25 µm
No. 635	20 µm
Regular Pan	
Extended Rim Pan	
Regular Cover	
Cover with Ring	





**040-014 Rev. 10/16**

**FIELD L.L., AND P.I. WORK SHEET**

**LINE**

**EXPLANATION OF NEEDED INFORMATION**

- A -** Contract number for the material being tested, found in the Contract Plans or Special Provisions (EX. 3925)
- B -** Tester, Print first and last name of the tester or testers who completed the test (EX. Wilma Flintstone)
- C -** Date the sample was taken (EX. 7/21/2010)
- D -** Test number for this particular test (EX. T-1-1 T = Acceptance Test, 1 = first test of the day, 1 = number of days material has been tested) **NOTE:** this test number should be the same number as the corresponding sieve
- E -** Material, type of as specified, found in the Contract Plans or Specials (EX. 1" Rock)
- F -** Actual date the sample was tested, which should always be the next day (EX 7/22/2010)
- G -** Location of sample, where the material came from (EX. Hunewill Pit Stockpile)
- H -** Dry weight of material, per Test Method Nev. T210 (EX. 25.56 Watch Glass No. 1) (weight includes glass weight)
- I -** Wet weight of the material, per Test Method Nev. T210 prior to drying (EX. 27.51 Watch Glass No. 1) (wet weight includes the glass weight)
- J -** Tare weight of the glass by itself (this weight is obtained before running any part of the test) (EX. 17.97 Watch Glass No. 1)
- K -** Dry weight of the material, per Test Method Nev. T210 (EX. 25.56 Watch Glass No. 1) (dry weight includes glass weight)
- L -** Line H (Dry Weight) - Line J (Tare Weight) = Line L (Dry Weight of Material) (EX. 25.56 - 17.97 = 7.59 Watch Glass No. 1)
- M -** Line I (Wet Weight) - Line K (Dry Weight) = Line M (Weight of Water) (EX. 27.51 - 25.56 = 1.95 Watch Glass No. 1)
- N -** Number of blows that it takes to close the groove of the soil cake per Test Method Nev. T210 (EX. 35 blows)

**040-014 Rev. 10/16**

**FIELD L.L., AND P.I. WORK SHEET**

**LINE**

**EXPLANATION OF NEEDED INFORMATION**

- O -** % of Moisture, Line M (Weight of Water) / Line L (Dry Weight of Material) X 100 = Line O (% of Moisture) (EX.  $(1.95 / 7.59) \times 100 = 25.7$  Watch Glass No. 1) **NOTE:** Repeat Lines H - O for Watch Glass No. 1, No. 2, and No. 3
- P -** Dry weight of the material per Test Method Nev. T211/T212 (dry weight includes glass weight)
- Q -** Wet weight of the material per Test Method Nev. T211/T212 prior to drying (wet weight includes the glass weight)
- R -** Tare weight of the glass by itself (this weight is obtained before running any part of the test)
- S -** Dry weight of the material per Test Method Nev. T211/T212 (dry weight includes glass weight)
- T -** Line P (Dry Weight) - Line R (Tare Weight of the Glass) = Line T (Dry Weight of Material) (EX.  $30.87 - 22.90 = 7.97$ )
- U -** Line Q (Wet Weight) - Line S (Dry Weight) = Line U (Weight of Water) (EX.  $32.44 - 30.87 = 1.57$ )
- V -** % of Moisture, Line U (Weight of Water) / Line T (Dry Weight of Material) x 100 = Line V (% of Moisture or P.L. (Plastic Limit)) (EX.  $(1.57 / 7.97) \times 100 = 19.7$ )
- W -** Liquid Limit, where the graphed line intersects the 25 shock ordinate line on the semi-logarithmic graph (EX. 26.2)
- X -** Plastic Limit from Line V (EX. 19.7)
- Y -** Plasticity Index, Line W (Liquid Limit) - Line X (Plastic Limit) = Line Y (Plasticity Index) (EX.  $26.2 - 19.7 = 6.5$ ) **NOTE:** This number shall not be a negative number, if it is start the test over, it is an invalid test.
- Z -** Weight of - # 40 material placed into the mixing bowl prior to water being added.

**040-014 Rev. 10/16**

**FIELD L.L., AND P.I. WORK SHEET**

**LINE**

**EXPLANATION OF NEEDED INFORMATION**

**AA -**

In this column, enter the amount of water added in ML's after each addition. Per test method T210, start by adding 15 ML's of water and then continue to add at a rate of 1 to 3 ML's until desired shock value is achieved. When the initial shock value between 25-35 blows is achieved, note hydration period by placing an "H" in the cell next to the water increment that achieved the shock value. After each addition of water that yields a desired shock value, write the number of shocks next to the amount of water added.

**BB -**

Graph Line N and Line O on the logarithmic chart, numbers on the left represent Lines N (number of blows), numbers on the bottom represent Lines O (% of Moisture) **NOTE:** there shall not be more than .3 of a percent (3 lines on the graph) between the two lines crossing the 25 shock ordinate line for the number of blows, Line W comes from the % of moisture and where it intersects the 25 shock ordinate line

**CC -**

Add remarks for anything that needs to be documented (i.e. if material was to granular, N.P., if the test met specs. or did not meet specs).  
(EX. Material was to granular to achieve roll-out, results are Non-plastic. Contractor and Resident Engineer notified of results.)

**DD -**

Place a check mark in the box indicating which method of sample preparation was used, MPA or hand mortar and pestle. Document the total mass processed and the amount of - # 40 material that was obtained.

**EE -**

Resident Engineer or Assistant Resident Engineer signature on that specific crew  
(EX. Dillon James)

**NOTES:**

**1.**

If you obtain less than 85 g of material after hand mortaring the test cannot be ran and INSUFF. MAT. will be written across Lines W, X and Y and an explanation is needed on Line Z under remarks

**2.**

There must be at least 10 blows between Line N. on watch Glass No. 1 and Line N for Watch Glass No. 3, if there is not then the test is invalid and another one shall be ran

**3.**

On the semi-logarithmic graph there shall be no more than .3 of a percent (3 lines on the graph) between the two lines that crossing the 25 shock ordinate line, if there is then the test is invalid and another complete test shall be started

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION

**REPORT OF TESTS OF PORTLAND CEMENT CONCRETE PAVEMENT**

Date Reported \_\_\_\_\_  
 Sampled by \_\_\_\_\_  
 Specification Reference \_\_\_\_\_

Contract No. \_\_\_\_\_  
 Contractor \_\_\_\_\_  
 Mix Design No. \_\_\_\_\_

Brand of Cement \_\_\_\_\_ Type \_\_\_\_\_  
 Brand of Admixture(s) \_\_\_\_\_  
 Brand of Curing Agent \_\_\_\_\_  
 Brand of Air Entraining Admixture \_\_\_\_\_  
 Source of Fine Aggregate \_\_\_\_\_  
 Source of Coarse Aggregate(s) \_\_\_\_\_  
 Source of Water \_\_\_\_\_  
 Batch Ticket No. \_\_\_\_\_ Quantity Batched \_\_\_\_\_ m<sup>3</sup> (yd<sup>3</sup>)

TESTS FOR CONCRETE BEAMS	
Field Set Number	
Test Number	
Location/Station	
Date Sampled	
Date Tested	
Class of Concrete	
Total Weight Fine Agg., kg/m <sup>3</sup> (lb/yd <sup>3</sup> )	
Total Weight Coarse Agg., kg/m <sup>3</sup> (lb/yd <sup>3</sup> )	
Total Water Added, L/m <sup>3</sup> (gal/yd <sup>3</sup> )	
7 Day Modulus of Rupture, MPa (psi)	
28 Day Modulus of Rupture, MPa (psi)	
* ___ Day Modulus of Rupture, MPa (psi)	
Slump, mm (in)	
Total Weight of all Materials Batched	
Unit Weight, kg/m <sup>3</sup> (lb/ft <sup>3</sup> )	
Yield, m <sup>3</sup> (yd <sup>3</sup> )	
**Water/Cement Ratio	
Entrained Air %	

\*Spare beam to test in case of a faulty break or if it is desired to vary the breaking schedule.  
 \*\*(Water Added to Batch + Free Water on Aggregate + Water added in Field) ÷ Total Cementitious Material  
 • Free Water = Total Moisture Content of the Aggregates – Absorbed Moisture

Remarks: \_\_\_\_\_

Tested by: \_\_\_\_\_

Resident Engineer: \_\_\_\_\_



STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION

REPORT OF TESTS OF PORTLAND CEMENT CONCRETE PAVEMENT

A. Date Reported 08/09/2010 B. Contract No. 3925  
 C. Sampled by M. Smart D. Contractor Granite Construction Co.  
 E. Specification Reference 409.03.13 F. Mix Design No. 503628

G. Brand of Cement Nevada H. Type II  
 I. Brand of Admixture(s) Daracem 55  
 J. Brand of Curing Agent WR Seal Tight 2500 White  
 K. Brand of Air Entraining Admixture Darex II  
 L. Source of Fine Aggregate Dayton Materials  
 M. Source of Coarse Aggregate(s) Dayton Materials  
 N. Source of Water City  
 O. Batch Ticket No. 112756 P. Quantity Batched 10 m<sup>3</sup> (yd<sup>3</sup>)

TESTS FOR CONCRETE BEAMS	
Q. Field Set Number	Set 1
R. Test Number	1
S. Location/Station	"X" 7+22 Lt.
T. Date Sampled	7/12/2010
U. Date Tested	7/16/2010
V. Class of Concrete	P.C.A.A.
W. Total Weight Fine Agg., kg/m <sup>3</sup> (lb/yd <sup>3</sup> )	1236
X. Total Weight Coarse Agg., kg/m <sup>3</sup> (lb/yd <sup>3</sup> )	1594
Y. Total Water Added, L/m <sup>3</sup> (gal/yd <sup>3</sup> )	31.3
Z. 7 Day Modulus of Rupture, MPa (psi)	610 PSI
AA. 28 Day Modulus of Rupture, MPa (psi)	745 PSI
BB. * 10 Day Modulus of Rupture, MPa (psi)	610 PSI
CC. Slump, mm (in)	2 1/2"
DD. Total Weight of all Materials Batched	3707
EE. Unit Weight, kg/m <sup>3</sup> (lb/ft <sup>3</sup> )	137.3
FF. Yield, m <sup>3</sup> (yd <sup>3</sup> )	27.0
GG. **Water/Cement Ratio	0.38
HH. Entrained Air %	4.6

\*Spare beam to test in case of a faulty break or if it is desired to vary the breaking schedule.  
 \*\* $(\text{Water Added to Batch} + \text{Free Water on Aggregate} + \text{Water added in Field}) \div \text{Total Cementitious Material}$   
 • Free Water = Total Moisture Content of the Aggregates – Absorbed Moisture

II. Remarks: First Break met spec. Contractor and R.E. notified of results.

JJ. Tested by: M. Smart KK. Resident Engineer: Sarra Jones

**REPORT OF TESTS OF PORTLAND CEMENT CONCRETE  
PAVEMENT**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>A -</b>	Date the beam was tested (EX. 8/9/2010)
<b>B -</b>	Contract number for the material being tested, found on the Contract Plans or Special Provisions (EX. 3925)
<b>C -</b>	Sampled by, Print first and last name of the tester or testers who sampled the material (EX. Mudd and Stone)
<b>D -</b>	Contractor awarded the contract (EX. Granite Construction Co.)
<b>E -</b>	Specification References, all of the specifications that apply to the material being tested, refer to the Standard Specifications and Special Provisions (EX. 409.03.13)
<b>F -</b>	Mix Design number assigned by the Materials Division for this specific material (Mix Design approved by the State Materials Division) (EX. 503628)
<b>G -</b>	Brand of Cement, found on the approved mix design (EX. Nevada)
<b>H -</b>	Type of Cement, found on the approved mix design (EX. Type II)
<b>I -</b>	Brand of Admixture, found on the approved mix design (EX. Daracem 55)
<b>J -</b>	Brand of Curing Agent, given by the contractor, found on the certificate of compliance <b>NOTE:</b> Check the current QPL for this project and verify that the curing compound is an approved material to be used
<b>K -</b>	Brand of Air Entraining Admixture, found on the approved Mix Design (EX. Darex II)
<b>L -</b>	Source of Fine Aggregate, found on the approved mix design (EX. Dayton Materials) <b>NOTE:</b> Where the material was produced
<b>M -</b>	Source of Coarse Aggregate, found on the approved Mix Design (EX. Dayton Materials) <b>NOTE:</b> Where the material was produced
<b>N -</b>	Source of Water, found on the approved Mix Design (EX. City) <b>NOTE:</b> Source will either be City or Domestic

**REPORT OF TESTS OF PORTLAND CEMENT CONCRETE  
PAVEMENT**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>O -</b>	Batch Ticket No., number assigned to the batch ticket found on the batch ticket (EX. 112756)
<b>P -</b>	Quantity Batched, Total amount of the single load batched (EX. 10 yd <sup>3</sup> )
<b>Q -</b>	Field Set Number, number designated to the beams being tested (EX. Set No. 1)
<b>R -</b>	Test number, is the same as the field sample number (EX. 1)
<b>S -</b>	Approximate sample location, found on the Contract Plans or jobsite survey stakes (EX. "X" 7 + 22 LT.)
<b>T -</b>	Date the sample was taken (EX. 7/12/2010)
<b>U -</b>	Date the material was tested (EX. 7/16/2010)
<b>V -</b>	Class of concrete found in the Contract Plans or Special Provisions (EX. P.C.A.A.)
<b>W -</b>	Total weight of Fine Aggregate (found on the delivery ticket) divided by yd <sup>3</sup> of total concrete batched (found on the delivery ticket) (EX. 12360 / 10 = 1236 lb/ft <sup>3</sup> )
<b>X -</b>	Total weight of Coarse Aggregate (found on the delivery ticket) divided by yd <sup>3</sup> of total concrete batched (found on the delivery ticket) (EX. 15940 / 10 = 1594 lb/ft <sup>3</sup> )
<b>Y -</b>	Total weight of water (found on the delivery ticket) divided by the yd <sup>3</sup> of total concrete batched (found on the delivery ticket) NOTE: If water has been indicated in lbs on the delivery ticket, divide by 8.33 (weight of one gallon of water) then divided by the total yd <sup>3</sup> of concrete batched (EX. 2607 / 8.33 = 312.97 / 10 = 31.3 gal/yd <sup>3</sup> )
<b>Z -</b>	7 day Modulus of Rupture see Test Method Nev. T442, using the following formula: $R = \frac{1.5 PI}{Bd^2} \quad (\text{EX. } 610 \text{ psi})$ Note: Read pSi off of the Beam Breaker Worksheet if unable to use formula
<b>AA -</b>	28 day Modulus of Rupture per Test Method Nev. T442, using the following formula: $R = \frac{1.5 PI}{Bd^2} \quad (\text{EX. } 745 \text{ psi})$ Note: Read pSi off of the Beam Breaker Worksheet if unable to use formula

**REPORT OF TESTS OF PORTLAND CEMENT CONCRETE  
PAVEMENT**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>BB -</b>	10 day Modulus of Rupture per Test Method Nev. T442, using the following formula: $R = \frac{1.5 PI}{Bd^2} \quad (\text{EX. } 610 \text{ psi})$ Note: Read pSi off of the Beam Breaker Worksheet if unable to use formula
<b>CC -</b>	Slump results per Test Method Nev. T438 (EX. 2 1/2")
<b>DD -</b>	Total weight of all material from the batch ticket per yd <sup>3</sup> (EX. 3707)
<b>EE -</b>	Unit weight per Test Method Nev. T435 (EX. 137.3 lb/ft <sup>3</sup> )
<b>FF -</b>	Yield is figured per Test Method Nev. T435 # 2 under calculations $S = \frac{W_a + W_1 + W_c + W_w}{W} \quad (\text{EX. } 27.0)$
<b>GG -</b>	Water added to Batch + Free Water on Aggregate + Water added in Field) / Total Cementitious Material = Water/Cement Ratio (EX. 0.38)
<b>HH -</b>	Percent of entrained air per Test Method Nev. T431 (EX. 4.6 %)
<b>II -</b>	Remarks, anything that needs to be documented (EX. First break met spec. Contractor and R.E. notified of results.)
<b>JJ -</b>	Tested By, print first and last name of the tester or testers who completed the test (EX. M. Smart)
<b>KK -</b>	Resident Engineer or Assistant Resident Engineer signature on that specific crew (EX. Sarra Jones)

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION  
**NUCLEAR THIN LAYER COMPACTION REPORT  
FOR PLANTMIX BITUMINOUS PAVEMENTS**

Material Type \_\_\_\_\_  
Lift, Lane & Direction \_\_\_\_\_  
Width and Depth \_\_\_\_\_  
Lot/Sublot \_\_\_\_\_

Contract Number \_\_\_\_\_  
Date \_\_\_\_\_  
Gauge Set Number \_\_\_\_\_  
Tested By \_\_\_\_\_

**TEST SECTION**

Sta.	Sta.	Sta.	Sta.	Sta.

Random Number Block:

Beginning Station:   
Ending Station:

(A x length = longitudinal , B x width = transverse)

A

	X		=	
	X		=	
	X		=	
	X		=	
	X		=	

B

	X		=	
	X		=	
	X		=	
	X		=	
	X		=	

TARGET DENSITY (lbs/ft<sup>3</sup>) \_\_\_\_\_

From (RICE or Control Strip) Test Number \_\_\_\_\_

TEST #	-PM-	-PM-	-PM-	-PM-	-PM-
STATION Nearest (25 ft.)					
Distance from edge		*Joint	*Joint	*Joint	*Joint
Left or Right		LT. RT.	LT. RT.	LT. RT.	LT. RT.
NUCLEAR DENSITY READINGS	1				
	2				
	3				
	4				
Average Density					
Corrected Density					
% Relative Compaction					

Correction Factor:

\* Mean Test Section Density (lbs/ft<sup>3</sup>) =   
\* Mean Percent Relative Compaction =

\* Not Applicable to Partial Test Sections or Joint Densities

Joint Test Specification                      Min.   
Single Test Specification                    Min.                       Max.   
Mean Test Section Specification            Min.                       Max.

**Remarks:**


Resident Engineer Signature \_\_\_\_\_

Accepted      Rejected  
*(Circle one of the above)*

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION  
**NUCLEAR THIN LAYER COMPACTION REPORT  
FOR PLANTMIX BITUMINOUS PAVEMENTS**

A. Material Type	<u>TYPE II PBS</u>	E. Contract Number	<u>3925</u>
B. Lift, Lane & Direction	<u>LIFT 1, LANE 1 and 2, NB</u>	F. Date	<u>11/12/2019</u>
C. Width and Depth	<u>22.0' 2.5"</u>	G. Gauge Set Number	<u>142</u>
D. Lot/Sublot		H. Tested By	<u>Jane Doe</u>

**TEST SECTION**

I. Sta. <b>125+06</b>	Sta. <b>121+77</b>	Sta. <b>119+83</b>	Sta. <b>117+48</b>	Sta. <b>114+07</b>
126+50	124+00	121+50	119+00	116+50

J. Random Number Block: 1      K. Beginning Station: "Z" 126+50  
 L. Ending Station: "Z" 114+00

(A x length = longitudinal , B x width = transverse)

<b>M. A</b>		<b>N.</b>		<b>O.</b>		<b>P. B</b>		<b>Q.</b>		<b>R.</b>
0.576	X	250.0	=	144.0		0.730	X	22.0	=	16.1
0.892	X	250.0	=	223.0		0.948	X	22.0	=	20.9
0.669	X	250.0	=	167.3		0.726	X	22.0	=	16.0
0.609	X	250.0	=	152.3		0.482	X	22.0	=	10.6
0.971	X	250.0	=	242.6		0.824	X	22.0	=	18.1

S. TARGET DENSITY (lbs/ft<sup>3</sup>) 147.6      T. From (RICE or Control Strip) Test Number T-1-1

<b>U. TEST #</b>	1 -PM- 1		1 -PM- 2			1 -PM- 3			1 -PM- 4			1 -PM- 5		
<b>V. STATION</b> (25 ft.)	125+00		121+75			119+75			117+50			114+00		
<b>W. Distance from edge</b>	16      *Joint		20      *Joint			16      *Joint			11      *Joint			18      *Joint		
<b>X. Left of Right</b>	Lt.    LT.    RT.		Lt.    LT.    RT.			Lt.    LT.    RT.			Lt.    LT.    RT.			Lt.    LT.    RT.		
<b>NUCLEAR</b> Y.	1	141.0	133.9	140.7	134.0	141.3	137.4	138.1	136.4	140.7	134.7			
<b>DENSITY</b> Z.	2	140.7	134.3	140.6	134.3	140.7	139.5	138.3	136.4	140.6	135.7			
<b>READINGS</b> AA.	3	140.8		140.7		140.6		138.3		140.7				
BB.	4	140.2		141.3		140.7		137.5		140.3				
<b>CC. Average Density</b>		140.7	134.1	140.8	134.2	140.8	138.5	138.1	136.4	140.6	135.2			
<b>DD. Corrected Density</b>		139.3	132.8	139.4	132.9	139.4	137.1	136.7	135.0	139.2	133.8			
<b>EE. % Relative Compaction</b>		94.4	90.0	94.4	90.0	94.4	92.9	92.6	91.5	94.3	90.7			

FF. Correction Factor: 0.99

GG. \* Mean Test Section Density (lbs/ft<sup>3</sup>) = 138.8  
 HH. \* Mean Percent Relative Compaction = 94.0

\* Not Applicable to Partial Test Sections or Joint Densities

II. Joint Test Specification      Min. 90.0  
 JJ. Single Test Specification    Min. 90.0      Max. 97.0  
 KK. Mean Test Section Specification    Min. 92.0      Max. 96.0

**LL. Remarks:** Test section ran to correlate the nuclear density gauge. Used test # 1, 2, 3, 4 and 5 to match the drilled cores for gauge correction factor. R.E. and contractor notified of results.

C.F. was conducted on a milled surface.

NN. Resident Engineer Signature James Fret

MM. Accepted    Rejected  
 (Circle one of the above)

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION  
**NUCLEAR THIN LAYER COMPACTION REPORT  
FOR PLANTMIX BITUMINOUS PAVEMENTS**

A. Material Type	<u>TYPE II PBS</u>	E. Contract Number	<u>3925</u>
B. Lift, Lane & Direction	<u>LIFT 1, LANE 1 and 2, NB</u>	F. Date	<u>11/12/2019</u>
C. Width and Depth	<u>22.0' 2.5"</u>	G. Gauge Set Number	<u>142</u>
D. Lot/Sublot		H. Tested By	<u>Jane Doe</u>

**TEST SECTION**

	I. Sta. <b>124+25</b>	Sta. <b>121+77</b>	Sta. <b>119+83</b>	Sta. <b>117+48</b>	Sta. <b>114+07</b>
126+50	124+00	121+50	119+00	116+50	114+00

J. Random Number Block: 1      K. Beginning Station: "Z" 126+50  
 L. Ending Station: "Z" 114+00

(A x length = longitudinal , B x width = transverse)

M. A		N.		O.	P. B		Q.		R.
	X		=			X		=	
	X		=			X		=	
	X		=			X		=	
	X		=			X		=	
	X		=			X		=	

S. TARGET DENSITY (lbs/ft<sup>3</sup>) 147.6      T. From (RICE or Control Strip) Test Number T-1-1

U. TEST #		1	-PM-	6	1	-PM-	7	-PM-	-PM-	-PM-	
V. STATION (25 ft.)	Nearest	124+25			122+00						
W. Distance from edge		5	*Joint		3	*Joint		*Joint	*Joint	*Joint	
X. Left or Right		Lt.	LT.	RT.	Lt.	LT.	RT.	LT.	RT.	LT.	RT.
NUCLEAR	Y.	1	135.2		134.2						
DENSITY	Z.	2	135.5		134.4						
READINGS	AA.	3	135.3		134.9						
	BB.	4	136.3		134.3						
CC. Average Density			135.6		134.5						
DD. Corrected Density			137.0		135.8						
EE. % Relative Compaction			92.8		92.0						

FF. Correction Factor: 0.99

GG. \* Mean Test Section Density (lbs/ft<sup>3</sup>) =   
 HH. \* Mean Percent Relative Compaction =   
 \* Not Applicable to Partial Test Sections or Joint Densities

II. Joint Test Specification      Min. 90.0  
 JJ. Single Test Specification      Min. 90.0      Max. 97.0  
 KK. Mean Test Section Specification      Min. 92.0      Max. 96.0

LL. Remarks: Page 2 of 2, test section ran to correlate the nuclear density gauge. Used test # 1, 2, 3, 4 and 5 to match the drilled cores for gauge correction factor. R.E. and contractor notified of results.  
C.F. was conducted on a milled surface.

NN. Resident Engineer Signature James Fret

MM. Accepted      Rejected  
 (Circle one of the above)

**NUCLEAR THIN LAYER COMPACTION REPORT FOR PLANTMIX  
BITUMINOUS PAVEMENTS**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>A -</b>	Material Type, found in the Standard Specifications, Contract Plans, Special Provisions or approved Mix Design (EX. Type II PBS)
<b>B -</b>	Lift, Lane & Direction, Lift of material that is being tested (EX. LIFT 1) Lane that is being paved and tested (EX. LANE 1 and 2) Direction of the paving operation (EX. NB - Northbound)
<b>C -</b>	Width and Depth, Width of the plantmix that is currently being placed (EX. 22.0') Depth of the plantmix that is being placed (EX. 2.5")
<b>D -</b>	Used exclusively for <b>END RESULT</b> contracts
<b>E -</b>	Contract Number, for the material being tested, found in the Contract Plans or Special Provisions (EX. 3925)
<b>F -</b>	Date, the compactions were taken (EX. 11/12/2019)
<b>G -</b>	Gauge Set Number, number assigned to the gauge that is being used to test the material (EX. 142) <b>NOTE:</b> Consultants shall use the gauge serial number found on the back of the gauge
<b>H -</b>	Tested By, print first and last name of the tester or testers who completed the test (EX. Jane Doe)



**NUCLEAR THIN LAYER COMPACTION REPORT FOR PLANTMIX  
BITUMINOUS PAVEMENTS**

**LINE**

**EXPLANATION OF NEEDED INFORMATION**

**I -**

**TEST SECTION STATIONING**

Ending Station - Beginning Station = length of test section  
(EX. "Z" 126+50 - "Z" 114+00 = 1,250' )

Length x Width / 9 = square yards for the test section  
(EX. 1,250' x 22.0' = 27,500 ft<sup>2</sup> / 9 = 3,055.6 = 3,056yds<sup>2</sup>)

Total length (station to station) / 5 (total of subsections) = length of each subsection  
(EX. 1,250' / 5 = 250')

Beginning Station - the length of one section = parameters for the first test for the nuclear gauge, repeat this five times

(EX. "Z" 126+50 - 250' = "Z" 124+00

"Z" 124+00 - 250' = "Z" 121+50

"Z" 121+50 - 250' = "Z" 119+00

"Z" 119+00 - 250' = "Z" 116+50

"Z" 116+50 - 250' = "Z" 114+00)

**NOTE:** If you are paving ahead on line add the length of one section. If you are paving back on line subtract the length of one section

Beginning Station for each section - result from Column O = the station where the test should be taken to the nearest 25 ft. for English

(EX. "Z" 126+50 - 144 = "Z" 125+06 = "Z" 125+00

"Z" 124+00 - 223 = "Z" 121+77 = "Z" 121+75

"Z" 121+50 - 166 = "Z" 119+84 = "Z" 119+75

"Z" 119+00 - 152 = "Z" 117+48 = "Z" 117+50

"Z" 116+50 - 243 = "Z" 114+07 = "Z" 114+00)

**NOTE:** This station is where the actual test for each subsection will be ran

**NUCLEAR THIN LAYER COMPACTION REPORT FOR PLANTMIX  
BITUMINOUS PAVEMENTS**

**LINE**

**EXPLANATION OF NEEDED INFORMATION**

**J -** Random Numbers Block, pick a block from Test Method Nev. T335 (EX. 1) **NOTE:** The same random number block shall not be used more than once per shift

**TABLE OF  
RANDOM NUMBERS**

A	B	A	B	A	B	A	B	A	B										
1	.576 .892 .669 .609 .971	2	.730 .948 .726 .482 .824	3	.430 .858 .501 .809 .902	4	.754 .025 .402 .140 .470	5	.271 .935 .231 .396 .997	6	.870 .114 .305 .025 .392	7	.732 .153 .009 .937 .892	8	.721 .508 .420 .310 .957	9	.998 .749 .517 .253 .640	10	.239 .291 .858 .761 .463
6	.053 .810 .081 .982 .095	7	.899 .159 .277 .468 .801	8	.554 .225 .035 .334 .576	9	.627 .163 .039 .921 .417	10	.427 .549 .860 .690 .251	11	.760 .405 .507 .806 .884	12	.470 .285 .081 .879 .522	13	.040 .542 .538 .414 .235	14	.904 .231 .986 .106 .398	15	.993 .919 .501 .031 .222
11	.509 .371 .165 .477 .788	12	.025 .059 .996 .535 .101	13	.794 .164 .356 .337 .434	14	.850 .838 .375 .155 .638	15	.917 .289 .654 .767 .021	16	.887 .169 .939 .187 .894	17	.751 .569 .815 .579 .324	18	.608 .977 .592 .787 .871	19	.698 .796 .348 .358 .698	20	.683 .996 .743 .595 .539
16	.566 .901 .470 .068 .874	17	.815 .342 .682 .242 .420	18	.622 .873 .412 .667 .127	19	.548 .964 .064 .356 .284	20	.947 .942 .150 .195 .448	21	.169 .985 .962 .313 .215	22	.317 .123 .925 .396 .833	23	.472 .086 .355 .460 .652	24	.864 .335 .909 .740 .601	25	.466 .212 .019 .247 .326
21	.897 .875 .190 .341 .846	22	.877 .969 .696 .688 .355	23	.209 .109 .757 .587 .831	24	.862 .843 .283 .908 .218	25	.428 .759 .666 .865 .945	26	.117 .239 .491 .333 .364	27	.100 .890 .523 .928 .673	28	.259 .317 .665 .404 .305	29	.425 .428 .919 .892 .195	30	.284 .802 .146 .696 .887
26	.882 .464 .123 .116 .836	27	.227 .658 .791 .120 .206	28	.552 .629 .503 .721 .914	29	.077 .269 .447 .137 .574	30	.454 .069 .659 .263 .870	31	.731 .998 .463 .176 .390	32	.716 .917 .994 .798 .104	33	.265 .217 .307 .879 .755	34	.058 .220 .631 .432 .082	35	.075 .659 .422 .391 .939
31	.636 .630 .804 .360 .183	32	.195 .673 .112 .193 .651	33	.614 .665 .331 .181 .157	34	.486 .666 .606 .399 .150	35	.629 .399 .551 .564 .800	36	.663 .592 .928 .772 .875	37	.619 .441 .830 .890 .205	38	.007 .649 .841 .062 .446	39	.296 .270 .602 .919 .648	40	.456 .612 .183 .875 .685

**NUCLEAR THIN LAYER COMPACTION REPORT FOR PLANTMIX  
BITUMINOUS PAVEMENTS**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>K -</b>	Beginning Station, for this specific test section (EX. "Z" 126 + 50)
<b>L -</b>	Ending Station, for this specific test section (EX. "Z" 114 + 00)
<b>M -</b>	Column A, from the random numbers block from Test Method Nev. T335 (EX. 0.576 0.892 0.669 0.609 0.971)
<b>N -</b>	Length of one individual sub-section figured out in Letter I (EX. 250)
<b>O -</b>	Letter M (Random numbers from Column A, Test Method Nev. T335) x Letter N (length of one subsection) = Letter O (distance into that one subsection to the nearest 25 ft.) (EX. $0.576 \times 250 = 144.0$ $0.892 \times 250 = 223.0$ $0.669 \times 250 = 167.3$ $0.609 \times 250 = 152.3$ $0.971 \times 250 = 242.6$ )
<b>P -</b>	Column B, from the random numbers block from Test Method Nev. T335 (EX. 0.730 0.948 0.726 0.482 0.824)
<b>Q -</b>	Width of the lane being paved from Line C (EX. 22.0')
<b>R -</b>	Letter P (Random numbers from Column B, Test Method Nev. T335) x Letter Q (width of subsections) = Letter R (distance of one subsection rounded to the nearest 1 ft) (EX. $0.730 \times 22 = 16.1 = 16$ $0.948 \times 22 = 20.9 = 21 = 20$ (due to 2' rule from edge of mat) $0.726 \times 22 = 16.0 = 16$ $0.482 \times 22 = 10.6 = 11$ $0.824 \times 22 = 18.1 = 18$ )

**NUCLEAR THIN LAYER COMPACTION REPORT FOR PLANTMIX  
BITUMINOUS PAVEMENTS**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>S -</b>	Target Density (lbs/ft <sup>3</sup> ), Theoretical maximum specific gravity (RICE) performed from that day per Test Method Nev. T324, one in the A.M. and one in the P.M. (EX. 147.6) <b>NOTE:</b> Tester who is running the plantmix sample at the field lab will give the tester the RICE results. The RICE results from the previous days P.M. test can be used until the A.M. results are completed. One test section will have one RICE, DO NOT use two RICES on one test section.
<b>T -</b>	RICE or Control Strip Test Number, RICE Test Number that correlates to the test number for the ignition oven sample, per Test Method Nev. T761 (EX. T-1-1) or Control Test Strip Number correlates to the "Control Strip No." on NDOT form 040-048, per Test Method Nev. T750 (Ex. 1)
<b>U -</b>	Test Number, for this particular test section (EX. 1-PM-1, 1-PM-2, 1-PM-3, 1-PM-4, 1-PM-5, 1-PM-6 AND 1-PM-7) 7 tests are used only for the gauge correlation. The next test section would be numbered 2-PM-1 through 2-PM-5 <b>NOTE:</b> TEST NUMBERS RUN IN CHRONOLOGICAL ORDER STARTING WITH 1-PM-1 THROUGH 1-PM-7 ANYTHING UNDER 1,000 YD <sup>2</sup> SHOULD BE CONSIDERED A SMALL TEST SECTION. If it's a small test section each test needs it's own test number, 2-PM-1, 3-PM-1 etc. and on it's own sheet (If the contractor is moving to various locations throughout the day and it will equal a full test section, make it a full test section not a bunch of small sections)
<b>V -</b>	Station, where the four test shots, at each location, are taken for the compactions, rounded to the nearest 25 ft. These stations were figured in Letter I (EX. "Z" 125+00, "Z" 121+75, "Z" 119+75, "Z" 117+50, "Z" 114+00)
<b>W -</b>	Distance from edge of the mat where the shots will be taken with the gauge. These numbers were figured in Letter R (EX. 16, 20, 16, 11, 18) <b>NOTE:</b> Do not take tests within 2 feet from the edge of the mat
<b>X -</b>	Left or Right, the side of the mat in which the distance is pulled from for the 4, 1-minute tests (EX. Left). Joint tests on LT, RT or both sides of hot mat. <b>NOTE:</b> DON'T CHANGE SIDES THROUGHOUT THE DAY. PICK LEFT OR RIGHT AND STAY WITH IT SO YOU YOU DON'T CONFUSE YOURSELF
<b>Y -</b>	Nuclear Density Reading, one minute test taken with the nuclear density gauge at "Z" 125+00, 16' left, gauge will read Dens: X.X (EX. 141.0) mark around the gauge with keil <b>NOTE:</b> If you are paving a joint, do not forget to take the shot within 6" of the joint. Place the gauge parallel to the joint, be sure the gauge sits flat on the mat and does not rock.

**NUCLEAR THIN LAYER COMPACTION REPORT FOR PLANTMIX  
BITUMINOUS PAVEMENTS**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>Z -</b>	Second one minute test taken with the nuclear density gauge rotated 90° at "Z" 125+00, 16' left, gauge will read Dens: X.X (EX. 140.7) mark around gauge with keil <b>NOTE:</b> If you are paving a joint, do not forget to take the shot within 6" of the joint. Rotate the gauge 180 degree's and parallel to the joint, be sure the gauge sits flat on the mat and does not rock.
<b>AA -</b>	Third one minute test taken with the nuclear density gauge rotated another 90° at "Z" 125+00, 16' left, gauge will read Dens: X.X (EX. 140.8)
<b>BB -</b>	Fourth one minute test taken with the nuclear density gauge rotated another 90° at "Z" 125+00, 16' left, gauge will read Dens: X.X (EX. 140.2) <b>NOTE:</b> Repeat letters Y, Z, AA, BB four more times at the next four stations that are written in Letter V for a complete test section
<b>CC -</b>	Average Density, add lines (Y + Z + AA + BB) / 4 = average density of the four shots taken (EX. 141.0 + 140.7 + 140.8 + 140.2 = 562.7 / 4 = 140.7) <b>NOTE:</b> (Line Y + Line Z) / 2 = the average of the joint shots (EX. 133.9 + 134.3 = 268.2 / 2 = 134.1)
<b>DD -</b>	Corrected Density, Line CC (Average Density) x Line FF (Correction Factor) = Line DD (Corrected Density) (EX. 140.7 x .99 = 139.3)
<b>EE -</b>	% Relative Compaction, Line DD (Corrected Density) / Line S (TARGET DENSITY) x 100 = Line EE (% Relative Comp.) (EX. (139.3 / 147.6) x 100 = 94.4%) <b>NOTE:</b> Round to the nearest tenth of a percent. <b>NOTE:</b> If this section fails, notify the contractor of the failing results, they may have the finish roller, re-roll this section. If section is re-rolled discard the failing results and start over from Letter Y
<b>FF -</b>	Correction Factor, is established on the first day of paving or when paving on a new surface using NDOT forms 040-017, 040-017A and 040-017B (EX. 0.99) <b>NOTE:</b> The correction factor will be used throughout the duration of the project unless the gauge is recorrealted
<b>GG -</b>	Mean Test Section Density (lbs/ft <sup>3</sup> ), Add all five of Line DD (average corrected densities) / 5 = Line GG (Mean Test Section Density) (EX. 139.3 + 139.4 + 139.4 + 136.7 + 139.2 = 694.0 694.0 / 5 = 138.8) <b>NOTE:</b> The joint corrected densities are not used when calculating the Mean Test Section Density (lbs/ft <sup>3</sup> )

**NUCLEAR THIN LAYER COMPACTION REPORT FOR PLANTMIX  
BITUMINOUS PAVEMENTS**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>HH -</b>	Mean Percent Relative Compaction, Line GG (Mean Test Section Density) / Line S (TARGET DENSITY) x 100 = Line HH (Mean Percent Relative Compaction) round to the nearest tenth of a percent (EX. $138.8 / 147.6 = 0.940 \times 100 = 94.0\%$ )
<b>II -</b>	Joint Test Specification, refer to the special Provisions or Standard Specifications for the joint test specification (EX. 90)
<b>JJ -</b>	Single Test Specification, refer to the Special Provisions or Standard Specifications for the single test specification (EX. 90 to 97)
<b>KK -</b>	Mean Test Section Specification, refer to the Special Provisions or Standard Specifications for the mean test section specifications (EX. 92 to 96)
<b>LL -</b>	Remarks, anything that needs to be documented in this test section (EX. Test section ran to correlate the nuclear density gauge. Used test # 1, 2, 3, 4 and 5 to match the drilled cores for gauge correction factor. R. E. and contractor notified of results. C.F. was conducted on a milled surface.)
<b>MM -</b>	Accepted Rejected, make sure you circle Accepted or Rejected for the test section <b>NOTE:</b> If an R.E. accepts a failing section on substantial compliance, they must write a note on the report and sign it
<b>NN -</b>	Resident Engineer or Assistant Resident Engineer signature on that specific crew (EX. James Fret)

**NOTES:**

1. Circle all failures in red and explain under remarks what transpired with failing test section (EX. Contractor ripped out or R.E. accepted on substantial compliance, etc.)
2. During the gauge correlation, two extra locations shall be tested within the test section. These two locations shall be labeled 1-PM-6 and 1-PM-7. These two extra test areas are randomly chosen and will be cored during gauge correlation. These two extra tests need to be submitted with the gauge correlation.

**NUCLEAR THIN LAYER COMPACTION REPORT FOR PLANTMIX  
BITUMINOUS PAVEMENTS**

**LINE**                      **EXPLANATION OF NEEDED INFORMATION**

**NOTES:**

- 3.**                      When figuring a test section that has a break in the stationing or an equation, figure the test section as follows: "Z" 126 + 50 to "Z" 124 + 00 break in stationing due to bridge "Z" 120 + 00 to "Z" 110 + 00  
(EX. 12,650 - 12,400 = 250', 12,000 - 11,000 = 1,000', 1,000 + 250 = 1,250' for this test section.)
- 4.**                      Small sized area is 1,000 yd<sup>2</sup> or less, it has its own test number 5-PM-1 and is on its own sheet. If there is over 1,000 yd<sup>2</sup> it shall be made into a full test section. The only way multiple small sections will be accepted is if they are approaches or small dig out areas and will be noted under remarks.
- 5.**                      There should not be any informational test sections for plantmix compactions unless the gauge is being correlated on another contract, or a road that is not on this specific contract. If this is the case then the test section numbering will be I-1-PM-1 through I-1-PM-7 and what transpired shall be documented under remarks.
- 6.**                      Correlate the gauge for each surface that is being paved (EX. paving on top of base - correlate gauge, paving on coldmilling - correlate gauge, paving second lift of plantmix - correlate gauge etc.).

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION  
**NUCLEAR THIN LAYER COMPACTION REPORT  
FOR PLANTMIX BITUMINOUS PAVEMENTS**

A. Material Type	<u>TYPE II PBS</u>	E. Contract Number	<u>3925</u>
B. Lift, Lane & Direction	<u>LIFT 1, Approach, N/A</u>	F. Date	<u>11/12/2019</u>
C. Width and Depth	<u>Varies 12.0' 2.5"</u>	G. Gauge Set Number	<u>142</u>
D. Lot/Sublot		H. Tested By	<u>Jane Doe</u>

**TEST SECTION**

I. Sta. <b>113+75</b>	Sta.	Sta.	Sta.	Sta.
114+00	113+25			

J. Random Number Block:       K. Beginning Station: "Z" 114+00  
 L. Ending Station: "Z" 113+25

(A x length = longitudinal , B x width = transverse)

M. A	X	N.	=	O.	P. B	X	Q.	=	R.
<input style="width: 100%; height: 20px;" type="text"/>	X	<input style="width: 100%; height: 20px;" type="text"/>	=	<input style="width: 100%; height: 20px;" type="text"/>	<input style="width: 100%; height: 20px;" type="text"/>	X	<input style="width: 100%; height: 20px;" type="text"/>	=	<input style="width: 100%; height: 20px;" type="text"/>
<input style="width: 100%; height: 20px;" type="text"/>	X	<input style="width: 100%; height: 20px;" type="text"/>	=	<input style="width: 100%; height: 20px;" type="text"/>	<input style="width: 100%; height: 20px;" type="text"/>	X	<input style="width: 100%; height: 20px;" type="text"/>	=	<input style="width: 100%; height: 20px;" type="text"/>
<input style="width: 100%; height: 20px;" type="text"/>	X	<input style="width: 100%; height: 20px;" type="text"/>	=	<input style="width: 100%; height: 20px;" type="text"/>	<input style="width: 100%; height: 20px;" type="text"/>	X	<input style="width: 100%; height: 20px;" type="text"/>	=	<input style="width: 100%; height: 20px;" type="text"/>
<input style="width: 100%; height: 20px;" type="text"/>	X	<input style="width: 100%; height: 20px;" type="text"/>	=	<input style="width: 100%; height: 20px;" type="text"/>	<input style="width: 100%; height: 20px;" type="text"/>	X	<input style="width: 100%; height: 20px;" type="text"/>	=	<input style="width: 100%; height: 20px;" type="text"/>

S. TARGET DENSITY (lbs/ft<sup>3</sup>) 147.6      T. From (RICE or Control Strip) Test Number T-1-1

U. TEST #	2	-PM-	1	-PM-	-PM-	-PM-	-PM-		
V. STATION (25 ft.)	Nearest <b>113+75</b>								
W. Distance from edge	5	*Joint		*Joint		*Joint		*Joint	
X. Left or Right	Lt.	LT.	RT.	LT.	RT.	LT.	RT.	LT.	RT.
NUCLEAR DENSITY READINGS	Y.	1	135.2						
	Z.	2	135.5						
	AA.	3	135.3						
	BB.	4	136.3						
CC. Average Density			135.6						
DD. Corrected Density			137.0						
EE. % Relative Compaction			92.8						

FF. Correction Factor:

GG. \* Mean Test Section Density (lbs/ft<sup>3</sup>) =   
 HH. \* Mean Percent Relative Compaction =   
 \* Not Applicable to Partial Test Sections or Joint Densities

II. Joint Test Specification      Min.   
 JJ. Single Test Specification      Min.       Max.   
 KK. Mean Test Section Specification      Min.       Max.

NN. Resident Engineer Signature James Fret

LL. Remarks:   
  
  
 Area = 100 yd<sup>2</sup>

MM.  Accepted       Rejected  
 (Circle one of the above)



**NUCLEAR THIN LAYER COMPACTION REPORT FOR PLANTMIX  
BITUMINOUS PAVEMENTS**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>A -</b>	Material Type, as specified, found in the Contract Plans, Special Provisions or Mix Designs (EX. TYPE II PBS)
<b>B -</b>	Lift, Lane & Direction, of material that is being tested (EX. LIFT 1) Lane that is being paved and tested (EX. Approach) Direction of the paving operation (EX. N/A)
<b>C -</b>	Width and Depth, Width of the plantmix that is currently being placed (EX. Varies 12') Depth of the plantmix that is being placed (EX. 2.5")
<b>D -</b>	Used exclusively for <b>END RESULT</b> contracts
<b>E -</b>	Contract Number, for the material being tested, found in the Contract Plans or Special Provisions (EX. 3925)
<b>F -</b>	Date, the compactions were taken (EX. 11/12/2019)
<b>G -</b>	Gauge Set Number, number assigned to the gauge that is being used to test the material (EX. 142) <b>NOTE:</b> Consultants shall use the gauge serial number found on the back of their gauge
<b>H -</b>	Tested By, print first and last name of the tester or testers who completed the test (EX. Jane Doe)
<b>I -</b>	Test Section Stationing, beginning and ending station. Randomly select a station within the station limits. (EX. 113+75) <b>NOTE:</b> No random number block needed for small areas
<b>J -</b>	Random Numbers Block, is not required for a small area, pick a miscellaneous location within the small area
<b>K -</b>	Beginning Station, for this specific small area (EX. "Z" 114+00)
<b>L -</b>	Ending Station, for this specific small area (EX. "Z" 113+25)
<b>M -</b>	Random Numbers, are not required for small areas
<b>N -</b>	Length not required for small areas

**NUCLEAR THIN LAYER COMPACTION REPORT FOR PLANTMIX  
BITUMINOUS PAVEMENTS**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>O -</b>	Random lengths are not required for small areas
<b>P -</b>	Random numbers are not required for small areas
<b>Q -</b>	Width not required for small areas
<b>R -</b>	Random widths not required for small areas
<b>S -</b>	Target Density (lbs/ft <sup>3</sup> ), theoretical maximum specific gravity (RICE) performed from that day per Test Method Nev. T324, one in the A.M. and one in the P.M. (EX. 147.6) <b>NOTE:</b> The tester who is running the plantmix sample at the field lab will give the tester the RICE results. The RICE results from the previous days P.M. test can be used until the A.M. results are completed. One test section will have one RICE, DO NOT use two RICES on one test section
<b>T -</b>	RICE or Control Strip Test Number, that correlates to the test number for the ignition oven sample, per Test Method Nev. T761 (EX. T-1-1)
<b>U -</b>	Test Number, for this particular small area (EX. 2-PM-1) <b>NOTE:</b> Test numbers run in chronological order starting with 1-PM-1 through 1-PM-5 anything under 1,000 yd <sup>2</sup> can be considered a small test section. If it's a small test section each test needs its own test number, 2-PM-1, 3-PM-1 etc. and on its own sheet and an explanation of why it's a small area (If the contractor is moving to various locations throughout the day and it will equal a full test section, make it a full test section instead of a bunch of small sections)
<b>V -</b>	Station, where the four test shots are taken for the compaction (EX. 113 + 75)
<b>W -</b>	Distance from Edge, of the mat where the shots will be taken with the gauge that day (EX. 5) <b>NOTE:</b> Do not take tests within 2 feet from the edge of the mat
<b>X -</b>	Left or Right, the side of the mat in which the distance is pulled from (EX. Left) <b>NOTE:</b> Do Not change sides throughout the day. Pick left or right and stay with it so you don't confuse yourself

**NUCLEAR THIN LAYER COMPACTION REPORT FOR PLANTMIX  
BITUMINOUS PAVEMENTS**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>Y -</b>	Nuclear Density Readings, one minute test taken with the nuclear density gauge at "Z" 113 + 75, 5' left, gauge will read Dens: X.X (EX. 135.2) mark around the gauge with keil <b>NOTE:</b> If you are paving a joint, do not forget to take the shot within 6" of the joint. Place the gauge parallel to the joint, be sure the gauge sits flat on the mat and does not rock.
<b>Z -</b>	Second one minute test taken with the nuclear density gauge rotated 90° at "Z" 113+75, 5' left, gauge will read Dens: X.X (EX. 135.5) mark around the gauge with keil. <b>NOTE:</b> If you are paving a joint, do not forget to take the shot within 6" of the joint. Rotate the gauge 180 degree's and parallel to the joint, be sure the gauge sits flat on the mat and does not rock.
<b>AA -</b>	Third one minute test taken with the nuclear density gauge rotated another 90° at "Z" 113+75, 5' left, gauge will read Dens: X.X (EX. 135.3)
<b>BB -</b>	Fourth one minute test taken with the nuclear density gauge rotated another 90° at "Z" 113+75, 5' left, gauge will read Dens: X.X (EX. 136.3)
<b>CC -</b>	Average Density, add lines Y + Z + AA + BB / 4 = average density of the four shots taken (EX. $135.2 + 135.5 + 135.3 + 136.3 = 542.3 / 4 = 135.6$ )
<b>DD -</b>	Corrected Density, Line CC (Average Density) x Line FF (Correction Factor) = Line DD (Corrected Density) (EX. $135.6 \times 1.01 = 137.0$ )
<b>EE -</b>	% Relative Compaction, Line DD (Corrected Density) / Line S (TARGET DENSITY) x 100 = Line EE (% Relative Compaction) (EX. $(137.0 / 147.6) \times 100 = 92.8\%$ ) <b>NOTE:</b> Round to the nearest tenth of a percent <b>NOTE:</b> If this section fails, notify the contractor of the failing results, they may have the finish roller to re-roll this section. If section is re-rolled discard the failing results and start over from Letter Y
<b>FF -</b>	Correction Factor is established on the first day of paving or when paving on a different surface than the original correlation, using NDOT forms 040-017, 040-017A and 040-017B (EX. 1.01) <b>NOTE:</b> The correction factor will be used throughout the duration of the project unless the gauge is recorrelated, per Test Method T335.
<b>GG -</b>	Mean Test Section Density, is not required for a small area
<b>HH -</b>	Mean Percent Relative Compaction, is not required for a small area

**NUCLEAR THIN LAYER COMPACTION REPORT FOR PLANTMIX  
BITUMINOUS PAVEMENTS**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>II -</b>	Joint Test Specification, refer to the Special Provisions or Standard Specifications for the joint test specification
<b>JJ -</b>	Single Test Specification, refer to the Special Provisions or Standard Specifications for the single test specifications (EX. 90 to 97)
<b>KK -</b>	Mean Test Section Specifications, are not required for a small area
<b>LL -</b>	Remarks, anything that needs to be documented for this small area (EX. Small area under 1,000yd <sup>2</sup> paving an approach at Topsey Lane. RE and contractor notified of results. Area = 100 yd <sup>2</sup> ) <b>NOTE:</b> Line K (Beginning Station) - Line L (Ending Station) = (Length of Test Section x Line C (Width)) / 9 = Yd <sup>2</sup>
<b>MM -</b>	Accepted Rejected, make sure you circle Accepted or Rejected for this small area <b>NOTE:</b> If an R.E. accepts a failing small area on substantial compliance, they must write a note on the report and initial it
<b>NN -</b>	Resident Engineer, or Assistant Resident Engineer signature on that specific crew (EX. James Fret)

**NOTES:**

- 1.** Circle all failures in red and explain under remarks what transpired with failing test section.
- 2.** Small sized area is 1,000 yd<sup>2</sup> or less, it has its own test number 5-PM-1 and is on its own sheet. If there is over 1,000 yd<sup>2</sup> it shall be made into a full test section. The only way multiple small areas will be accepted is if they are approaches.



STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION

**NUCLEAR THIN LIFT CORRECTION FACTOR WORKSHEET**

A. Date	<u>11/12/2019</u>	D. Contract No.	<u>3925</u>
B. Material Type	<u>Type II PBS</u>	E. Nuclear Set No.	<u>142</u>
C. Calculated By	<u>Jane Doe</u>	F. Mix Design No.	<u>BF19-137</u>

(pcf) will be carried to the 0.1

NUCLEAR DENSITIES

<b>G.</b>		<b>H.</b>			
# 1-PM-1	=	140.7	Lbs/ft <sup>3</sup>		
# 1-PM-2	=	140.8	Lbs/ft <sup>3</sup>		
# 1-PM-3	=	140.8	Lbs/ft <sup>3</sup>		
# 1-PM-4	=	138.1	Lbs/ft <sup>3</sup>		
# 1-PM-5	=	140.6	Lbs/ft <sup>3</sup>		
<b>K. Average</b>	=	140.2	Lbs/ft <sup>3</sup>		

CORE DENSITIES

<b>I.</b>		<b>J.</b>			
# 1-PM-1	=	143.0	Lbs/ft <sup>3</sup>		
# 1-PM-2	=	138.7	Lbs/ft <sup>3</sup>		
# 1-PM-3	=	140.8	Lbs/ft <sup>3</sup>		
# 1-PM-4	=	134.2	Lbs/ft <sup>3</sup>		
# 1-PM-5	=	135.5	Lbs/ft <sup>3</sup>		
<b>L. Average</b>	=	138.4	Lbs/ft <sup>3</sup>		

(Nuclear Density Numbers and Core Density Numbers Must Correspond)

CORRECTION FACTOR

<b>M.</b> <u>138.4</u>	/	<b>N.</b> <u>140.2</u>	=	<b>O.</b> <u>0.99</u>	
Core Density Average		Nuclear Density Average		Correction factor	

**P. REMARKS:** The correction factor is 0.99, C.F. was conducted on a milled surface.  
Used 1-PM-1, 1-PM-2, 1-PM-3, 1-PM-4 AND 1-PM-5 for the gauge correlation  
Did not use cores 1-PM-6 and 1-PM-7 in the gauge correlation.

---

---

---

---

---

---

---

---

---

---

**Q. Resident Engineer:** \_\_\_\_\_ *James Fret* \_\_\_\_\_

**NUCLEAR THIN LIFT CORRECTION FACTOR  
WORKSHEET**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>A -</b>	Date, the cores were taken (EX. 11/12/2019)
<b>B -</b>	Material Type, as specified, found in the Contract Plans, Special Provisions or Mix Design (EX. Type II PBS)
<b>C -</b>	Calculated By, print first and last name of the tester or testers who completed the test (EX. Jane Doe)
<b>D -</b>	Contract Number, for the material being tested, found in the Contract Plans or Special Provisions (EX. 3925)
<b>E -</b>	Nuclear Set Number assigned to the gauge that is being used to test the plantmix (EX. 142) NOTE: Consultants shall use the gauge serial number found on the back of the gauge
<b>F -</b>	Mix Design No., approved by the Materials Division that the sample represents (EX. BF19-137) NOTE: Approved copies are on the Construction - Quality Assurance SharePoint site.
<b>G -</b>	Nuclear Densities, actual test number for this particular test given to a specific nuclear gauge shot and core while paving, use the same test number used on NDOT form 040-017 to fill in Line G (Nuclear Densities) on form 040-017A (EX. 1-PM-1, 1-PM-2, 1-PM-3, 1-PM-4 and 1-PM-5) NOTE: If correlating multiple gauges, number all test reports 1-PM-1 through 1-PM-7 since all tests are taken at the same location. Only use 1-PM-6 and 1-PM-7 for a gauge correlation and only if one of the cores 1-PM-1 to 1-PM-5 breaks, is damaged or is a flyer.
<b>H -</b>	Nuclear Densities, Average density from the four one minute shots taken from NDOT form 040-017 Line CC (Average Densities) (EX. 140.7, 140.8, 140.8, 138.1, 140.6), make sure to use the average densities that are correlated to the cores being used NOTE: These numbers are NOT from Line DD (Corrected Density) on Form 040-017
<b>I -</b>	Core densities, Actual test number for this particular test given to that specific nuclear gauge shot and core while paving, use the same test number used on NDOT form 040-017 and 040-017B (EX. 1-PM-1, 1-PM-2, 1-PM-3, 1-PM-4 AND 1-PM-5) NOTE: If correlating multiple gauges, number all cores 1-PM-1 through 1-PM-7 since the same set of cores will be used for all gauges being correlated

**NUCLEAR THIN LIFT CORRECTION FACTOR  
WORKSHEET**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>J -</b>	Core Densities, density of the actual core after completing Test Method Nev. T336 and reported on Form 040-017B. (EX. 143.0, 138.7, 140.8, 134.2, and 135.5) NOTE: Be sure that the core used is the one drilled from the same nuclear test shot
<b>K -</b>	Average, Line H (Nuclear Average Density numbers from NDOT form 040-017) / 5 = Line K (Nuclear Density Average) (EX. $140.7 + 140.8 + 140.8 + 138.1 + 140.6 = 701.0 / 5 = 140.2$ )
<b>L -</b>	Average, Line J (core densities from NDOT form 040-017B) / 5 = Line L (Core Density Average) (EX. $143.0 + 138.7 + 140.8 + 134.2 + 135.5 = 692.2 / 5 = 138.4$ )
<b>M -</b>	Core Density Average, from Line L (EX. 138.4)
<b>N -</b>	Nuclear Density Average, from Line K (EX. 140.2)
<b>O -</b>	Line M (Core Density Average) / Line N (Nuclear Density Average) = Line O (Correction Factor) (EX. $138.4 / 140.2 = 0.99$ ) NOTE: This correction factor will be used for the Type II PBS for the duration of the job unless a new correction factor is established due to a new mix design, a change in material or the paving surface is different than that of the original surface that was cored
<b>P -</b>	Remarks, Anything that needs to be documented (EX. The correction factor is 0.99, C.F. was conducted on a milled surface. Used 1-PM-1, 1-PM-2, 1-PM-3, 1-PM-4 and 1-PM-5 for the gauge correlation. Did not use cores 1-PM-6 and 1-PM-7 in the gauge correlation)
<b>Q -</b>	Resident Engineer or Assistant Resident Engineer signature on that specific crew (EX. James Fret)

**NOTE:**

1. Gauge shall be correlated for every different surface of material being paved on top of (EX. gauge correlated - milled surface, gauge correlated - base surface, gauge correlated - second lift of plantmix, gauge correlated - cold recycle surface etc.)
2. Use the first 5 cores for the gauge correlation unless one of the first five cores is damaged (EX. broken core, diesel spilled on the core etc.).



STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION

**BULK SPECIFIC GRAVITY AND DENSITY OF COMPACTED BITUMINOUS MIXTURES**

Contract No.: \_\_\_\_\_

Material Type: \_\_\_\_\_

Date: \_\_\_\_\_

Gauge Set Number: \_\_\_\_\_

Bulk Specific Gravity =  $\frac{A}{B - C}$   
to nearest 0.001

Core Density = Bulk Specific Gravity x 62.4 lbs/ft<sup>3</sup>  
to nearest 0.001 Mg/m<sup>3</sup> (0.1 lb/ft<sup>3</sup>)

Nuclear Density to nearest 0.001 Mg/m<sup>3</sup> (0.1 lb/ft<sup>3</sup>)

"A" = Weight in grams in air (oven-dry condition)

Difference to nearest 0.001 Mg/m<sup>3</sup> (0.1 lb/ft<sup>3</sup>)

"B" = Weight in grams (saturated surface-dry)

"C" = Weight in grams (immersed in water)

Core No.	Station	"A"	"B"	"C"	Bulk Specific Gravity	Core Density	Nuclear Density	Difference
AVERAGE OF FIVE (5) CORES								

Remarks: \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

Tested By: \_\_\_\_\_

Resident Engineer: \_\_\_\_\_

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION

**BULK SPECIFIC GRAVITY AND DENSITY OF COMPACTED BITUMINOUS MIXTURES**

A. Contract No.: 3925

C. Material Type: PBS Type 2

B. Date: 8/27/2013

D. Gauge Set Number: 121

Bulk Specific Gravity =  $\frac{A}{B - C}$   
to nearest 0.001

Core Density = Bulk Specific Gravity x 62.4 lbs/ft<sup>3</sup>  
to nearest 0.001 Mg/m<sup>3</sup> (0.1 lb/ft<sup>3</sup>)

Nuclear Density to nearest 0.001 Mg/m<sup>3</sup> (0.1 lb/ft<sup>3</sup>)

"A" = Weight in grams in air (oven-dry condition)

Difference to nearest 0.001 Mg/m<sup>3</sup> (0.1 lb/ft<sup>3</sup>)

"B" = Weight in grams (saturated surface-dry)

"C" = Weight in grams (immersed in water)

E. Core No.	F. Station	G. "A"	H. "B"	I. "C"	J. Bulk Specific Gravity	K. Core Density	L. Nuclear Density	M. Difference
1-PM-1	"Z" 125 + 00	1243.1	1248.0	705.4	2.291	143.0	143.1	-0.1
<del>1-PM-2</del>	<del>"Z" 121 + 75</del>	<del>1245.4</del>	<del>1249.2</del>	<del>709.1</del>	<del>2.306</del>	<del>143.9</del>	<del>146.1</del>	<del>2.2</del>
1-PM-3	"Z" 119 + 75	780.5	783.7	437.9	2.257	140.8	139.7	1.1
1-PM-4	"Z" 117 + 50	972.0	987.1	535.3	2.151	134.2	134.7	-0.5
1-PM-5	"Z" 114 + 00	973.6	987.5	539.3	2.172	135.5	135.4	0.1
<del>1-PM-6</del>	<del>"Z" 124 + 75</del>	<del>1100.5</del>	<del>1110.0</del>	<del>613.7</del>	<del>2.217</del>	<del>138.3</del>	<del>136.9</del>	<del>1.4</del>
1-PM-7	"Z" 123 + 00	1235.1	1242.4	686.5	2.222	138.7	139.5	-0.8
<b>N. AVERAGE OF FIVE (5) CORES</b>					2.219	138.4	138.5	

O. Remarks: Correlation was completed on a milled surface

P. Tested By: Leonard Cooper

Q. Resident Engineer: Howard Koothrappali

**BULK SPECIFIC GRAVITY AND DENSITY OF COMPACTED BITUMINOUS MIXTURES**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>A -</b>	Contract number for the material being tested, found in the Contract Plans or Special Provisions (ex. 3925)
<b>B -</b>	Date the cores were taken (ex. 8/27/2013)
<b>C -</b>	Material Type, as specified, in the Contract Plans or Special Provisions (ex. PBS Type 2)
<b>D -</b>	Gauge Set Number, assigned to the gauge that is being used to test the plantmix (ex. 121) <b>NOTE:</b> Consultants shall use the gauge serial number found on the back of the gauge
<b>E -</b>	Core No., number assigned to each core taken from the roadway (ex. 1-PM-1 etc.)
<b>F -</b>	Station, corresponding sample location found on NDOT form 040-017 (station) (ex. "Z" 125 + 00)
<b>G -</b>	Column "A", weight of the oven-dry core in grams in air, per Test Method Nev. T336 (ex. 1243.1)
<b>H -</b>	Column "B", weight of the saturated surface-dry core in grams, per Test Method Nev. T336 (ex. 1248.0)
<b>I -</b>	Column "C", weight of the immersed in water core in grams, per Test Method Nev. T336 (ex. 705.4)
<b>J -</b>	Bulk Specific Gravity, Line G (Oven-Dry Condition) / Line H ((Saturated Surface-Dry) - Line I (Immersed in Water)) = Line J ( Bulk Specific Gravity) (ex. $1243.1 / (1248.0 - 705.4) = 2.291$ )
<b>K -</b>	Core Density, Line J (Bulk Specific Gravity) x 62.4 lbs/ft <sup>3</sup> = Line K (Core Density) (ex. $2.291 \times 62.4 = 143.0$ )
<b>L -</b>	Nuclear Density, Thin-Layer Average Density value obtained at the corresponding test location found on Form 040-017 (ex. 143.1)
<b>M -</b>	Difference, Line K (Core Density) - Line L (Nuclear Density) = M (Difference) (ex. $143.0 - 143.1 = -0.1$ )

**BULK SPECIFIC GRAVITY AND DENSITY OF COMPACTED BITUMINOUS MIXTURES**

**LINE**

**EXPLANATION OF NEEDED INFORMATION**

**N -**

Average, sum of the five cores divided by 5 to get the average of the Bulk Specific Gravity (ex.  $2.291 + 2.257 + 2.151 + 2.172 + 2.222 = 11.093 / 5 = 2.219$ )

Average, sum of the five cores divided by 5 to get the average of the Core Density (ex.  $143.0 + 140.8 + 134.2 + 135.5 + 138.7 = 692.2 / 5 = 138.4$ )

Average, sum of the five cores divided by 5 to get the average of the Nuclear Density (ex.  $143.1 + 139.7 + 134.7 + 135.4 + 139.5 = 692.4 / 5 = 138.5$ )

**Note:** From the initial seven cores taken, discard the two cores with the biggest difference between the Core Density and the Nuclear Density. Use five cores that are the most uniform to obtain the "Average of Five (5) Cores"

**O -**

Remarks, anything that needs to be documented (ex. Correlation was completed on a milled surface.)

**P -**

Tested By, print first and last name of the tester or testers who completed the test (ex. Leonard Cooper)

**Q -**

Resident Engineer or Assistant Resident Engineer signature on that specific crew verifying the accuracy of the reported results. (ex. Howard Koothrappali)

**NOTE:**

**1.**

Unless a core is broken or damaged, five cores shall be used to correlate the Thin-Layer density gauge. If a core is broken or damaged, one of the other cores will be used in its place.

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION

**COMPACTION REPORT FOR PLANTMIX BITUMINOUS PAVEMENTS**  
(Drilled Core Data)

Material Type \_\_\_\_\_ Contract Number \_\_\_\_\_  
 Lift, Lane & Description \_\_\_\_\_ Date \_\_\_\_\_  
 Width and Depth \_\_\_\_\_ Tested By \_\_\_\_\_

**CONTROL DENSITY:**

Theoretical Maximum Density

**AM**

**PM**

Test Number		
Station		
Target Density (Rice)		

**TEST SECTION DENSITY:**

Location of Test Section Station \_\_\_\_\_ to Station \_\_\_\_\_

Random Block Number \_\_\_\_\_

**CORE DATA**

Test Number					
Station					
Distance from Edge					
Left or Right					
Dry Weight					
Weight in Water					
SSD Weight					
Bulk Specific Gravity					
Core Density					
Percent Relative Compaction					

Mean Test Section Density = \_\_\_\_\_

Mean Percent Relative Compaction = \_\_\_\_\_

Test Section: Accepted \_\_\_\_\_ Rejected \_\_\_\_\_

Remarks: \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

Tested By: \_\_\_\_\_

Resident Engineer: \_\_\_\_\_

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION

**COMPACTION REPORT FOR PLANTMIX BITUMINOUS PAVEMENTS**  
(Drilled Core Data)

A. Material Type PBS Type II B. Contract Number 3925  
 C. Lift, Lane & Description Lift 1, Lane 1, NB D. Date 7/12/2010  
 E. Width and Depth 20.0' 2" F. Tested By J. Moren

**CONTROL DENSITY:**

Theoretical Maximum Density	AM	PM
G. Test Number	T-1-1	
H. Station	"PW" 541 + 90	
I. Target Density (Rice)	149.8	

**TEST SECTION DENSITY:**

J. Location of Test Section Station "PW" 544 + 00 to Station "PW" 537 + 40  
 K. Random Block Number 3

**CORE DATA**

L. Test Number	1-PM-1	1-PM-2	1-PM-3	1-PM-4	1-PM-5
M. Station	"PW" 543+75	"PW"541+50	"PW"541+00	"PW"539+50	"PW"537+25
N. Distance from Edge	17'	2'	10'	19'	8'
O. Left or Right	LT.	LT.	LT.	LT.	LT.
P. Dry Weight	1247	1160	1143	1266	1088
Q. Weight in Water	691	648	636	713	602
R. SSD Weight	1261	1168	1155	1274	1099
S. Bulk Specific Gravity	2.188	2.231	2.202	2.257	2.189
T. Core Density	136.5	139.2	137.4	140.8	136.6
U. Percent Relative Compaction	91	93	92	94	91

V. Mean Test Section Density = 138.1

W. Mean Percent Relative Compaction = 92

X. Test Section: Accepted X Rejected \_\_\_\_\_

Y. Remarks: These cores were used to accept this test section per the Standard Specifications for Road and Bridge Construction. This test section met specification and the Resident Engineer was notified of results.

---



---



---

Z. Tested By: J. Moren

AA. Resident Engineer: Samuel Plets

**040-018 REV. 08/06**

**Compaction Report for Plantmix Bituminous Pavements  
(Drilled Core Data)**

<b><u>LINE</u></b>	<b><u>EXPLANATION OF NEEDED INFORMATION</u></b>
<b>A -</b>	Material type as specified, found in the Standard Specifications, Contract Plans or Special Provisions (EX. PBS Type II)
<b>B -</b>	Contract number for the material being tested, found in the Contract Plans or Special Provisions (EX. 3925)
<b>C -</b>	Lift of plantmix that the cores represent, lane that the cores were taken from, direction of the lane the cores were taken from (EX. Lift 1, Lane 1, NB)
<b>D -</b>	Date the sample was taken (EX. 7/12/2010)
<b>E -</b>	Width of the lane the cores were taken from, depth of the lane the cores were taken from (EX. Width - 20.0' Depth - 2")
<b>F -</b>	Tested by, print first and last name of the tester or testers who completed the test (EX. J. Moren)
<b>G -</b>	Test number from the RICE that was taken at the cored location while initial paving was taking place (EX. T-1-1)
<b>H -</b>	Location of sample from the RICE test that was taken while initial paving was taking place prior to compaction per Test Method Nev. T200 (EX. "PW" 541 + 90)
<b>I -</b>	Target density (RICE) from the test taken while initial paving was taking place per Test Method Nev. T335 (EX. 149.8)
<b>J -</b>	Beginning station and ending station of the test section that was determined per Test Method Nev. T335 (EX. "PW" 544 + 00 to "PW" 537 + 40)
<b>K -</b>	Number of the random block that was used to determine the test section per Test Method Nev. T335 (EX. 3)
<b>L -</b>	Test number that was given to the test section that is being cored, found on NDOT form 040-017 (EX. 1-PM-1 through 1-PM-5)
<b>M -</b>	Station where the core was taken from on the roadway, found on NDOT form 040-017 (EX. "PW" 543 + 75)

**040-018 REV. 08/06**

**Compaction Report for Plantmix Bituminous Pavements  
(Drilled Core Data)**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>N -</b>	Distance from the edge of oil the core was drilled, found on NDOT form 040-017 (EX. 17') <b>NOTE:</b> Rounded to the nearest foot and at least 1 foot away from the edge of oil
<b>O -</b>	Side of the mat that the distance from the edge is pulled (EX. LT.)
<b>P -</b>	Dry weight of the core determined per Test Method Nev. T336 (EX. 1247)
<b>Q -</b>	Weight of the core immersed in water per Test Method Nev. T336 (EX. 691)
<b>R -</b>	Saturated surface dry weight of the core per Test Method Nev. T336 (EX. 1261)
<b>S -</b>	Bulk Specific Gravity per Test Method Nev. T335 Line P (Dry weight) / (Line R (SSD Weight) - Line Q (Weight in Water)) = Line S (Bulk Specific Gravity) (EX. $1247 / (1261 - 691) = 2.188$ )
<b>T -</b>	Core density determined per Test Method Nev. T336 Line S (Bulk Specific Gravity) x 62.4 (weight of water in 1lb/ft <sup>3</sup> ) = Line T (Core Density) (EX. $2.188 \times 62.4 = 136.5$ )
<b>U -</b>	(Line T (Core Density) / Line I (Target Density (Rice))) x 100 = Line U (Percent Relative Compaction) (EX. $(136.5 / 149.8) \times 100 = 91.1\% = 91\%$ )
<b>V -</b>	Add all 5 core tests from Line T (Core Density) / 5 = Mean Test Section Density (EX. $136.5 + 139.2 + 137.4 + 140.8 + 136.6 = 690.5 / 5 = 138.1$ )
<b>W -</b>	(Line V (Mean Test Section Density) / Line I (Target Density (RICE))) x 100 = Line W (Mean Percent Relative Compaction) (EX. $138.1 / 149.8 = 0.922 \times 100 = 92.2\% = 92\%$ )
<b>X -</b>	If this test is within specification, it will be accepted. If this test is out of specification it will be rejected. Find the specification in the Standard Specifications.
<b>Y -</b>	Any remarks that need to be documented (EX. These cores were used to accept this test section per the Standard Specifications for Road and Bridge Construction. This test section met specification and the Resident Engineer was notified of the results)
<b>Z -</b>	Tested by, print first and last name of the tester or testers who completed the test (EX. J. Moren)
<b>AA -</b>	Resident Engineer or Assistant Resident Engineer signature on that specific crew (EX. Samuel Ritz)



**STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION  
STRIPING PAINT THICKNESS REPORT**

Date of Test \_\_\_\_\_  
Contract Number \_\_\_\_\_  
Instrument Model \_\_\_\_\_  
Serial Number \_\_\_\_\_

**Location of Test:**

Route \_\_\_\_\_  
Direction of Travel \_\_\_\_\_  
Position of Stripe \_\_\_\_\_  
Station or Milepost \_\_\_\_\_

Name of Operator \_\_\_\_\_

Sampled By \_\_\_\_\_

Name of Tester \_\_\_\_\_

**Average Thickness Reading:** \_\_\_\_\_

**Specification Requirement:** \_\_\_\_\_

**Stripe Color:** \_\_\_\_\_

COMMENTS: \_\_\_\_\_

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

\_\_\_\_\_  
Resident Engineer

**STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION  
STRIPING PAINT THICKNESS REPORT**

A. Date of Test 8/12/2020  
B. Contract Number 3925  
C. Instrument Model Mitutoyo 0-1"  
D. Serial Number No. 389-711-30

**Location of Test:**

E. Route US 50  
F. Direction of Travel East Bound  
G. Position of Stripe Double Yellow (Centerline)  
H. Station or Milepost Milepost CL. 13.22

I. Name of Operator Jammie Rittle

J. Sampled By Sonia Gittel

K. Name of Tester Sonia Gittel

L. Average Thickness Reading: 635um

M. Specification Requirement: 500um

N. Stripe Color: Yellow

O. COMMENTS: This test met specifications. Resident Engineer notified of results.

---

---

---

---

---

P. Jackson L Robertson  
Resident Engineer

**STRIPING PAINT THICKNESS REPORT**

<u>LINE</u>	<u>EXPLANATION OF NEEDED MATERIAL</u>
<b>A -</b>	Date the sample was taken (EX. 8/12/2020)
<b>B -</b>	Contract number for the material being tested, found in the Contract Plans or Special Provisions (EX. 3925)
<b>C -</b>	Model number of the micrometer that is used to measure the thickness of the plate (EX. Mitutoyo 0 – 1")
<b>D -</b>	Serial number found on the micrometer that is used to measure the thickness of the plate (EX. No. 389-711-30)
<b>E -</b>	Route that is getting painted and will be tested (EX. US 50)
<b>F -</b>	Direction of travel (EX. East Bound)
<b>G -</b>	Type and location of the stripe in regards to the roadway (EX. Dbl. Yellow, Centerline)
<b>H -</b>	Station or Milepost at which the striping plate was placed (EX. Milepost CL. 13.22)
<b>I -</b>	First and last name of the operator, who is operating the striping truck (EX. Jammie Rittle)
<b>J -</b>	Print first and last name of the inspector who sampled the material as it was being placed on the roadway (EX. Sonia Gittel)
<b>K -</b>	Print first and last name of the tester or testers who completed the test per Test Method Nev. T510 (EX. Sonia Gittel)
<b>L -</b>	Average thickness of the striping determined by Test Method Nev. T510 (EX. 635um)
<b>M -</b>	Specification requirement found in the Standard Specifications or Special Provisions (EX. Minimum 500um)
<b>N -</b>	Color of the stripe that is being placed on the roadway (EX. Yellow)
<b>O -</b>	Any remarks that need to be documented (EX. This test met specifications. Resident Engineer notified of results.)
<b>P -</b>	Resident Engineer or Assistant Resident Engineer signature on that specific crew (EX. Jackson L. Robertson)

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION

**ABSORPTION AND SPECIFIC GRAVITY FOR FINE AGGREGATE**

Contract No. \_\_\_\_\_

Mix Design No. \_\_\_\_\_

Date \_\_\_\_\_

Source \_\_\_\_\_

Material \_\_\_\_\_

Tested By \_\_\_\_\_

A = Weight of dry sample \_\_\_\_\_

B = Weight of pycnometer filled with water to calibration level \_\_\_\_\_

C = Weight of pycnometer with fine aggregate and water filled to calibration level \_\_\_\_\_

S = Weight of saturated surface-dry sample \_\_\_\_\_

Bulk Specific Gravity  
(Saturated Surface-Dry Basis) =  $\frac{S}{B + S - C}$  \_\_\_\_\_

Percent Absorption =  $\frac{S - A}{A} \times 100$  \_\_\_\_\_

Remarks: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Resident Engineer: \_\_\_\_\_

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION

**ABSORPTION AND SPECIFIC GRAVITY FOR FINE AGGREGATE**

A. Contract No. 3925

B. Mix Design No. STN370DAR

C. Date 07/12/2010

D. Source Hunewill Pit Stockpile

E. Material Concrete Sand

F. Tested By James Bones

G. A = Weight of dry sample 476.1

H. B = Weight of pycnometer filled with water to calibration level 1468.1

I. C = Weight of pycnometer with fine aggregate and water filled to calibration level 1773.0

J. S = Weight of saturated surface-dry sample 500.0

K. Bulk Specific Gravity  
(Saturated Surface-Dry Basis) =  $\frac{S}{B + S - C}$  2.56

L. Percent Absorption =  $\frac{S - A}{A} \times 100$  5.0

M. Remarks: Test met specs.

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

N. Resident Engineer: J. Read

**ABSORPTION AND SPECIFIC GRAVITY FOR FINE AGGREGATE**

<u>Line</u>	<u>Explanation of Needed Information</u>
<b>A -</b>	Actual contract number for the material being tested, found on the Contract Plans, Special Provisions etc. (EX. 3925)
<b>B -</b>	Mix design number assigned by the Materials Division for this specific material (EX. STN370DAR) Note: If this is for mix design submittal there will not be a mix design number assigned to this material yet
<b>C -</b>	Actual date the sample was taken (EX. 7/12/2010)
<b>D -</b>	Name of the location where the material was produced (EX. Hunewill Pit Stockpile)
<b>E -</b>	Type of material as specified, found on the Contract Plans, Special Provisions etc. (EX. Concrete Sand)
<b>F -</b>	Printed name of the tester or testers who completed the test (EX. J. Bones)
<b>G -</b>	Weight of dry sample after drying per Test Method Nev. T112 (EX. 476.1)
<b>H -</b>	Weight of pycnometer filled with water to the calibration level per Test Method Nev. T493 (EX. 1468.1)
<b>I -</b>	Weight of pycnometer with fine aggregate and water filled to the calibration level per Test Method Nev. T493 (EX. 1773.0)
<b>J -</b>	Weight of saturated surface-dry sample per Test Method Nev. T493 (EX. 500.0)
<b>K -</b>	Line J (Weight of Saturated Surface-Dry Sample) / ((Line H (Weight of Pycnometer Filled with Water to Calibration Level) + Line J (Weight of Saturated Surface-Dry Sample) - Line I (Weight of Pycnometer with Fine Aggregate and Water Filled to Calibration Level)) = Line K (Bulk Specific Gravity Saturated Surface-Dry Basis) (EX. $500.0 / (1468.1 + 500.0 - 1773.0) = 2.56$ )
<b>L -</b>	(Line J (Weight of Saturated Surface-Dry Sample) - Line G (Weight of Dry Sample)) / Line G (Weight of Dry Sample) x 100 = Line L (Percent Absorption) (EX. $((500.0 - 476.1) / 476.1) \times 100 = 5.0$ )

**ABSORPTION AND SPECIFIC GRAVITY FOR FINE AGGREGATE**

<u>Line</u>	<u>Explanation of Needed Information</u>
<b>M -</b>	Anything that should be documented. (EX. Test met specs.)
<b>N -</b>	Actual signature of the Resident Engineer or Assistant Engineer on that specific crew (EX. J. Read)

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION

**ABSORPTION AND SPECIFIC GRAVITY FOR COARSE AGGREGATES**

Contract No. \_\_\_\_\_

Mix Design No. \_\_\_\_\_

Date \_\_\_\_\_

Source \_\_\_\_\_

Material \_\_\_\_\_

Tested By \_\_\_\_\_

AR = Weight of Sample in air (as received condition) \_\_\_\_\_

A = Weight of sample in oven-dry condition \_\_\_\_\_

B = Weight of sample in saturated surface-dry condition \_\_\_\_\_

C = Weight of saturated sample immersed in water \_\_\_\_\_

Bulk Specific Gravity  
(oven-dry basis) =  $\frac{A}{B - C}$  \_\_\_\_\_

Bulk Specific Gravity  
(saturated surface-dry basis) =  $\frac{B}{B - C}$  \_\_\_\_\_

Apparent Specific Gravity =  $\frac{A}{A - C}$  \_\_\_\_\_

Percent Absorption =  $\frac{B - A}{A} \times 100$  \_\_\_\_\_

Remarks: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Resident Engineer: \_\_\_\_\_



STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION

**ABSORPTION AND SPECIFIC GRAVITY FOR COARSE AGGREGATES**

A. Contract No. 3925

B. Mix Design No. STN370DAR

C. Date 7/12/2010

D. Source Hunewill Pit

E. Material #67 Rock

F. Tested By James Bones

G. AR = Weight of Sample in air (as received condition) 4405

H. A = Weight of sample in oven-dry condition 4169

I. B = Weight of sample in saturated surface-dry condition 4403

J. C = Weight of saturated sample immersed in water 2451

K. Bulk Specific Gravity (oven-dry basis) =  $\frac{A}{B - C}$  2.14

L. Bulk Specific Gravity (saturated surface-dry basis) =  $\frac{B}{B - C}$  2.26

M. Apparent Specific Gravity =  $\frac{A}{A - C}$  2.43

N. Percent Absorption =  $\frac{B - A}{A} \times 100$  5.6

O. Remarks: Test met specs.  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

P. Resident Engineer: J. Read

**ABSORPTION AND SPECIFIC GRAVITY FOR COARSE AGGREGATES**

<u>LINE</u>	<u>EXPLANATION OF NEEDED MATERIAL</u>
<b>A -</b>	Contract number for the material being tested, found in the Contract Plans or Special Provisions (EX. 3925)
<b>B -</b>	Mix design number assigned by the Materials Division for this specific material (EX. STN370DAR) <b>NOTE:</b> If this is for mix design submittal, there will not be a mix design number assigned to this material at first
<b>C -</b>	Date the sample was taken (EX. 7/12/2010)
<b>D -</b>	Name of the location where the material was produced (EX. Hunewill Pit Stockpile)
<b>E -</b>	Type of material as specified, found in the Contract Plans or Special Provisions (EX. #67 Rock)
<b>F -</b>	Print first and last name of the tester or testers who completed the test (EX. James Bones)
<b>G -</b>	Weight of sample in air (as received condition) after it has been split to the appropriate sample size per Test Method Nev. T200 (EX. 4405)
<b>H -</b>	Weight of sample in oven-dry condition per Test Method Nev. T111 (EX. 4169)
<b>I -</b>	Weight of sample in saturated surface-dry condition after sample soaked per Test Method Nev. T111 (EX. 4403)
<b>J -</b>	Weight of saturated sample immersed in water per Test Method Nev. T111 (EX. 2451)
<b>K -</b>	Line H (Weight of Sample in Oven-Dry Condition) / ((Line I (Weight of Sample in Saturated Surface-Dry Condition) - Line J (Weight of Saturated Sample Immersed in Water)) = Line K (Bulk Specific Gravity Oven-Dry Basis) (EX. 4169 / (4403 - 2451) = 2.14 rounded to the nearest 0.01)
<b>L -</b>	Line I (Weight of Sample in Saturated Surface-Dry Condition) / (Line I (Weight of Sample in Saturated Surface-Dry Condition) - Line J (Weight of Saturated Sample Immersed in Water)) = Line L (Bulk Specific Gravity Saturated Surface-Dry Basis) (EX. 4403 / (4403 - 2451) = 2.26 rounded to the nearest 0.01)

**ABSORPTION AND SPECIFIC GRAVITY FOR COARSE  
AGGREGATES**

**LINE**

**EXPLANATION OF NEEDED MATERIAL**

- M -** Line H (Weight of Sample in Oven-Dry Condition) / (Line H (Weight of Sample in Oven-Dry Condition) - Line J (Weight of Saturated Sample Immersed in Water)) = Line M (Apparent Specific Gravity) (EX.  $4169 / (4169 - 2451) = 2.43$  rounded to the nearest 0.01)
- N -** (Line I (Weight of Sample in Saturated Surface-Dry Condition) - Line H (Weight of Sample in Oven-Dry Condition)) / Line H (Weight of Sample in Oven-Dry Condition)) x 100 = Line N (Percent Absorption) (EX.  $((4403 - 4169) / 4169) \times 100 = 5.6$  rounded to the nearest 0.1)
- O -** Any remarks that need to be documented (EX. Test met spec.)
- P -** Resident Engineer or Assistant Resident Engineer signature on that specific crew (EX. J. Read)

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION

**NUCLEAR GAUGE / SAND CONE CORRELATION FORM**

Date \_\_\_\_\_  
Material Type \_\_\_\_\_  
Material Source \_\_\_\_\_

Contract No. \_\_\_\_\_  
Nuclear Set No. \_\_\_\_\_

**IN-PLACE WET DENSITY CORRELATION** *(with Offsets Disabled)*

	Test No.	Sand Cone Wet Density	Nuclear Gauge Wet Density	
<b>1</b>				
<b>2</b>				
<b>3</b>				Difference (±)
	Average:			

**Sand Cone - Nuclear Gauge = Wet Density Offset**

	Test No.	% Moisture Oven Dry	% Moisture Gauge
<b>1</b>			
<b>2</b>			
<b>3</b>			
	Average:		

**Moisture Correction Factor Equation**

$\frac{\text{Avg. \% Moisture Oven Dry} - \text{Avg. \% Moisture Gauge}}{100 + \text{Avg. \% Moisture Gauge}} \times 1000 =$	-	100 +	x 1000 =	Moisture Offset (MCF)
------------------------------------------------------------------------------------------------------------------------------	---	-------	----------	-----------------------

**MODIFIED PROCTOR COMPACTION TEST RESULTS**

<b>1</b>	Test No.	
	Maximum Dry Density = (d) Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )	
	Optimum Moisture %	

*(if applicable)*

Corr. Max. Dry Density = (D) Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )	
Corr. Optimum Moisture %	

**CHECK TESTS** *(with Offsets Enabled)*

	Test No.	Sand Cone Wet Density	Nuclear Gauge Wet Density	Difference (±)
<b>4</b>				
<b>5</b>				

Maximum Deviation:  
(± 0.032 Mg/m<sup>3</sup> or ± 2.0 lb/ft<sup>3</sup> Allowable) \_\_\_\_\_

Remarks: \_\_\_\_\_  
\_\_\_\_\_

Tested By: \_\_\_\_\_ Resident Engineer: \_\_\_\_\_

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION

**NUCLEAR GAUGE / SAND CONE CORRELATION FORM**

A. Date 7/12/2010 D. Contract No. 3925  
 B. Material Type Type 1 Class B Base / Gran. Bkfl. E. Nuclear Set No. 43  
 C. Material Source Slona Pit, Bardon Materials

**IN-PLACE WET DENSITY CORRELATION** *(with Offsets Disabled)*

F. Test No.	G. Sand Cone Wet Density	H. Nuclear Gauge Wet Density	J. Difference (±)
1	I-1-1B-95 120.4	119.1	
2	I-2-1B-95 126.5	122.0	
3	I-3-1B-95 117.5	115.8	
I. Average:		121.5	119.0
			+ 2.5

*Sand Cone - Nuclear Gauge = Wet Density Offset*

K. Test No.	L. % Moisture Oven Dry	M. % Moisture Gauge
1	I-1-1B-95 11.2	8.8
2	I-2-1B-95 11.0	11.8
3	I-3-1B-95 6.0	5.7
N. Average:		9.4
		8.8

<b>Moisture Correction Factor Equation</b>	O.	P.	R.	
$\frac{\text{Avg. \% Moisture Oven Dry} - \text{Avg. \% Moisture Gauge}}{100 + \text{Avg. \% Moisture Gauge}} \times 1000 =$	9.4	-	8.8	x 1000 =
	100 +	8.8	+ 5.51	Moisture Offset (MCF)
		Q.		

**MODIFIED PROCTOR COMPACTION TEST RESULTS**

S.	1	Test No.	I-1-1B-95
T.		Maximum Dry Density = (d) Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )	111.2
U.		Optimum Moisture %	14.4

*(if applicable)*

V.		Corr. Max. Dry Density = (D) Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )	114.7
W.		Corr. Optimum Moisture %	12.9

**CHECK TESTS** *(with Offsets Enabled)*

X. Test No.	Y. Sand Cone Wet Density	Z. Nuclear Gauge Wet Density	AA. Difference (±)
4	I-4-1B-95 117.2	117.7	- 0.5
5	I-5-1B-95 118.0	119.0	- 1.0

Maximum Deviation: ± 2.0 lb/ft<sup>3</sup> Allowable

BB. - 1.0

CC. Remarks: Gauge met correlation tolerances for Type 1 Class B and Granular Backfill. RE and Contractor notified of results

DD. Tested By: Leonard Cooper EE. Resident Engineer: Howard Koothrappali

NDOT  
040-026  
Rev. 07/14

Distribution: Headquarters Construction, District, Resident Engineer, Contractor

**NUCLEAR GAUGE / SAND CONE CORRELATION FORM**

**LINE**

**EXPLANATION OF NEEDED MATERIAL**

- A -** Date the sample was taken (ex. 7/12/2010)
- B -** Material Type, as specified in the Contract Plans or Special Provisions (ex. Type 1 Class B Base / Gran. Bkfl.)  
**NOTE:** Multiple material types can use the same correlation as long as it's been indicated on NDOT form 040-026
- C -** Material Source, where the material was produced (ex. Sloan Pit, Bardon Materials)
- D -** Contract number for the material being tested, found in the Contract Plans or Special Provisions (ex. 3925)
- E -** Nuclear Set No., assigned to the moisture density gauge that is used for testing the material (ex. 43)  
**NOTE:** Consultants shall use the serial number found on the back of the gauge
- F -** Test No., I indicates informational test number(s) for this particular test. 1 is the number of tests performed on that material, 1B represents the material being tested (refer to the Field Testing Guide - Part 1, for coding) and 95 is the minimum percent compaction required (Standard Specifications or Special Provisions) (ex. I-1-1B-95)
- G -** Sand Cone Wet Density, determined per Test Method Nev. T102 from NDOT form 040-069 (ex. 120.4)
- H -** Nuclear Gauge Wet Density, determined per Test Method Nev. T103 from NDOT form 040-007 (ex. 119.1)
- I -** Average, the sum of all three Line G's (Sand Cone Wet Density) / 3 = Line I (Average) (ex.  $120.4 + 126.5 + 117.5 = 364.4 / 3 = 121.5$  rounded to the nearest 0.1)  
Average, the sum of all three Line H's (Nuclear Gauge Wet Density) / 3 = Line I (Average) (ex.  $119.1 + 122.0 + 115.8 = 356.9 / 3 = 119.0$  rounded to the nearest 0.1)
- J -** Difference ( $\pm$ ), Line I (Sand Cone Wet Density Average) -  
Line I (Nuclear Gauge Wet Density Average) = Line J (ex.  $121.5 - 119.0 = + 2.5$ )  
**NOTE:** Pay attention to the algebraic sign (+ or -)
- K -** Test No., I indicates informational test number(s) for this particular test. 1 is the number of tests performed on that material, 1B represents the material being tested (refer to the Field Testing Guide - Part 1, for coding) and 95 is the minimum percent compaction required (Standard Specifications or Special Provisions) (ex. I-1-1B-95)

**NUCLEAR GAUGE / SAND CONE CORRELATION FORM**

**LINE**

**EXPLANATION OF NEEDED MATERIAL**

- L -** % Moisture Oven Dry, obtained from NDOT form 040-069 (ex. 11.2)
- M -** % Moisture Gauge, obtained from NDOT form 040-007 (ex. 8.8)
- N -** Average, the sum of all three Line L's (% Moisture Oven Dry) / 3 = Line N (Average)  
(ex.  $11.2 + 11.0 + 6.0 = 28.2 / 3 = 9.4$  rounded to the nearest 0.1)  
Average, the sum of all three Line M's (% Moisture Gauge) / 3 = Line N (Average)  
(ex.  $8.8 + 11.8 + 5.7 = 26.3 / 3 = 8.8$  rounded to the nearest 0.1)
- O -** Average % Moisture Oven Dry, Line N (ex. 9.4)
- P -** Average % Moisture Gauge, Line N (ex. 8.8)
- Q -** Average % Moisture Gauge, Line N (ex. 8.8)
- R -** Moisture Offset (MCF), ((Line O (Average % Moisture Oven Dry) -  
Line P (Average % Moisture Gauge)) / (100 + Line Q (Average % Moisture Gauge))  
x 1000 = Line R (ex.  $((9.4 - 8.8) / (100 + 8.8)) \times 1000 = + 5.51$ )  
**NOTE:** Pay attention to the algebraic sign (+ or -)
- S -** Test No., I indicates informational test number(s) for this particular test. 1 is the number of tests performed on that material, 1B represents the material being tested (refer to the Field Testing Guide - Part 1, for coding) and 95 is the minimum percent compaction required (Standard Specifications or Special Provisions) (ex. I-1-1B-95)
- T -** Maximum Dry Density = (d) Mg/m<sup>3</sup> (lb/ft<sup>3</sup>), the highest dry density as established per Test Method Nev. T108 from NDOT form 040-069 (ex. 111.2)
- U -** Optimum Moisture %, as established per Test Method Nev. T108 from NDOT form 040-069 (ex. 14.4)
- V -** Corr. Max. Dry Density = (D) Mg/m<sup>3</sup> (lb/ft<sup>3</sup>), as established per test Method Nev. T108 from NDOT form 040-069 (ex. 114.7)
- W -** Corr. Optimum Moisture %, as established per Test Method Nev. T108 from NDOT form 040-069 (ex. 12.9)
- X -** Test No., I indicates informational test number(s) for this particular test. 4 is the number of tests performed on that material, 1B represents the material being tested (refer to the Field Testing Guide - Part 1, for coding) and 95 is the minimum percent compaction required (Standard Specifications or Special Provisions) (ex. I-4-1B-95)

**NUCLEAR GAUGE / SAND CONE CORRELATION FORM**

<u>LINE</u>	<u>EXPLANATION OF NEEDED MATERIAL</u>
<b>Y -</b>	Sand Cone Wet Density, determined per Test Method Nev. T102 from NDOT form 040-069 (ex. 117.2)
<b>Z -</b>	Nuclear Gauge Wet Density, determined per Test Method Nev. T103 from NDOT form 040-007 (ex. 117.7)
<b>AA -</b>	Difference ( $\pm$ ), Line Y (Sand Cone Wet Density) - Line Z (Nuclear Gauge Wet Density) = Line AA (Difference $\pm$ ) (ex. 117.2 - 117.7 = - 0.5) <b>NOTE:</b> Pay attention to the algebraic sign (+ or -)
<b>BB -</b>	Maximum Deviation, is the largest difference between the sand cones and gauge shots obtained at the same locations. If the number is within $\pm 0.032 \text{ Mg/m}^3$ ( $\pm 2.0 \text{ pcf}$ ), a successful moisture density gauge correlation has been performed. If tolerances exceed re-correlation shall be required (ex. - 1.0 pcf)
<b>CC -</b>	Remarks, anything that needs to be documented (ex. Gauge met correlation tolerances for Type 1 Class B Base and Granular Backfill. RE and Contractor notified of results)
<b>DD -</b>	Tested By, printed first and last name of the tester or testers who completed the test (ex. Leonard Cooper)
<b>EE -</b>	Resident Engineer, or Assistant Resident Engineer signature on that specific crew verifying the accuracy of the reported results. (ex. Howard Koothrappali)

**NOTES:**

1. Gauge correlation can be performed on acceptance tests or on informational pads
2. Gauge rod depth and the in-place sand cone depth shall be the same depth for the gauge correlation. After a successful correlation, a desired rod depth of choice may be used.



STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION

**THEORETICAL MAXIMUM SPECIFIC GRAVITY OF BITUMINOUS PAVING MIXTURES (FIELD METHOD)**

Material Type: \_\_\_\_\_ Date: \_\_\_\_\_  
Tested By: \_\_\_\_\_ Contract Number: \_\_\_\_\_  
Sampled By: \_\_\_\_\_ Test Number (same as burn-off): \_\_\_\_\_  
Sampled From Station: \_\_\_\_\_ Time of Day: \_\_\_\_\_  
Lot / Sublot: \_\_\_\_\_

**FIELD RICE RESULTS**

"A" = Mass of sample in air \_\_\_\_\_  
"B" = Mass of pycnometer and water \_\_\_\_\_  
"C" = Mass of evacuated sample, pycnometer and water \_\_\_\_\_

**APPARENT SPECIFIC GRAVITY**

$A / [(A + B) - C] =$  \_\_\_\_\_

**DENSITY**

S.G. x 1 Mg/m<sup>3</sup> = \_\_\_\_\_ Mg/m<sup>3</sup>  
S.G. x 62.4 lbs/ft<sup>3</sup> = \_\_\_\_\_ lbs/ft<sup>3</sup>

Resident Engineer: \_\_\_\_\_

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION

**THEORETICAL MAXIMUM SPECIFIC GRAVITY OF BITUMINOUS PAVING MIXTURES (FIELD METHOD)**

A. Material Type: PBS Type II B. Date: 7/12/2010  
C. Tested By: Jacob Willis D. Contract Number: 3925  
E. Sampled By: Jacob Willis F. Test Number (same as burn-off): T-1-1  
G. Sampled From Station: "X" 79 + 80 Rt. H. Time of Day: 7:08 A.M.  
I. Lot / Sublot: N/A

**FIELD RICE RESULTS**

J. "A" = Mass of sample in air 1231.1  
K. "B" = Mass of pycnometer and water 2575.2  
L. "C" = Mass of evacuated sample, pycnometer and water 3305.2

**APPARENT SPECIFIC GRAVITY**

M.  $A / [(A + B) - C] =$  2.457

**DENSITY**

N. S.G. x 1 Mg/m<sup>3</sup> = 2.457 Mg/m<sup>3</sup>  
O. S.G. x 62.4 lbs/ft<sup>3</sup> = 153.3 lbs/ft<sup>3</sup>

P. Resident Engineer: *Jeffrey Rodgers*

**THEORETICAL MAXIMUM DENSITY WORKSHEET**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>A -</b>	Material type as specified, found in the Standard Specifications, Contract Plans or Special Provisions (EX. PBS Type II)
<b>B -</b>	Date the sample was taken (EX. 7/12/2010)
<b>C -</b>	Print first and last name of tester or testers who completed the test (EX. Jacob Willis)
<b>D -</b>	Contract number for the material being tested, found in the Contract Plans or Special Provisions (EX. 3925)
<b>E -</b>	Print first and last name of tester or testers who sampled the material to be tested (EX. Jacob Willis)
<b>F -</b>	Test number of the RICE that correlates to the test number for the ignition oven sample per Test Method Nev. T761 (EX. T-1-1)
<b>G -</b>	Approximate sample location, found in the Contract Plans or jobsite survey stakes (EX. "X" 79 + 80 Rt.)
<b>H-</b>	Time of day the sample was taken (EX. 7:08 a.m.) <b>NOTE:</b> One for each half day of paving (one in a.m. and one in p.m.)
<b>I -</b>	Only applies to End Result projects
<b>J -</b>	Mass of sample in the air determined per Test Method Nev. T324 (EX. 1231.1)
<b>K -</b>	Mass of pycnometer, with lid, and water with a meniscus at the top determined per Test Method Nev. T324 (EX. 2575.2)
<b>L -</b>	Total mass of evacuated sample, pycnometer with the lid, water with the meniscus and the material determined per Test Method Nev. T324 (EX. 3305.2)
<b>M -</b>	Line J (Mass of Sample in Air) / [(Line J (Mass of Sample in Air) + Line K (Mass of Pycnometer and Water)) - Line L (Mass of Evacuated Sample, Pycnometer and Water)] = Line M (Apparent Specific Gravity) (EX. $1231.1 / [(1231.1 + 2575.2) - 3305.2] = 2.457$ ) Rounded to the nearest 0.001
<b>N -</b>	Line M (Apparent Specific Gravity) x 1 = Metric Specific Gravity (EX. $2.457 \times 1 = 2.457 \text{ Mg/m}^3$ ) Rounded to the nearest 0.001

**THEORETICAL MAXIMUM DENSITY WORKSHEET**

**LINE**

**EXPLANATION OF NEEDED INFORMATION**

**O -**

Line M (Apparent Specific Gravity) x 62.4 = English specific gravity  
(EX.  $2.457 \times 62.4 = 153.3 \text{ lbs/ft}^3$ )

**P -**

Resident Engineer or Assistant Resident Engineer signature on that specific crew  
(EX. Jeffry Rodgers)





**EMULSION VISCOSITY WORKSHEET**

**LINE**

**EXPLANATION OF NEEDED INFORMATION**

- A -** Contract number for the material being tested, found in the Contract Plans or Special Provisions (EX. 3925)
- B -** All the specifications that apply to the material being tested see the Standard Specifications and Special Provisions etc. (EX. 703.03.02)
- C -** Type of material as specified, found in the Contract Plans or Special Provisions (EX. CMS-2S)
- D -** Sample number for this particular sample in chronological order (EX. 1)
- E -** Number given to the truck and trailer by its company, found on the truck and trailer, on the bill of lading or Certificate of Compliance (EX. Truck # 14, Trailer # 001B)
- F -** Time it takes for the emulsion to come out of the viscometer per Test Method Nev. T759 (EX. Stop watch shows 3 minutes and 21.6 seconds = 201.6 seconds  
Take  $3 \times 60 = 180$ ; Take  $180 + 21.6 = 201.6$ )
- G -** Calibration factor is on the viscometer tube (EX. 1.006)
- H -** Line F (Time in Seconds) x Line G (Calibration Factor) = Line H (Viscosity) rounded to the nearest whole number (EX.  $201.6 \times 1.006 = 202.8 = 203$ )
- I -** Total tons of what this specific test represents, it will be the total tons of the truck or total tons of the trailer, not both truck and trailer combined (EX. 14.04 tons)
- J -** Print first and last name of the tester or testers who completed the test (EX. Jesse Some)
- K -** Date the sample was tested (EX. 6/22/2010)

**NOTES:**

- 1.** Once this sheet is full, turn into the office so they can submit to the Construction Office. Continue the numbering from the previous sheet. DO NOT start over.

**STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION  
REPORT OF FIELD TESTS OF COARSE AND FINE AGGREGATE FOR CONCRETE**

Test Number	Contract Number
Date sampled	Contractor
Sampled by	Mix Design Number
Tested by	Item to be Constructed
Specifications reference	
Quantity represented by sample	
Source of No. 4 coarse aggregate	
Source of No. 57 or 67 coarse aggregate	
Source of No. 467 coarse aggregate	
Source of fine aggregate (sand)	

**COARSE AGGREGATE**

TOTAL %	No. 4	Specs.	No. 57	No. 67	Specs.	No. 467	Specs.	Fines	Total Combined	Comb. Specs.
Passing	-----%		-----%		-----%		-----%			
75 mm (3")										
63 mm (2½")										
50 mm (2")										
37.5 mm (1½")										
25 mm (1")										
19 mm (¾")										
12.5 mm (½")										
9.5 mm (⅜")										
4.75 mm (No. 4)										
2.36 mm (No. 8)										
1.18 mm (No. 16)										
600 µm (No. 30)										
300 µm (No. 50)										
150 µm (No.100)										
75 µm (No. 200)										
Cleaness Value										

**FINE AGGREGATE (SAND)**

Screen size	A % Retained	B % Passing	Specs.	C Total % Retained Fin. Mod. Sieves (100 - "B")	Remarks:
9.5 mm (⅜")					
4.75 mm (No. 4)					
2.36 mm (No. 8)					
1.18 mm (No. 16)					
600 µm (No. 30)					
300 µm (No. 50)					
150 µm (No.100)					
75 µm (No. 200)					

Sand equivalent \_\_\_\_\_ (Specs.) \_\_\_\_\_  
 Fineness Modulus (sum of column ÷ C 100) \_\_\_\_\_ +/- 0.2 of \_\_\_\_\_ Base F.M.

Resident Engineer: \_\_\_\_\_



**STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION  
REPORT OF FIELD TESTS OF COARSE AND FINE AGGREGATE FOR CONCRETE**

<b>A. Test Number</b> T-1-1	<b>K. Contract Number</b> 3925
<b>B. Date sampled</b> 7/12/2010	<b>L. Contractor</b> Granite Construction Co.
<b>C. Sampled by</b> Chris Time	<b>M. Mix Design Number</b> PSPT 375
<b>D. Tested by</b> Chris Time	<b>N. Item to be Constructed</b> Barrier Rail
<b>E. Specifications reference</b> 706.03.01 and 706.03.03	
<b>F. Quantity represented by sample</b> 300 yd <sup>3</sup>	
<b>G. Source of No. 4 coarse aggregate</b> N/A	
<b>H. Source of No. 57 of 67 coarse aggregate</b> Sierra Stone Quarry	
<b>I. Source of No. 467 coarse aggregate</b> N/A	
<b>J. Source of fine aggregate (sand)</b> Tracy Pit	

**COARSE AGGREGATE**

O. TOTAL %	P. No. 4	Q. Specs.	R. No. 57 No. 67	S. Specs.	T. No. 467	U. Specs.	V. Fines	W. Total Combined	X. Comb. Specs.
Passing	-----%		-----%		-----%		-----%		
75 mm (3")									
63 mm (2½")									
50 mm (2")									
37.5 mm (1½")									
25 mm (1")			100	100					
19 mm (¾")			95	90 - 100					
12.5 mm (½")									
9.5 mm (⅜")			23	20 - 55					
4.75 mm (No. 4)			4	0 - 10					
2.36 mm (No. 8)			2	0 - 5					
1.18 mm (No. 16)									
600 µm (No. 30)									
300 µm (No. 50)									
150 µm (No. 100)									
75 µm (No. 200)			1	0 - 1					
<b>Y. Cleanness Value</b>			<b>91</b>	<b>71 Min.</b>					

**FINE AGGREGATE (SAND)**

Z. Screen size	A. AA. % Retained	B. BB. % Passing	CC. Specs.	C. DD. Total % Retained Fin. Mod. Sieves (100 - "B")	EE. Remarks: Test met
9.5 mm (⅜")	0	100	100		specs. Resident
4.75 mm (No. 4)	0.3	99.7	95 - 100	0.3	
2.36 mm (No. 8)	7.0	92.9	80 - 100	7.1	Engineer and
1.18 mm (No. 16)	23.1	62.4	50 - 85	37.6	
600 µm (No. 30)	21.4	41.0	25 - 60	59.0	Contractor notified of
300 µm (No. 50)	7.8	24.5	5 - 30	75.5	
150 µm (No. 100)	14.2	10.3	0 - 10	89.7	results.
75 µm (No. 200)	7.3	3.0	0 - 5		

**FF. Sand equivalent** 88 **GG. (Specs.)** 71 Min.

**HH. Fineness Modulus (sum of column ÷ C 100)** 2.7 **II. +/- 0.2 of** 2.7 **Base F.M.**

**JJ. Resident Engineer:** H. Pally

**REPORT OF FIELD TESTS OF COURSE AND  
FINE AGGREGATE FOR CONCRETE**

<b><u>LINE</u></b>	<b><u>EXPLANATION OF NEEDED INFORMATION</u></b>
<b>A -</b>	Test number for this particular test (EX. T-1-1 T = Acceptance; 1 = first acceptance test of the day; 1 = number of days the material has been tested) NOTE: Test numbering will be consecitively numbered for all sources and mix designs, found in the Field Testing Guide - Part 1.
<b>B -</b>	Date the sample was taken (EX. 7/12/2010)
<b>C -</b>	Print first and last name of the tester or testers who sampled the material (EX. Chris Time)
<b>D -</b>	Print first and last name of the tester or testers who completed the test (EX. Chris Time)
<b>E -</b>	All of the specifications that apply to the material being tested; see the Standard Specifications and Special Provisions (EX. 706.03.01 and 706.03.03)
<b>F -</b>	Total yards of concrete from the Field Testing Guide - Part 2, Minimum Required Samples and Tests: Project frequencies (EX. 300 yd3)
<b>G -</b>	Where the number 4 material was produced, not where it was stockpiled
<b>H -</b>	Where the number 67 material was produced, not where it was stockpiled (EX. Sierra Stone Quarry)
<b>I -</b>	Where the number 467 material was produced, not where it was stockpiled
<b>J -</b>	Where the fine material was produced, not where it was stockpiled (EX. Tracy Pit)
<b>K -</b>	Contract number for the material being tested, found in the Contract Plans or Special Provisions (EX. 3925)
<b>L -</b>	Name of the Prime contractor awarded the contract (EX. Granite Construction Co.)
<b>M -</b>	Number of the Mix Design that the sample represents (Mix Design approved by the Materials Division) (EX. PSPT 375) NOTE: Mix Design shall be on file in the Field Office and copies handed out to the crew
<b>N -</b>	Name of the item being constructed, where the concrete is being placed (EX. Barrier Rail)

**040-035 Rev. 10/09**

**REPORT OF FIELD TESTS OF COURSE AND  
FINE AGGREGATE FOR CONCRETE**

<b><u>LINE</u></b>	<b><u>EXPLANATION OF NEEDED INFORMATION</u></b>
<b>O -</b>	Sieves that could be used for particular materials, depending on the aggregate requirement
<b>P -</b>	No. 4 material percent passing the required sieves from NDOT form 040-013 reported to the whole number
<b>Q -</b>	Specifications for the No. 4 or larger material
<b>R -</b>	No. 57 or No. 67 material percent passing the required sieves from NDOT form 040-013 reported to the whole number
<b>S -</b>	Required specifications for the No. 57 or No. 67
<b>T -</b>	No. 467 material percent passing the required sieves from NDOT form 040-013 reported to the whole number
<b>U -</b>	Specifications for the No. 467 material
<b>V -</b>	Fine material percent passing the required sieves from NDOT form 040-013 NOTE: This column will only be used when combining aggregates for combined gradation requirements
<b>W -</b>	Total combined if combining sieves for aggregates that require combined gradations
<b>X -</b>	Combined specification for this particular mix design
<b>Y -</b>	Value determined by Test Method Nev. T228 (EX. 91) NOTE: This test is only performed on coarse material
<b>Z -</b>	Sieves that are used for fine concrete aggregates
<b>AA -</b>	Percent retained on each sieve determined per Test Method Nev. T206 from NDOT form 040-013 reported to the nearest 0.1
<b>BB -</b>	Percent passing each sieve determined per Test Method Nev. T206 from NDOT form 040-013 reported to the nearest 0.1

**REPORT OF FIELD TESTS OF COURSE AND  
FINE AGGREGATE FOR CONCRETE**

<b><u>LINE</u></b>	<b><u>EXPLANATION OF NEEDED INFORMATION</u></b>
<b>DD -</b>	Fineness Modulus is determined for Fine Aggregates for materials between the No. 4 sieve to the No. 100 sieve. $100 - \text{Line BB (\% Passing)} = \text{Line DD (Total \% Retained Fin. Mod. Sieves)}$ (EX. use the No. 100 sieve $100 - 10.3 = 89.7$ )
<b>EE -</b>	Any remarks that needs to be documented (EX. Test met specs. Resident Engineer and Contractor notified of results)
<b>FF -</b>	Value determined per Test Method Nev. T227 from NDOT form 040-006 reported to the whole number (EX. 88)
<b>GG -</b>	Specifications per Test Method Nev. T227 found in the Standard Specifications or Special Provisions (EX. 71 min.)
<b>HH -</b>	Fineness Modulus is the sum of Lines DD (Total % Retained Fin. Mod. Sieves) / 100 = Fineness Modulus reported to the 0.1 (EX. $0.3 + 7.1 + 37.6 + 59.0 + 75.5 + 89.7 = 269.2 / 100 = 2.7$ )
<b>II -</b>	Base Fineness Modulus is determined by taking the sum of the Fineness Modulus values and dividing by 10. A rolling average is kept of the Fineness Modulus values as the tests are performed. Anything over 10, average tests 2 - 11 or 3 - 12 etc. If there are less than 10 tests taken, all the tests that are completed to date are to be averaged. $\# 1 + \# 2 + \# 3 = \# / 3 = \text{Line II (Base F.M.)}$ NOTE: There will always be a number for the Base Fineness Modules
<b>JJ -</b>	Resident Engineer or Assistant Resident Engineer on that specific crew (EX. H. Polly) specific crew (EX. H. Polly)

**NOTE:**

- 1.** NDOT forms 040-013 and 040-006 are to be submitted with this form
- 2.** If performing a combined gradation and assistance is needed, contact the Independence Assurance Lab or the Quality Assurance Section
- 3.** PCCP is to be reported to the nearest 0.1 on this form. Since the PCCP is a combined gradation, all other concrete is to be reported to the nearest whole number





**RETROREFLECTIVITY MEASUREMENTS**

**LINE**

**EXPLANATION OF NEEDED INFORMATION**

- A -** Contract number for the material being tested, found in the Contract Plans or Special Provisions (EX. 3925)
- B -** Indicate white or yellow as the color of striping that is being tested (EX. White)
- C -** Specification requirement found in the Contract Plans or Special provisions etc. (EX. 375 Minimum)
- D -** Name of the equipment that is being utilized to test the material (EX. LTL-X) Check the current Qualified Product List (QPL) for this contract to determine if the contractor is using an appropriate and approved model
- E -** Date the equipment was last calibrated and serviced (EX. 5/8/2010)
- F -** Type of material that is being tested (EX. Epoxy Pavement Striping)
- G -** Date and time the material was placed (EX. 6-16-10 / 7:00 a.m.)
- H -** Approximate sample location, found in the Contract Plans or jobsite survey stakes (EX. "R2" 7 + 00 LT)
- I -** Direction of traffic in which the striping is being placed (EX. South Bound)
- J -** Line type that is being applied (EX. 4" Solid)
- K -** Date the material was tested for retroreflectivity determined per Test Method Nev. T511 (EX. 7/12/2010)
- L -** Reading indicated by the Retroreflectometer per Test Method Nev. T511 (EX. 395)
- M -** Three additional readings outside of the original five constitute a re-test per Test Method Nev. T511
- N -** Any remarks that need to be documented (EX. All tests meet specifications.)
- O -** Tested by, print first and last name of the tester or testers who completed the test (EX. Martin Hopeful)
- P -** Resident Engineer or Assistant Resident Engineer signature on that specific crew (EX. Tony Hepner)

**040-041 Rev. 3/05**

**RETROREFLECTIVITY MEASUREMENTS**

**LINE**

**EXPLANATION OF NEEDED INFORMATION**

**NOTE:**

Only one color per sheet should be indicated as white and yellow striping have different specified requirements for reflectivity







**PAVEMENT MARKING FILM ADHESION TEST (SECTION 634)**

**LINE**

**EXPLANATION OF NEEDED INFORMATION**

- A -** Contract number for the material being tested, found in the Contract Plans or Special Provisions (EX. 3925)
- B -** Choose white or yellow for the color of striping that is tested (EX. White)
- C -** Specification requirement found in the Contract Plans or Special Provisions (EX. 8 lb Minimum)
- D -** Type of material that is tested (EX. Pavement Marking Film)
- E -** Date the material was placed (EX. 8/15/2010)
- F -** Approximate sample location, found in the Contract Plans or jobsite survey stakes (EX. "LE" 125 + 00)
- G -** Direction of traffic the striping is being placed (EX. East Bound)
- H -** Marking film description that was placed, description can be found in Contract Plans (EX. 4" Marking Film)
- I -** Date the material was tested for adhesion test results per Test Method Nev. T512 (EX. 8/16/2010)
- J -** Value indicated by the clamp scale determined per Test Method Nev. T512 (EX. 10 lb)
- K -** Additional test determined per Test Method Nev. T512
- L -** Any remarks that need to be documented (EX. Tests met specs.)
- M -** Printed name of the tester or testers who completed the test (EX. Jane Mackenna)
- N -** Resident Engineer or Assistant Resident Engineer signature on that specific crew (EX. Kindra Kind)

## NUCLEAR GAUGE OPERATOR'S WORKSHEET FOR CONTROL STRIP DENSITY - PART 1

Material Type \_\_\_\_\_

Contract No. \_\_\_\_\_

Lift & Pad Number \_\_\_\_\_

Date \_\_\_\_\_

Width of Spread \_\_\_\_\_

Station \_\_\_\_\_

Control Strip No. \_\_\_\_\_

Nuclear Set No. \_\_\_\_\_


### TESTS DURING ROLLING

No. of Roller Passes										
Site Number		1	2	3	1	2	3	1	2	3
Density, Mg/m <sup>3</sup> (pcf)	1									
	2									
Average Test Site Density										
Average Density										

No. of Roller Passes										
Site Number		1	2	3	1	2	3	1	2	3
Density, Mg/m <sup>3</sup> (pcf)	1									
	2									
Average Test Site Density										
Average Density										

No. of Roller Passes										
Site Number		1	2	3	1	2	3	1	2	3
Density, Mg/m <sup>3</sup> (pcf)	1									
	2									
Average Test Site Density										
Average Density										

### DENSITY PLOT




## NUCLEAR GAUGE OPERATOR'S WORKSHEET FOR CONTROL STRIP DENSITY - PART 2

Material Type \_\_\_\_\_ Contract No. \_\_\_\_\_  
 Lift & Pad Number \_\_\_\_\_ Date \_\_\_\_\_  
 Width of Spread \_\_\_\_\_ Station \_\_\_\_\_  
 Control Strip No. \_\_\_\_\_ Nuclear Set No. \_\_\_\_\_

### DIAGRAM OF CONTROL STRIP

Show: centerline, stations at ends of control strip, stations at test sites, site number and offset from edge of oil or centerline.



### TESTS AFTER ROLLING

Site Number		1	2	3	4	5
Density, Mg/m <sup>3</sup> (pcf)	1					
	2					
Average Test Site Density						

Site Number		6	7	8	9	10
Density, Mg/m <sup>3</sup> (pcf)	1					
	2					
Average Test Site Density						

Mean Control Strip Density, Mg/m<sup>3</sup> (pcf) = \_\_\_\_\_

Rolling Pattern: \_\_\_\_\_  
 \_\_\_\_\_

Remarks (initial compaction or recompaction): \_\_\_\_\_  
 \_\_\_\_\_

Tested by: \_\_\_\_\_ Resident Engineer: \_\_\_\_\_

## NUCLEAR GAUGE OPERATOR'S WORKSHEET FOR CONTROL STRIP DENSITY - PART 1

A. Material Type <u>Cold Recycle</u>	B. Contract No. <u>3925</u>
C. Lift & Pad Number <u>1 / NB Lane # 1</u>	D. Date <u>7/12/2010</u>
E. Width of Spread <u>15.5'</u>	F. Station <u>"X" 800+68 to "X" 803+00</u>
G. Control Strip No. <u>1</u>	H. Nuclear Set No. <u>133</u>

### TESTS DURING ROLLING

I. No. of Roller Passes		Pneumatic Tire Roller - 1			Pneumatic Tire Roller - 2			Steel Wheel Roller - 3		
J. Site Number		1	2	3	1	2	3	1	2	3
K. Density, Mg/m <sup>3</sup> (pcf)	1	114.1	115.0	125.2	118.5	116.9	124.0	118.9	118.6	120.9
	2	115.6	117.6	124.2	119.3	116.9	123.8	118.8	117.2	122.6
L. Average Test Site Density		114.9	116.3	124.7	118.9	116.9	123.9	118.9	117.9	121.8
M. Average Density		118.6			119.9			119.5		

No. of Roller Passes		Steel Wheel Roller - 4			Steel Wheel Roller - 5			Steel Wheel Roller - 6		
Site Number		1	2	3	1	2	3	1	2	3
Density, Mg/m <sup>3</sup> (pcf)	1	119.8	122.8	124.8	121.5	123.4	124.1	121.5	123.4	124.0
	2	121.2	123.7	126.9	122.3	123.1	127.3	122.3	123.1	127.1
Average Test Site Density		120.5	123.3	125.9	121.9	123.3	125.7	121.9	123.3	125.6
Average Density		123.2			123.6			123.6		

No. of Roller Passes										
Site Number		1	2	3	1	2	3	1	2	3
Density, Mg/m <sup>3</sup> (pcf)	1									
	2									
Average Test Site Density										
Average Density										

**N. DENSITY PLOT**




## NUCLEAR GAUGE OPERATOR'S WORKSHEET FOR CONTROL STRIP DENSITY - PART 2

O. Material Type Cold Recycle P. Contract No. 3925  
 Q. Lift & Pad Number 1 / NB Lane #1 R. Date 7/12/2010  
 S. Width of Spread 15.5' T. Station "X"800+68 to "X" 803+00  
 U. Control Strip No. 1 V. Nuclear Set No. 133

### W. DIAGRAM OF CONTROL STRIP

Show: centerline, stations at ends of control strip, stations at test sites, site number and offset from edge of oil or centerline.



### TESTS AFTER ROLLING

X. Site Number		1	2	3	4	5
Y. Density, Mg/m <sup>3</sup> (pcf)	1	121.5	123.4	124.0	125.2	125.3
	2	122.3	123.1	127.1	125.3	123.6
Z. Average Test Site Density		121.9	123.3	125.6	125.3	124.5

AA. Site Number		6	7	8	9	10
BB. Density, Mg/m <sup>3</sup> (pcf)	1	125.7	127.0	119.2	123.4	126.9
	2	125.3	126.0	117.0	123.6	126.4
CC. Average Test Site Density		125.5	126.5	118.1	123.5	126.7

DD. Mean Control Strip Density, Mg/m<sup>3</sup> (pcf) = 124.1

EE. Rolling Pattern: Two rubber passes and two steel passes for this control strip

FF. Remarks (initial compaction or recompaction): Initial Compaction

GG. Tested by: Stew Simon

HH. Resident Engineer Jenell Rice

**NUCLEAR GAUGE OPERATOR'S WORKSHEET FOR CONTROL STRIP DENSITY - PART 1 AND 2**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>A -</b>	Type of material as specified, found in the Contract Plans or Special Provisions (EX. Cold Recycle)
<b>B -</b>	Contract number for the material being tested, found in the Contract Plans or Special Provisions (EX. 3925)
<b>C -</b>	Lift and pad that is currently being tested (EX. 1st lift, Northbound lane #1)
<b>D -</b>	Date the compactions were taken (EX. 7/12/2010)
<b>E -</b>	Total width of the pavement mat being tested (EX. 15.5')
<b>F -</b>	Station to station for the control strip test section found in the Contract Plans, or jobsite survey stakes (EX. "X" 800 + 68 to "X" 803 + 00)
<b>G -</b>	Control Strip number shall be numbered in chronological order starting with one. Numbering will start over for the re-roll or different material (EX. 1)
<b>H -</b>	Set number assigned to the gauge that is being used to test the material (EX. 133) NOTE: Consultants are to use the gauge serial number found on the back of their gauge
<b>I -</b>	One pass of a roller is described as one complete pass, forward and back across the entire width of the mat (EX. 1 is the number of passes the pneumatic tire roller made)
<b>J -</b>	Three random site numbers determined per Test method Nev. T750, continue to use the same roller until the curve levels off or drops off (EX. Site Number 1, 2 and 3)
<b>K -</b>	Two one minute density shots performed at each of the three random site locations per Test Method Nev. T750 (EX. 114.1 and gauge rotated 180° is 115.6)
<b>L -</b>	Average of the two densities from Line K (Density) (EX. $114.1 + 115.6 = 229.7 / 2 = 114.85 = 114.9$ round to the nearest 0.1)
<b>M -</b>	Average of Line L (Three Average Test Site Densities) equals average density (EX. $114.9 + 116.3 + 124.7 = 355.9 / 3 = 118.63 = 118.6$ round to the nearest)
<b>N -</b>	Plot the Average Densities from Line M (Average Density) for Line I (No. of Roller Passes) (EX. 118.6, 119.9, 119.5, 123.2, 123.6, 123.6)



**NUCLEAR GAUGE OPERATOR'S WORKSHEET FOR CONTROL STRIP DENSITY - PART 1 AND 2**

<b><u>LINE</u></b>	<b><u>EXPLANATION OF NEEDED INFORMATION</u></b>
<b>O -</b>	Type of material as specified, found in the Contract Plans or Special Provisions (EX. Cold Recycle)
<b>P -</b>	Contract number for the material being tested, found in the Contract Plans or Special Provisions (EX. 3925)
<b>Q -</b>	Lift and pad that is currently being tested (EX. 1st lift, Northbound Lane #1)
<b>R -</b>	Date the compactions were taken (EX. 7/12/2010)
<b>S -</b>	Total width of the pavement being tested (EX. 15.5')
<b>T -</b>	Station to station for the control strip test section found on the Contract Plans, or jobsite survey stakes (EX. "X" 800 + 68 to "X" 803 + 00)
<b>U -</b>	Control Strip shall be numbered in chronological order starting with one. Numbering will start over for the re-roll or different material (EX. 1)
<b>V -</b>	Set number assigned to the gauge that is being used to test the material (EX. 133) NOTE: Consultants are to use the gauge serial number found on the back of their gauge
<b>W -</b>	Diagram of control strip illustrates all 10 test locations. Indicate the site location labeled 1 to 10 with each corresponding station, distance from edge, centerline location and the beginning and ending station of the control strip
<b>X -</b>	Ten random site numbers per Test method Nev. T750
<b>Y -</b>	Two one minute density shots performed at each of the ten random number site locations per Test Method Nev. T750 (EX. 121.5 and gauge rotated 180° is 122.3)
<b>Z -</b>	Average of the two densities from Line Y (Density) (EX. $121.5 + 122.3 = 243.8/2 = 121.9$ rounded to the nearest 0.1)
<b>AA -</b>	Ten random site numbers determined per Test method Nev. T750
<b>BB -</b>	Two one minute density shots performed at each of the ten random number site locations per Test Method Nev. T750 (EX. 125.7 and gauge rotated 180° is 125.3)

**NUCLEAR GAUGE OPERATOR'S WORKSHEET FOR CONTROL STRIP DENSITY - PART 1 AND 2**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>CC -</b>	Average of the two densities from Line BB (Density) (EX. $125.7 + 125.3 = 251.0 / 125.5$ rounded to the nearest 0.1)
<b>DD -</b>	Average of Line Z (Average Test Site Densities) + Line CC (Average Test Site Densities) / 10 = Line DD (Mean Control Strip Density) (EX. $121.9 + 123.3 + 125.6 + 125.3 + 124.5 + 125.5 + 126.5 + 118.1 + 123.5 + 126.7 = 1240.9 / 10 = 124.09 = 124.1$ )
<b>EE -</b>	Record and indicate the rolling pattern per Test Method Nev. T750 (EX. Two rubber passes and two steel passes for this control strip) this information comes from Part I of this form NOTE: If the density for one roller does not gain 1 pound or more do not use that pass as part of the rolling pattern
<b>FF -</b>	Any remarks that needs to be documented (EX. Initial compaction)
<b>GG -</b>	Tested by, print first and last name of the tester or testers who performed the test (EX. Stew Simon)
<b>HH -</b>	Resident Engineer or Assistant Resident Engineer signature on that specific crew (EX. Jenell Rice)

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION  
**FIELD MATERIAL SIEVE TEST / BITUMINOUS RATIO BY IGNITION METHOD**

Contract No.: \_\_\_\_\_ JM F No.: \_\_\_\_\_ Tested By: \_\_\_\_\_  
 Type of Mixture: \_\_\_\_\_ Station: \_\_\_\_\_ Location: \_\_\_\_\_  
 Asphalt Grade: \_\_\_\_\_ Test No.: \_\_\_\_\_ Date Sampled: \_\_\_\_\_  
 Mix Design No.: \_\_\_\_\_ Furnace Temp: \_\_\_\_\_ Date Tested: \_\_\_\_\_

SIEVE	WEIGHT RETAINED	% RETAINED	% PASSING	JOB-MIX	SPEC
25 mm (1")					
19 mm (3/4")					
12.5 mm (1/2")					
9.5 mm (3/8")					
4.75 mm (No. 4)					
2.00 mm (No. 10)					
1.18 mm (No. 16)					
425 µm (No. 40)					
300 µm (No. 50)					
150 µm (No. 100)					
75 µm (No. 200)					
Pan			(MF) Mass After _____	Bitumen Ratio From Job-mix: _____	
Wash			Mass After Wash _____		
Mass After			Mass - 200 Wash _____		

**CALIBRATION FACTOR:**  
 Factor \_\_\_\_\_  
 Date Performed \_\_\_\_\_  
 Furnace No. \_\_\_\_\_  
 \*Calibration Factor from form  
 NDOT 040-053

**MOISTURE CORRECTION:**  

$$\left[ \left( \frac{\text{_____}}{(A)} - \frac{\text{_____}}{(B)} \right) \div \frac{\text{_____}}{(B)} \right] \times 100 = \frac{\text{_____}}{MC} \%$$
 Initial Mass      Final Mass      Final Mass

**BITUMEN RATIO FROM TAPE CALCULATION:**  

$$\frac{\text{_____}}{(MI)} \text{ Dry Mass} \quad \frac{\text{_____}}{(B.R.)} \% \text{ Printed Tape} \quad - \quad \frac{\text{_____}}{(MC)} \% = \frac{\text{_____}}{B.R.} \%$$

**\*\*BITUMEN RATIO FROM MANUAL CALCULATION:**  

$$\left[ \left( \frac{\text{_____}}{(MI)} - \frac{\text{_____}}{(MF)} \right) \div \frac{\text{_____}}{(MF)} \right] \times 100 \text{ *}\pm \frac{\text{_____}}{(CF)} \% - \frac{\text{_____}}{(MC)} \% = \frac{\text{_____}}{B.R.} \%$$
 Dry Mass      Mass After      Mass After

\* NOTE: add (-) correction factors and subtract (+) correction factors  
 \*\*NOTE: If the furnace can't automatically calculate a corrected bitumen ratio, calculations can be performed manually.  
 Only fill in Tape Calculation or Manual Calculation, not both.

Resident Engineer: \_\_\_\_\_



**040-050 Rev. 11/10**

**FIELD MATERIAL SIEVE TEST / BITUMINOUS RATIO BY  
IGNITION METHOD**

<b><u>LINE</u></b>	<b><u>EXPLANATION OF NEEDED INFORMATION</u></b>
<b>A -</b>	Contract number for the material being tested, found in the Contract Plans or Special Provisions (EX. 3925)
<b>B -</b>	Job Mix Formula number assigned by the Resident Engineer (EX. 1)
<b>C -</b>	Print first and last name of the tester or testers who completed the test (EX. Stew Simon)
<b>D -</b>	Type of plantmix placed on the jobsite found on the Mix Design from the Materials Division (EX. PBS Type IIC)
<b>E -</b>	Approximate sample location, found in the Contract Plans or jobsite survey stakes (EX. "X" 7 + 22 RT.)
<b>F -</b>	Location from where the sample was taken, lanes travel direction, lane number and the side of center line the sample was taken (EX. NB / #1 lane / RT.)
<b>G -</b>	Grade of asphalt that is utilized in the plantmix, found on the approved Mix Design provided by the Materials Division (EX. PG64-28NV)
<b>H -</b>	Acceptance Test number for this particular test (EX. T-1-1 T = Acceptance Test; 1 = First acceptance test of the day; 1 = Number of days the material has been tested)
<b>I -</b>	Date the sample was taken (EX. 7/12/2010)
<b>J -</b>	Mix design number given to this material by the Materials Division (EX. BF10-31)
<b>K -</b>	Temperature of the ignition furnace that the Correction Factor was established, will either be 482°C or 538°C per Test Method Nev. T61 (EX. 482°C)
<b>L -</b>	Date the material was tested (EX. 7/12/2010)
<b>M -</b>	List of sieves that could be used in the testing of specified material, found in the Special Provisions or Standard Specifications
<b>N -</b>	Weight of the material retained on each specified sieve determined per Test Method Nev. T206 NOTE: This number is reported to the whole number

**FIELD MATERIAL SIEVE TEST / BITUMINOUS RATIO BY  
IGNITION METHOD**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>O -</b>	Take the weight retained from Line N (Weight Retained) / Line N (Mass After) x 100 = Line O (% Retained) NOTE: Reported to the nearest tenth (EX. # 200 sieve is 59 / 2786 x 100 = 2.1%) NOTE: All of Column O. shall add up to 100%. If it does not, the largest sieve shall be adjusted accordingly so Column O equals 100%. If Column O has to be adjusted by more than .3 the sieve is invalid and another sieve shall be ran
<b>P -</b>	Take Line S (% Passing) + Line R (% Retained) = Line S (% Passing) (EX. #200 sieve 5.5 + 2.1 = 7.6)
<b>Q -</b>	Job Mix range is sound on the Job Mix Formula written by the Resident Engineer NOTE: Make sure the current JMF is used
<b>R -</b>	Specification range for the material being tested, found in the Special Provisions or Standard Specifications
<b>S -</b>	Weight of the entire sample (Mass After) after it has been burned off determined per Test Method Nev. T761. Is usually taken off of the ticket (EX. 2786) or can be manually weighed if there is a problem with the ticket print out.
<b>T -</b>	Weight of the material (Mass After Wash) after it has been burned off, washed and dried determined per Test Method Nev. T761 and T206 (EX. 2658)
<b>U -</b>	Line S (Mass After (MF)) - Line T (Mass After Wash) = Line U (Mass - 200 Wash) (EX. 2786 - 2658 = 128)
<b>V -</b>	Bitumen Ratio found on the current Job Mix Formula written by the Resident Engineer (EX. 5.3%)
<b>W -</b>	Correction Factor that is determined prior to any acceptance testing for this Mix Design and current JMF per Test Method Nev. T761, enter this number into the ignition furnace prior to performing the burn-off procedure (EX. + 0.96) NOTE: Each ignition furnace and mix design have it's own correction factor
<b>X -</b>	Date the current correction factor being used was determined (EX. 7/1/2010)
<b>Y -</b>	Number assigned to the ignition furnace that is being used to perform the burn-offs, found on the outside of the furnace (EX. 250400)

**040-050 Rev. 11/10**

**FIELD MATERIAL SIEVE TEST / BITUMINOUS RATIO BY  
IGNITION METHOD**

<b><u>LINE</u></b>	<b><u>EXPLANATION OF NEEDED INFORMATION</u></b>
<b>Z -</b>	Initial Mass of PBS Type IIC determined per Test Method Nev. T306 (EX. 706.9)
<b>AA -</b>	Final Mass of PBS Type IIC determined per Test Method Nev. T306 (EX. 705.6)
<b>BB -</b>	Final Mass of PBS Type IIC determined per Test Method Nev. T306 (EX. 705.6)
<b>CC -</b>	Line Z (Initial Mass) - Line AA (Final Mass) / Line BB (Final Mass) x 100 = Line CC (Moisture Correction) (EX. 706.9 - 705.6 / 705.6 x 100 = 0.18%)
<b>DD -</b>	Weight of the sample (Dry Mass) that is placed in the baskets prior to the burn off per Test Method Nev. T761 (EX. 2968.2)
<b>EE -</b>	Bitumen Ratio off of the printed ticket from the Muffle Furnace (EX. 5.65)
<b>FF -</b>	Moisture correction value from Line CC (Moisture Correction) determined per Test Method Nev. T306 (EX. 0.18%)
<b>GG -</b>	Line EE (Bitumen Ratio) - Line FF (Moisture Content) = Line GG (Bitumen Ratio) (EX. Ticket says 5.65 - 0.18 = 5.47%) Report to the nearest 0.1 as 5.5% on NDOT form 040-011)
<b>HH -</b>	NOTE: Manual Calculation shall only be used if the printed tape cannot be used (EX. power failure during burn-off, approval from Quality Assurance to manually calc etc.)
<b>II -</b>	Resident Engineer or Assistant Resident Engineer on that specific crew (EX. R. John)

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION

**REPORT OF CALIBRATION FACTOR (INCLUDING WEEKLY CHECKS) USING THE IGNITION FURNACE METHOD**

Contract No.: \_\_\_\_\_ Tested By: \_\_\_\_\_ Date: \_\_\_\_\_  
 Mix Design No.: \_\_\_\_\_ JMFB No.: \_\_\_\_\_  
 Ignition Oven No.: \_\_\_\_\_ Calibration Factor: \_\_\_\_\_  
 Date Lift Test Taken: \_\_\_\_\_ Lift Test Result: \_\_\_\_\_ Lift Test Range: - 3.2 to - 8.2  
 Ignition Oven at Room Temperature for Lift Test: YES or NO Date Ignition Oven Cleaned: \_\_\_\_\_

Test No.	C.F.	Temperature	Accept or Reject
1			
2			
3			
4			
5			

Asphalt Source: \_\_\_\_\_  
 Asphalt Grade: \_\_\_\_\_  
 Type of Mixture: \_\_\_\_\_

<p><b>Calibration Factor (C.F.) From Printed Tape:</b></p> $\frac{\text{BITUMEN RATIO FROM PRINTED TICKET}}{\text{ACTUAL BITUMEN RATIO FROM HOTPLANT CHECK}} = \text{C.F. } \underline{\hspace{2cm}}$ <p><small>*Only use the manual calculation if there is a power failure during the test or ticket fails to print.</small></p> $\left\{ \left[ \frac{\text{Dry Mass} - \text{Mass After}}{\text{Mass After}} \right] \div \text{Bitumen Ratio} \right\} \times 100 = \underline{\hspace{2cm}}$	<p>Basket Tare Weight (g): _____</p> <p>Wt. of Basket + Sample (g): _____</p> <p>Wt. of Bask. + Samp. in Ign. Oven (g): _____</p>
<p><b>Calibration Factor (C.F.) From Printed Tape:</b></p> $\frac{\text{BITUMEN RATIO FROM PRINTED TICKET}}{\text{ACTUAL BITUMEN RATIO FROM HOTPLANT CHECK}} = \text{C.F. } \underline{\hspace{2cm}}$ <p><small>*Only use the manual calculation if there is a power failure during the test or ticket fails to print.</small></p> $\left\{ \left[ \frac{\text{Dry Mass} - \text{Mass After}}{\text{Mass After}} \right] \div \text{Bitumen Ratio} \right\} \times 100 = \underline{\hspace{2cm}}$	<p>Basket Tare Weight (g): _____</p> <p>Wt. of Basket + Sample (g): _____</p> <p>Wt. of Bask. + Samp. in Ign. Oven (g): _____</p>
<p><b>Calibration Factor (C.F.) From Printed Tape:</b></p> $\frac{\text{BITUMEN RATIO FROM PRINTED TICKET}}{\text{ACTUAL BITUMEN RATIO FROM HOTPLANT CHECK}} = \text{C.F. } \underline{\hspace{2cm}}$ <p><small>*Only use the manual calculation if there is a power failure during the test or ticket fails to print.</small></p> $\left\{ \left[ \frac{\text{Dry Mass} - \text{Mass After}}{\text{Mass After}} \right] \div \text{Bitumen Ratio} \right\} \times 100 = \underline{\hspace{2cm}}$	<p>Basket Tare Weight (g): _____</p> <p>Wt. of Basket + Sample (g): _____</p> <p>Wt. of Bask. + Samp. in Ign. Oven (g): _____</p>
<p><b>Calibration Factor (C.F.) From Printed Tape:</b></p> $\frac{\text{BITUMEN RATIO FROM PRINTED TICKET}}{\text{ACTUAL BITUMEN RATIO FROM HOTPLANT CHECK}} = \text{C.F. } \underline{\hspace{2cm}}$ <p><small>*Only use the manual calculation if there is a power failure during the test or ticket fails to print.</small></p> $\left\{ \left[ \frac{\text{Dry Mass} - \text{Mass After}}{\text{Mass After}} \right] \div \text{Bitumen Ratio} \right\} \times 100 = \underline{\hspace{2cm}}$	<p>Basket Tare Weight (g): _____</p> <p>Wt. of Basket + Sample (g): _____</p> <p>Wt. of Bask. + Samp. in Ign. Oven (g): _____</p>
<p><b>Calibration Factor (C.F.) From Printed Tape:</b></p> $\frac{\text{BITUMEN RATIO FROM PRINTED TICKET}}{\text{ACTUAL BITUMEN RATIO FROM HOTPLANT CHECK}} = \text{C.F. } \underline{\hspace{2cm}}$ <p><small>*Only use the manual calculation if there is a power failure during the test or ticket fails to print.</small></p> $\left\{ \left[ \frac{\text{Dry Mass} - \text{Mass After}}{\text{Mass After}} \right] \div \text{Bitumen Ratio} \right\} \times 100 = \underline{\hspace{2cm}}$	<p>Basket Tare Weight (g): _____</p> <p>Wt. of Basket + Sample (g): _____</p> <p>Wt. of Bask. + Samp. in Ign. Oven (g): _____</p>

Remarks: \_\_\_\_\_

Resident Engineer: \_\_\_\_\_  
 NDOT  
 040-053  
 Rev. 10/20

Distribution: Headquarters Construction, District, Resident Engineer, Contractor



STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION

**REPORT OF CALIBRATION FACTOR (INCLUDING WEEKLY CHECKS) USING THE IGNITION FURNACE METHOD**

A. Contract No.: 4100      B. Tested By: J. Powell      C. Date: 10/1/2020  
D. Mix Design No.: BF20-212      E. JMF No.: 1  
F. Ignition Oven No.: 123456      G. Calibration Factor: + 0.96  
H. Date Lift Test Taken: 10/1/20      I. Lift Test Result: - 4.7      Lift Test Range: - 3.2 to - 8.2  
J. Ignition Oven at Room Temperature for Lift Test: YES or NO      K. Date Ignition Oven Cleaned: 9/28/20

L. Test No.	M. C.F.	N. Temperature	O. Accept or Reject	
1	I-1-1	+ 1.13	538	Reject
2	I-2-1	- 0.78	482	Reject
3	I-3-1	+ 0.94	482	Accept
4	I-4-1	+ 0.97	482	Accept
5	I-5-1	+ 1.05	482	Reject

P. Asphalt Source: Marathon - Fernley  
Q. Asphalt Grade: PG64-28NV  
R. Type of Mixture: PBS Type 2 w/RAP

<p><b>Calibration Factor (C.F.) From Printed Tape:</b>  <u>6.43</u> - <u>5.30</u> = X. C.F. <u>+ 1.13</u>  V. BITUMEN RATIO FROM PRINTED TICKET      W. ACTUAL BITUMEN RATIO FROM HOTPLANT CHECK</p> <p>*Only use the manual calculation if there is a power failure during the test or ticket fails to print.  {{{ <u>2750.0</u> - _____ } ÷ _____ } 100 } = _____  Y. Dry Mass      Mass After      Mass After      Bitumen Ratio</p>	<p>S. Basket Tare Weight (g): <u>3086.4</u>  T. Wt. of Basket + Sample (g): <u>5836.4</u>  U. Wt. of Bask. + Samp. in Ign. Oven (g): <u>5833.8</u></p>
<p><b>Calibration Factor (C.F.) From Printed Tape:</b>  <u>4.52</u> - <u>5.30</u> = C.F. <u>- 0.78</u>  BITUMEN RATIO FROM PRINTED TICKET      ACTUAL BITUMEN RATIO FROM HOTPLANT CHECK</p> <p>*Only use the manual calculation if there is a power failure during the test or ticket fails to print.  {{{ <u>2750.4</u> - _____ } ÷ _____ } 100 } = _____  Dry Mass      Mass After      Mass After      Bitumen Ratio</p>	<p>Basket Tare Weight (g): <u>3072.7</u>  Wt. of Basket + Sample (g): <u>5823.1</u>  Wt. of Bask. + Samp. in Ign. Oven (g): <u>5822.8</u></p>
<p><b>Calibration Factor (C.F.) From Printed Tape:</b>  <u>6.24</u> - <u>5.30</u> = C.F. <u>+ 0.94</u>  BITUMEN RATIO FROM PRINTED TICKET      ACTUAL BITUMEN RATIO FROM HOTPLANT CHECK</p> <p>*Only use the manual calculation if there is a power failure during the test or ticket fails to print.  {{{ <u>2752.3</u> - _____ } ÷ _____ } 100 } = _____  Dry Mass      Mass After      Mass After      Bitumen Ratio</p>	<p>Basket Tare Weight (g): <u>3086.4</u>  Wt. of Basket + Sample (g): <u>5838.7</u>  Wt. of Bask. + Samp. in Ign. Oven (g): <u>5839.4</u></p>
<p><b>Calibration Factor (C.F.) From Printed Tape:</b>  <u>6.27</u> - <u>5.30</u> = C.F. <u>+ 0.97</u>  BITUMEN RATIO FROM PRINTED TICKET      ACTUAL BITUMEN RATIO FROM HOTPLANT CHECK</p> <p>*Only use the manual calculation if there is a power failure during the test or ticket fails to print.  {{{ <u>2749.7</u> - _____ } ÷ _____ } 100 } = _____  Dry Mass      Mass After      Mass After      Bitumen Ratio</p>	<p>Basket Tare Weight (g): <u>3072.7</u>  Wt. of Basket + Sample (g): <u>5822.4</u>  Wt. of Bask. + Samp. in Ign. Oven (g): <u>5826.7</u></p>
<p><b>Calibration Factor (C.F.) From Printed Tape:</b>  _____ - <u>5.30</u> = C.F. <u>+ 1.05</u>  BITUMEN RATIO FROM PRINTED TICKET      ACTUAL BITUMEN RATIO FROM HOTPLANT CHECK</p> <p>*Only use the manual calculation if there is a power failure during the test or ticket fails to print.  {{{ <u>2747.9</u> - <u>2583.8</u> } ÷ <u>2583.8</u> } 100 } = <u>6.35</u>  Z. Dry Mass      AA. Mass After      BB. Mass After      CC. Bitumen Ratio</p>	<p>Basket Tare Weight (g): <u>3086.4</u>  Wt. of Basket + Sample (g): <u>5834.3</u>  Wt. of Bask. + Samp. in Ign. Oven (g): <u>5830.9</u></p>

DD. Remarks: Used I-3-1 and I-4-1 for the calibration factor. I-1-1 exceeded 1.0%, dropped the temperature to 482°C for I-2-1. Manually calculated I-5-1, generator shut off during burn-off.

EE. Resident Engineer: R. John

NDOT  
040-053  
Rev. 10/20

Distribution: Headquarters Construction, District, Resident Engineer, Contractor

**REPORT OF CALIBRATION FACTOR (INCLUDING WEEKLY CHECKS) USING THE IGNITION OVEN METHOD**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>A -</b>	Contract Number, for the material being tested, found in the Contract Plans or Special Special Provisions (4100)
<b>B -</b>	Tested By, print first and last name of the tester or testers who completed the test (EX. J. Powell)
<b>C -</b>	Date, the Calibration Factor was performed (EX. 10/1/2020)
<b>D -</b>	Mix Design Number, given to this material by the Materials Division (EX. BF20-212)
<b>E -</b>	Job Mix Formula Number, assigned and created by the Resident Engineer (EX. 1)
<b>F -</b>	Ignition Oven Number, assigned to the ignition oven that is being used to perform the burn-offs, found somewhere on the outside of the furnace (EX. 123456)
<b>G -</b>	Calibration Factor, is determined prior to any acceptance testing for this Mix Design and current JMF per Test Method Nev. T761 (EX. + 0.96) <b>NOTE:</b> Each ignition furnace will have it's own correction factor per mix design and they are not interchangeable.
<b>H -</b>	Date Lift Test Taken, date lift test is conducted (EX. 10-1-20)
<b>I -</b>	Lift Test Result, the number read on the ignition oven when the lift test is conducted. For an accurate lift test result, conduct the lift test on a clean, cold oven. Ensure it is within the range. If it is not, clean the oven, clean the smoke stack, verify the pipe is joints are properly sealed with heat tape and check the lift test again. If it is still outside the range contact your local IA Lab. (EX. - 4.7)
<b>J -</b>	Ignition Oven at Room Temperature for the Lift Test, circle one (EX. Yes)
<b>K -</b>	Date Ignition Oven Cleaned, the actual date of the last ignition oven cleaning. Ignition oven shall be cleaned before a C.F. is established and before the weekly check of the C.F. is conducted. (EX. 9-28-20)
<b>L -</b>	Test Number, particular test for this material (EX. I-1-1; I = Informational Test; 1 = First Informational test of the day; 1 = Number of days the material has been tested)
<b>M -</b>	Calibration Factor, from each individual test performed (EX. + 1.13)

**REPORT OF CALIBRATION FACTOR (INCLUDING WEEKLY CHECKS) USING THE IGNITION OVEN METHOD**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>N -</b>	Temperature, determined per Test Method Nev. T761, will either be 538°C or 482°C (EX. 538°C)
<b>O -</b>	Accept or Reject, each individual test determined per Test method Nev. T761 (EX. Reject)
<b>P -</b>	Asphalt Source, name of the producer providing the asphalt being utilized in the plantmix (EX. Marathon - Fernley)
<b>Q -</b>	Asphalt Grade, type of asphalt being used in the plantmix, found on the Mix Design approved by the Materials Division (EX. PG64-28NV)
<b>R -</b>	Type of Mixture, name of material that is being placed on the contract, found in the Contract Plans or Special Provisions (EX. PBS Type 2 w/RAP)
<b>S -</b>	Basket Tare Weight (g), total weight of basket assembly (empty baskets, lid, catch pan and guard) in grams (EX. 3086.4)
<b>T -</b>	Wt. of Basket + Sample (g), total weight of basket assembly and sample in grams (EX. 5836.4)
<b>U -</b>	Wt. of Basket + Sample in Ignition Oven (g), zero the ignition oven balance prior to placing the basket and sample in the ignition oven. Then place the basket and sample in the ignition oven, close the door and let the balance stabilize. Record this weight to the 0.1. Before the ignition oven is started, verify this weight and the weight in Letter T are within 5 grams of each other. If they are, press the start button. If they aren't, obtain more material out of the pan, so it is within 5 grams. (EX. 5833.8)
<b>V -</b>	Bitumen Ratio from Printed Ticket, when the test is started a ticket will start to print, when the test is complete the ticket will finish printing. Tear the ticket off of the printer and record the "Bitumen Ratio" to the 0.01. (EX. 6.43)
<b>W -</b>	Actual Bitumen Ratio from Hotplant Check, the hotplant inspector will give you this number and range of trucks to obtain your sample from during the field trial mixture. (EX. 5.30)

**REPORT OF CALIBRATION FACTOR (INCLUDING WEEKLY CHECKS) USING THE IGNITION OVEN METHOD**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>X -</b>	C.F., Line V (Bitumen Ratio from Printed Ticket) - Line W (Actual Bitumen Ratio from Hotplant Check) = Line X (C.F.) (EX. $6.43 - 5.30 = + 1.13$ ) <b>NOTE:</b> This number can be a positive (+) or negative (-) number.
<b>Y -</b>	Dry Mass, take Line T (Wt. of Basket and Sample (g)) - Line S (Basket Tare Weight (g)) = Line Y (Dry Mass) (EX. $5836.4 - 3086.4 = 2750.0$ )
<b>Z -</b>	Dry Mass, take Line T (Wt. of Basket and Sample) - Line S (Basket Tare Weight) = Line Y (Dry Mass) (EX. $5834.3 - 3086.4 = 2747.9$ ) <b>NOTE:</b> Only use the manual calculation if there is a power failure during the test or the ticket fails to print. Make sure to document in remarks why the manual calculation was used.
<b>AA -</b>	Mass After, weight of the cooled off basket assembly and sample after it has completed the burn-off, weighed to the 0.1 grams. This weight is obtained on an external balance in the lab. (EX. 2583.8)
<b>BB -</b>	Mass After, same weight obtained in Letter AA (EX. 2583.8)
<b>CC -</b>	Bitumen Ratio, calculated by Letter Z (Dry Mass) - Letter AA (Mass After) / Letter BB (Mass After) x 100 = Letter CC (Bitumen Ratio) (EX. $(2747.9 - 2583.8) / 2583.8 \times 100 = 6.35$ )
<b>DD -</b>	Remarks, anything that needs to be documented (EX. Used I-3-1 and I-4-1 for the calibration factor. I-1-1 exceeded 1.0%, dropped the temperature to 482°C for I-2-1. Manually calculated I-5-1, generator shut off during the burn-off.)
<b>EE -</b>	Resident Engineer, or Assistant Resident Engineer signature on that specific crew (EX. R. John)

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION

**WATER VOLUME CALCULATIONS FOR SAND CONE APPARATUS  
AND MEASURING VESSEL (HAT)**

Contract No. \_\_\_\_\_

Temperature of Water \_\_\_\_\_

Date \_\_\_\_\_

State Id No. \_\_\_\_\_

One Piece Sand Cone

Measuring Vessel Hat 250 mm (10 in.)

Three Piece Sand Cone

Measuring Vessel Hat 200 mm (8 in.)

Weight of Water \_\_\_\_\_ lb  
(Carry to nearest 0.1)

Volume of Vessel = Weight of Water / 62.4 \_\_\_\_\_ ft<sup>3</sup>  
(Carry to nearest 0.001)

Volume of Vessel in m<sup>3</sup> = Volume in ft<sup>3</sup> x 0.0283168 \_\_\_\_\_ m<sup>3</sup>  
(Carry to nearest 0.00001)

Remarks: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Tested By: \_\_\_\_\_

Resident Engineer: \_\_\_\_\_

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION

**WATER VOLUME CALCULATIONS FOR SAND CONE APPARATUS  
AND MEASURING VESSEL (HAT)**

A. Contract No. 3925

B. Temperature of Water: 78°F

C. Date 7/12/2010

D. State Id No. 19315

- E.  One Piece Sand Cone  Measuring Vessel Hat 250 mm (10 in.)  
 Three Piece Sand Cone  Measuring Vessel Hat 200 mm (8 in.)

F. Weight of Water 12.5 lb  
(Carry to nearest 0.1)

G. Volume of Vessel = Weight of Water / 62.4 0.200 ft<sup>3</sup>  
(Carry to nearest 0.001)

H. Volume of Vessel in m<sup>3</sup> = Volume in ft<sup>3</sup> x 0.0283168 \_\_\_\_\_ m<sup>3</sup>  
(Carry to nearest 0.00001)

I. Remarks: Performed at the Elko Progress Lab, with the supervision of the progress tester.  
\_\_\_\_\_  
\_\_\_\_\_

J. Tested By: Jane Gethro

K. Resident Engineer: *Jay Gales*

**WATER VOLUME CALCULATIONS FOR SAND CONE APPARATUS  
AND MEASURING VESSEL (HAT)**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>A -</b>	Contract number for the material being tested, found in the Contract Plans or Special Provisions (3925)
<b>B -</b>	Temperature of the water used to determine the volume of the apparatus calibrated per Test Method Nev. T761 (EX. 78°)
<b>C -</b>	Date the calibration was performed (EX. 7/12/2010)
<b>D -</b>	Fixed ID number on the calibrated piece of equipment (EX. 19315) NOTE: If there is not an ID number on the piece of equipment, label it with the crew number and a #1 or #2 depending if there is more than one piece of the same equipment
<b>E -</b>	Check the appropriate box that applies to the specific type of equipment being calibrated (EX. X - One Piece Sand Cone)
<b>F -</b>	Total weight of water that it took to fill up the apparatus determined per Test Method Nev. T102 (EX. 12.5 lb)
<b>G -</b>	Line F (Weight of Water) / 62.4 (Weight of a Cubic Foot of Water) = Line G (Volume of Vessel) (EX. 12.5 / 62.4 = 0.200)
<b>H -</b>	Line G (Volume of Vessel in ft <sup>3</sup> ) x 0.0283168 (conversion factor from English to metric) = Line H (Volume of Vessel in m <sup>3</sup> ) NOTE: Only fill this line out if work is being performed on a metric contract
<b>I -</b>	Any remarks that need to be documented (EX. Performed at the Elko Progress Lab, with the supervision of the progress tester)
<b>J -</b>	Tested by, print first and last name of the tester or testers who completed the test (EX. Jane Gethro)
<b>K -</b>	Resident Engineer or Assistant Resident Engineer signature on that specific crew (EX. Ray Geles)

**NOTES:**

1. Per Test Method Nev. T102, the apparatus shall be calibrated annually

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION

**SAND DENSITY CALCULATION - T102**

Contract No. \_\_\_\_\_

State Id No. \_\_\_\_\_

Date \_\_\_\_\_

Three Piece Sand Cone with 200 mm (8 in.) Measuring Vessel (Hat)

One Piece Sand Cone with 250 mm (10 in.) Measuring Vessel (Hat)

Trial Pours

Initial Weight of Sand - Weight of Residue = Weight of Sand Used

1. \_\_\_\_\_ - \_\_\_\_\_ = \_\_\_\_\_ lb

2. \_\_\_\_\_ - \_\_\_\_\_ = \_\_\_\_\_ lb

3. \_\_\_\_\_ - \_\_\_\_\_ = \_\_\_\_\_ lb

Trial Pour Average = \_\_\_\_\_ lb

(Note: All three trial pours must be within  $\pm 0.2$  lb of each other, if not repeat this procedure.)

Trial Pour Average / Volume of the Sand Cone and Measuring Vessel (Hat) = Sand Density in  $\text{lb/ft}^3$

\_\_\_\_\_ / \_\_\_\_\_ = \_\_\_\_\_  $\text{lb/ft}^3$

Sand Density in  $\text{lb/ft}^3$  / 62.4 = Sand Density in  $\text{Mg/m}^3$

\_\_\_\_\_  $\text{lb/ft}^3$  / 62.4 = \_\_\_\_\_  $\text{Mg/m}^3$

Remarks: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Tested By: \_\_\_\_\_

Resident Engineer: \_\_\_\_\_



STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION

**SAND DENSITY CALCULATION - T102**

A. Contract No. 3925

B. State Id No. 19315

C. Date 7/12/2010

- D.  Three Piece Sand Cone with 200 mm (8 in.) Measuring Vessel (Hat)  
 One Piece Sand Cone with 250 mm (10 in.) Measuring Vessel (Hat)

Trial Pours

E. F. G.  
Initial Weight of Sand - Weight of Residue = Weight of Sand Used

1. 51.9 - 21.9 = 30.0 lb

2. 50.6 - 20.6 = 30.0 lb

3. 50.3 - 20.3 = 30.0 lb

H. Trial Pour Average = 30.0 lb

(Note: All three trial pours must be within  $\pm 0.2$  lb of each other, if not repeat this procedure.)

I. J. K.  
Trial Pour Average / Volume of the Sand Cone and Measuring Vessel (Hat) = Sand Density in lb/ft<sup>3</sup>

30.0 / 0.334 = 89.8 lb/ft<sup>3</sup>

L. M. N.  
Sand Density in lb/ft<sup>3</sup> / 62.4 = Sand Density in Mg/m<sup>3</sup>

89.8 lb/ft<sup>3</sup> / 62.4 = 1.44 Mg/m<sup>3</sup>

O. Remarks: New sand brought in, calibrated for ratholes.

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

P. Tested By: Bill Lewis

Q. Resident Engineer: Kyle Bess

**SAND DENSITY CALCULATION - T102**

**LINE**

**EXPLANATION OF NEEDED INFORMATION**

- A -** Contract number for the material being tested, found in the Contract Plans or Special Provisions (EX. 3925)
- B -** Fixed ID number on the piece of equipment being tested (EX. 19315) NOTE: If there is not an ID number on the piece of equipment, label it with the crew number and a #1 or # 2 depending on if there is more than one piece of the same equipment
- C -** Date the calibration was performed (EX. 7/12/2010)
- D -** Check the appropriate box that applies to the equipment being calibrated (EX. X - One Piece Sand Cone)
- E -** Initial weight of sand being used to determine the sand density determined per Test Method Nev. T102 (EX. 51.9) NOTE: A minimum amount of 50.0 lb shall be used
- F -** Weight of sand residue from filling the measuring vessel (hat) and sand cone determined per Test Method Nev. T102 (EX. 21.9)
- G -** Line E (Initial Weight of Sand) - Line F (Weight of Residue) = Line G (Weight of Sand Used) (EX. 51.9 - 21.9 = 30.0 round to the nearest 0.1)
- H -** The sum of all three values of Line G (Weight of Sand Used) / 3 = Line H (Trial Pour Average) (EX. 30.0 + 30.0 + 30.0 = 90.0 / 3 = 30.0 round to the nearest 0.1)
- I -** Value from Line H (Trial Pour Average) (EX. 30.0)
- J -** Volume of sand cone and measuring vessel (hat) from NDOT form 040-067 (EX. 0.334)
- K -** Line I (Trial Pour Average) / Line J (Volume of the Sand Cone and Measuring Vessel (hat)) = Line K (Sand Density in lb/ft<sup>3</sup>) (EX. 30.0 / 0.334 = 89.8 round to the nearest 0.1)
- L -** Line K (Sand Density in lb/ft<sup>3</sup>) (EX. 89.8) NOTE: Only fill this line out if work is being performed on a metric contract
- M -** 62.4 (weight of a cubic foot of water) NOTE: Only fill this line out if work will be done on a metric contract

**SAND DENSITY CALCULATION - T102**

**LINE**

**EXPLANATION OF NEEDED INFORMATION**

- N -** Line L (Sand Density in lb/ft<sup>3</sup>) / Line M (62.4 weight of a cubic foot of water) = Line N (Sand Density in Mg/m<sup>3</sup>) (EX. 89.8 / 62.4 = 1.439) NOTE: Only fill this line out if work is being performed on a metric contract
  
- O -** Any remarks that need to be documented (EX. New sand brought in, calibrated for ratholes)
  
- P -** Print first and last name of the tester or testers who completed the test (EX. Bill Lewis)
  
- Q -** Resident Engineer or Assistant Resident Engineer signature on that specific crew (EX. Kyle Ross)

**STATE OF NEVADA DEPARTMENT OF TRANSPORTATION  
MOISTURE-DENSITY DETERMINATION, COMPACTION REPORT - PART 1**

Contract No. \_\_\_\_\_  
Date \_\_\_\_\_

Test Hole No. (code) \_\_\_\_\_  
Station \_\_\_\_\_  
Distance to Centerline \_\_\_\_\_  
Embankment Depth \_\_\_\_\_  
Type of Material \_\_\_\_\_  
Compaction Equipment \_\_\_\_\_


**Sand Volume Data Nev. T102**

1. Initial Wt. of Sand	kg (lbs)			
2. Wt. of Residue	kg (lbs)			
3. Wt. of Sand Used, 1 - 2	kg (lbs)			
4. Sand Density	Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )			
5. Vol. Hole + Cone + Plate, 3 / 4	m <sup>3</sup> x 1000 (ft <sup>3</sup> )			
6. Vol. of Cone + Plate	m <sup>3</sup> x 1000 (ft <sup>3</sup> )			
7. Vol. of Hole, 5 - 6	m <sup>3</sup> x 1000 (ft <sup>3</sup> )			

**Excavated Sample Nev. T102**

8. Total Excavated Wet Wt.	kg (lbs)			
9. Wet Wt.	grams			
10. Dry Wt.	grams			
11. Wt. of Water, 9 - 10	grams			
12. % Moisture, (11 / 10)100				
13. Dry Weight of + 3/4				
14. Dry Weight of - 3/4, 10 - 13				
15. Field Wet Density, 8 / 7	Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )			
16. Field Dry Density, [15 / (100 + % Moisture)]100	Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )			

**Data for Calculated Maximum Density Determination Nev. T108**

Total Sample Wt. \_\_\_\_\_  
Wt. of + 3/4" \_\_\_\_\_  
% retained on 3/4" \_\_\_\_\_

Proctor Test No.: \_\_\_\_\_

		Point 1	Point 2	Point 3	Point 4	Point 5
17. Wt. of Mold + Compacted Soil	grams					
18. Wt. of Mold	grams					
19. Wt. of Compacted Soil, 17 - 18	grams					
20. Wet Density, (Line 19 / 453.59) x Factor	lb/ft <sup>3</sup>					
21. Dry Density, (Line 20 / (100 + % Moist.))100	lb/ft <sup>3</sup>	*				

Note: Mold Volume Factor, F = (1 / Volume)  
6" Mold use 13.33

Wet Density = (Wt. of Compacted Soil / 453.59) x Factor

Dry Density = (Wet Density / (100 + % Moisture)) x 100

**Moisture Content, Nev. T112 or T108 (Microwave Oven Procedure)**

		Point 1	Point 2	Point 3	Point 4	Point 5
22. Wet Wt.	grams					
23. Dry Wt.	grams					
24. Wt. of Water, 22 - 23	grams					
25. % Moisture, (24 / 23)100		*				

\* Oven-dry density points shall be plotted as ordinates (y-axis) and corresponding moisture contents as abscissa (x-axis)


**STATE OF NEVADA DEPARTMENT OF TRANSPORTATION  
MOISTURE-DENSITY DETERMINATION, COMPACTION REPORT - PART 2**

**Coarse Aggregate Correction, Nev. T104**

Apply if aggregate particles exceed 5% by mass retained on the 19.0 mm (3/4 in.) sieve

26. Wt. of Aggregate = A			
27. Wt. of Pycnometer = p			
28. (Wt. of Pyc. + Water) - p = M	M =	M =	M =
29. (Wt. of Pyc. + Water + Aggregate) - (p + A) = M <sub>1</sub>	M <sub>1</sub> =	M <sub>1</sub> =	M <sub>1</sub> =
30. Wt. of Water Recovered from Pyc. = M <sub>2</sub>	M <sub>2</sub> =	M <sub>2</sub> =	M <sub>2</sub> =
31. If M <sub>1</sub> - M <sub>2</sub> ≤ 14 g, G = [A / (M - M <sub>1</sub> )] x 62.4			
32. If M <sub>1</sub> - M <sub>2</sub> > 14 g, G = [A / [(M - M <sub>1</sub> ) + 0.5 (M <sub>1</sub> - M <sub>2</sub> - 14 g)]] x 62.4			
33. Decimal Equiv. of % + 3/4", (1 - P), 13 / 10			
34. Decimal Equiv. of % - 3/4", P, 14 / 10			
35. Maximum Dry Density = d (lb/ft <sup>3</sup> )			
36. Corrected Max. Dry Density D = dG / [(d)(1 - P) + (G)(P)] (lb/ft <sup>3</sup> )			
37. Corrected Optimum Moisture [(1 - P) x 2] + [P x "As Plotted" Opt. Moisture]			
38. % Compaction = (16 / 35 or 36)100			

**PLOTTED PROCTOR CURVE**



Proctor Test No. Reference: \_\_\_\_\_

**As Plotted**

Max. Dry Density (d)	Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )
Optimum Moisture	%

**Note:** For Metric, lb/ft<sup>3</sup> / 62.4 = Mg/m<sup>3</sup>

**Enter When Referencing Curve**

Max. Dry Density (d)	Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )
Optimum Moisture	%

REMARKS: \_\_\_\_\_

TESTED BY: \_\_\_\_\_

RESIDENT ENGINEER: \_\_\_\_\_

**STATE OF NEVADA DEPARTMENT OF TRANSPORTATION  
MOISTURE-DENSITY DETERMINATION, COMPACTION REPORT - PART 1**

**A.** Contract No. 1234  
**B.** Date 5/20/2020

**C.** Test Hole No. (code)  
**D.** Station  
**E.** Distance to Centerline  
**F.** Embankment Depth  
**G.** Type of Material  
**H.** Compaction Equipment

9-IB-95	10-IB-95	10-IB-95 R1
X ~ 665+50	X ~ 745+00	X ~ 745+00
33' RT	38' RT	38' RT
8' BFG	8' BFG	8' BFG
T1CB Base	T1CB Base	T1CB Base
Steel Roller	Steel Roller	Steel Roller

**Sand Volume Data Nev. T102**

<b>I.</b> 1. Initial Wt. of Sand	kg (lbs)	50.4	50.4	50.4
<b>J.</b> 2. Wt. of Residue	kg (lbs)	18.5	17.0	17.7
<b>K.</b> 3. Wt. of Sand Used, 1 - 2	kg (lbs)	31.9	33.4	32.7
<b>L.</b> 4. Sand Density	Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )	84.8	84.8	84.8
<b>M.</b> 5. Vol. Hole + Cone + Plate, 3 / 4	m <sup>3</sup> x 1000 (ft <sup>3</sup> )	0.376	0.394	0.386
<b>N.</b> 6. Vol. of Cone + Plate	m <sup>3</sup> x 1000 (ft <sup>3</sup> )	0.217	0.217	0.217
<b>O.</b> 7. Vol. of Hole, 5 - 6	m <sup>3</sup> x 1000 (ft <sup>3</sup> )	0.159	0.177	0.169

**Excavated Sample Nev. T102**

<b>P.</b> 8. Total Excavated Wet Wt.	kg (lbs)	21.7	21.5	21.9
<b>Q.</b> 9. Wet Wt.	grams	1888	1965	1902
<b>R.</b> 10. Dry Wt.	grams	1816	1886	1901
<b>S.</b> 11. Wt. of Water, 9 - 10	grams	72	79	1
<b>T.</b> 12. % Moisture, (11 / 10)100		4.0	4.2	0.1
<b>U.</b> 13. Dry Weight of + 3/4		117	128	10
<b>V.</b> 14. Dry Weight of - 3/4, 10 - 13		1699	1758	1891
<b>W.</b> 15. Field Wet Density, 8 / 7	Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )	136.5	121.5	129.6
<b>X.</b> 16. Field Dry Density, [15 / (100 + % Moisture)]100	Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )	131.3	116.6	129.5

**Data for Calculated Maximum Density Determination Nev. T108**

<b>Y.</b> Total Sample Wt.	11748
<b>Z.</b> Wt. of + 3/4"	804
<b>AA.</b> % retained on 3/4"	6.8

**BB.** Proctor Test No.: 9-1B-95

		Point 1	Point 2	Point 3	Point 4	Point 5
<b>CC.</b> 17. Wt. of Mold + Compacted Soil	grams	10449	10707	10926	10834	
<b>DD.</b> 18. Wt. of Mold	grams	5895	5895	5895	5895	
<b>EE.</b> 19. Wt. of Compacted Soil, 17 - 18	grams	4554	4812	5031	4939	
<b>FF.</b> 20. Wet Density, (Line 19 / 453.59) x Factor	lb/ft <sup>3</sup>	133.8	141.4	147.8	145.1	
<b>GG.</b> 21. Dry Density, (Line 20 / (100 + % Moist.))100	lb/ft <sup>3</sup>	* 128.4	133.0	136.9	132.9	

Note: Mold Volume Factor, F = (1 / Volume)  
6" Mold use 13.33

Wet Density = (Wt. of Compacted Soil / 453.59) x Factor  
Dry Density = (Wet Density / (100 + % Moisture)) x 100

**Moisture Content, Nev. T112 or T108 (Microwave Oven Procedure)**

		Point 1	Point 2	Point 3	Point 4	Point 5
<b>HH.</b> 22. Wet Wt.	grams	253.3	227.0	221.8	241.5	
<b>II.</b> 23. Dry Wt.	grams	243.0	213.6	205.3	221.2	
<b>JJ.</b> 24. Wt. of Water, 22 - 23	grams	10.3	13.4	16.5	20.3	
<b>KK.</b> 25. % Moisture, (24 / 23)100		* 4.2	6.3	8.0	9.2	

\* Oven-dry density points shall be plotted as ordinates (y-axis) and corresponding moisture contents as abscissa (x-axis)

**STATE OF NEVADA DEPARTMENT OF TRANSPORTATION  
MOISTURE-DENSITY DETERMINATION, COMPACTION REPORT - PART 2**

**Coarse Aggregate Correction, Nev. T104**

Apply if aggregate particles exceed 5% by mass retained on the 19.0 mm (3/4 in.) sieve


- LL.** 26. Wt. of Aggregate = A  
**MM.** 27. Wt. of Pycnometer = p  
**NN.** 28. (Wt. of Pyc. + Water) - p = M  
**OO.** 29. (Wt. of Pyc. + Water + Aggregate) - (p + A) = M<sub>1</sub>  
**PP.** 30. Wt. of Water Recovered from Pyc. = M<sub>2</sub>  
**QQ.** 31. If M<sub>1</sub> - M<sub>2</sub> ≤ 14 g,  
 $G = [A / (M - M_1)] \times 62.4$   
**RR.** 32. If M<sub>1</sub> - M<sub>2</sub> > 14 g,  
 $G = [A / [(M - M_1) + 0.5 (M_1 - M_2 - 14 \text{ g})]] \times 62.4$

504	500	
442	442	
1451	M = 1009	1451
1763	M <sub>1</sub> = 817	1757
	800	M <sub>2</sub> = 810
		M =
		M <sub>1</sub> =
		M <sub>2</sub> =
	161.0	
162.2		

- SS.** 33. Decimal Equiv. of % + 3/4", (1 - P), 13 / 10  
**TT.** 34. Decimal Equiv. of % - 3/4", P, 14 / 10  
**UU.** 35. Maximum Dry Density = d (lb/ft<sup>3</sup>)  
**VV.** 36. Corrected Max. Dry Density  
 $D = dG / [(d)(1 - P) + (G)(P)]$  (lb/ft<sup>3</sup>)  
**WW.** 37. Corrected Optimum Moisture  
 $[(1 - P) \times 2] + [P \times \text{"As Plotted" Opt. Moisture}]$   
**XX.** 38. % Compaction = (16 / 35 or 36)100

0.064	0.068	0.005
0.936	0.932	0.995
136.9	136.9	136.9
138.3	138.3	
7.5	7.5	
95	84	95

**YY. PLOTTED PROCTOR CURVE**



**ZZ.** Proctor Test No. Reference: **9-IB-95**

**AAA. As Plotted**

Max. Dry Density (d)	136.9	Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )
Optimum Moisture	7.9	%

**Note:** For Metric, lb/ft<sup>3</sup> / 62.4 = Mg/m<sup>3</sup>

**BBB. Enter When Referencing Curve**

Max. Dry Density (d)		Mg/m <sup>3</sup> (lb/ft <sup>3</sup> )
Optimum Moisture		%

**CCC.** REMARKS: Test performed on corrugated metal pipe 9-1B-95 and 10-1B-95R1 met specs. 10-1B-95 failed to meet specs, contractor reworked the failing area and material was re-tested. Contractor and R.E. notified of all test results.

**DDD.** TESTED BY: **Leonard Cooper**

**EEE.** RESIDENT ENGINEER: **Howard Koothrappali**

**MOISTURE-DENSITY DETERMINATION, COMPACTION REPORT**

<u>LINE</u>	<u>EXPLANATION OF NEEDED MATERIAL</u>
<b>A -</b>	Contract Number for the material being tested, found in the contract plans or special provisions (ex. 1234)
<b>B -</b>	Date the sample was taken or test was performed (ex. 5/20/2020, all 3 tests were performed in the same day)
<b>C -</b>	Test Hole No., actual test number for this particular test. (ex. 9-1B-95). 9 is the number of tests ran on that material, 1B represents the material being tested (refer to the Field Testing Guide - Part 1, for coding) and 95 is the minimum percent compaction required (see Standard Specifications or Special Provisions)
<b>D -</b>	Station, approximate sample location, found in the Contract Plans or on the jobsite survey stationing (ex. "X" 665+50)
<b>E -</b>	Distance to Centerline, distance right or left of centerline that the compaction test was performed (ex. 33' RT.)
<b>F -</b>	Embankment Depth, depth at which the compaction test was performed (ex. 8' below finish grade) (Depth may also be found on the slope stakes or by using the elevation markers)
<b>G -</b>	Type of Material as specified and found in the contract plans or special provisions (ex. Type 1 Class B Base)
<b>H -</b>	Compaction Equipment, type of equipment used to compact the material (ex. Steel Roller)
<b>I -</b>	Initial Wt. of Sand in lbs or kg used to fill the test hole and cone (ex. 50.4) <b>NOTE:</b> Minimum of 50 lb of sand needed
<b>J -</b>	Wt. of Residue, remaining in the bucket after the test hole and sand cone are filled (ex. 18.5)
<b>K -</b>	Line I (Initial Wt. of Sand) - Line J (Wt. of Residue) = Wt. of Sand Used (ex. 50.4 - 18.5 = 31.9)
<b>L -</b>	Sand Density, established per Test Method Nev. T102 during sand calibration, and reported on NDOT form 040-068 <b>NOTE:</b> Sand densities may change each time the sand is calibrated (ex. 84.8)



MOISTURE-DENSITY DETERMINATION, COMPACTION REPORT

LINE

EXPLANATION OF NEEDED MATERIAL

- M -** Line K (Wt. of Sand Used) / Line L (Sand Density) = Vol. Hole + Cone + Plate  
(ex. 31.9 / 84.8 = 0.376)
- N -** Vol. of Cone + Plate, is established per Test Method Nev. T102 (ex. 0.217)
- O -** Line M (Vol. Hole + Cone + Plate) - Line N (Vol. of Cone + Plate) = Vol. of Hole  
(ex. 0.376 - 0.217 = 0.159)
- NOTE:** If the test hole is less than .0042 m<sup>3</sup> (Metric) or 0.15 ft<sup>3</sup> (English), the test is invalid and another test shall be performed immediately
- P -** Total Excavated Wet Wt. - entire sample excavated from the test hole per Test Method Nev. T102 (ex. 21.7)
- Q -** Wet Wt., Representative split of the entire sample excavated from the test hole per Test Method Nev. T102 (ex. 1888)
- R -** Dry Wt., sample after all moisture has been removed, per Test Method Nev. T112 (ex. 1816)
- S -** Line Q (Wet Wt.) - Line R (Dry Wt.) = Wt. of Water (ex. 1888 - 1816 = 72)
- T -** Line S (Wt. of Water) / Line R (Dry Wt.) x 100 = % Moisture  
(ex. (72 / 1816) X 100 = 4.0)
- U -** After weighing and recording the dry weight on Line R.(Dry Wt.), screen the entire portion of material over a 3/4" sieve. Record the dry weight of plus 3/4" material.  
(ex. 117)
- V -** Line R (Dry Wt.) - Line U. (Dry Wt. of +3/4") = Dry Wt. of -3/4" (ex. 1816 - 117 = 1699)
- W -** Line P (Total Excavated Wet Wt.) / Line O (Vol. Of Hole) = Field Wet Density  
(ex. 21.7 / 0.159 = 136.5)
- X -** [Line W (Field Wet Density) / (100 + Line T (% Moisture))] x 100 = Field Dry Density  
(ex. [136.5 / (100 + 4.0)] X 100 = 131.3)
- Y -** Total Sample Wt., Representative sample as obtained per Test Method Nev. T200 (ex. 11748) This number can be the total Excavated Wet Wt. of material in grams from the rathole or it can be a representative split portion of the Excavated Wet Wt.

**MOISTURE-DENSITY DETERMINATION, COMPACTION REPORT**

<u>LINE</u>	<u>EXPLANATION OF NEEDED MATERIAL</u>
<b>Z -</b>	Wt. of +3/4", Thoroughly screen the material from Line Y (Total Sample Wt.) over a 19.0 mm (3/4 in.) sieve and record the weight of +3/4" material. (ex. 804).
<b>AA -</b>	$(\text{Line Z (Wt. of +3/4")} / \text{Line Y (Total Sample Wt.)}) \times 100 = \% \text{ Retained on +3/4"}$ (ex. $(804 / 11748) \times 100 = 6.8\%$ ) If the number is 5.0% or greater then a Coarse Aggregate Correction (T104) will be ran on this proctor.
<b>BB -</b>	Proctor Test No., actual test number for this particular proctor test. (ex. 9-1B-95).
<b>CC -</b>	Wt. of Mold + Compacted Soil, determined weight of mold with base plate without the collar extension and trimmed compacted specimen recorded to the nearest 1 g. (ex. 10449 for Point 1)
<b>DD -</b>	Wt. of Mold, determined weight of clean dry mold. Include the base plate, exclude the collar extension and record to the nearest 1 g. (ex. 5895 for Point 1)
<b>EE -</b>	$\text{Line CC (Wt. of Mold + Compacted Soil)} - \text{Line DD (Wt. of Mold)} =$ Wt. of Compacted Soil (ex. $10449 - 5895 = 4554$ for Point 1)
<b>FF -</b>	$\text{Line EE (Wt. of Compacted Soil)} / 453.59 \text{ (g to lbs)} \times 13.33 \text{ (Mold Volume Factor)} =$ Wet Density (ex. $(4554 / 453.59) \times 13.33 = 133.8$ for Point 1)
<b>GG -</b>	$(\text{Line FF (Wet Density)} / (100 + \text{Line KK ( \% Moisture)})) \times 100 = \text{Dry Density}$ (ex. $(133.8 / (100 + 4.2)) \times 100 = 128.4$ for Point 1)
<b>HH -</b>	Wet Wt., wet weight of representative moisture sample from middle portion obtained from the extruded specimen (ex. 253.3 for Point 1)
<b>II -</b>	Dry Wt., dry weight of representative sample from middle portion obtained from the extruded specimen (ex. 243.0 for Point 1)
<b>JJ -</b>	$\text{Line HH (Wet Wt.)} - \text{Line II (Dry Wt.)} = \text{Wt. of Water}$ (ex. $253.5 - 243.0 = 10.3$ for Point 1)
<b>KK -</b>	$\text{Line JJ (Wt. of Water)} / \text{Line II (Dry Wt.)} \times 100 = \% \text{ Moisture}$ (ex. $(10.3 / 243.0) \times 100 = 4.2\%$ for Point 1)
<b>LL -</b>	Wt. of Aggregate = A, sample shall be 500 g of + 3/4" material per Test Method Nev. T104 (ex. 504)

MOISTURE-DENSITY DETERMINATION, COMPACTION REPORT

LINE

EXPLANATION OF NEEDED MATERIAL

MM -

Wt. of Pycnometer = p, clean, dry and with lid (ex. 442)

NN -

Wt. of Pyc. + Water with a meniscus formed on top of the lid in grams. (ex. 1451)

$M = (\text{Line NN (Weight of Pyc. + Water)} - \text{Line MM (Wt. of Pycnometer)})$

(ex.  $1451 - 442 = 1009$ )

OO -

Wt. of Pyc. + Water + Aggregate in grams (ex. 1763)

$M_1 = (\text{Line OO (Wt. of Pyc. + Water + Agg.)}) - ((\text{Line MM (Wt. of Pyc.)}) +$

$\text{Line LL (Wt. of Aggregate)})$  (ex.  $1763 - (504 + 442) = 817$ )

PP -

Wt. of Water Recovered from Pyc. =  $M_2$ , (ex. 800)

QQ -

**If  $M_1 - M_2 \leq 14$  g, use formula  $G = [A / (M - M_1)] \times 62.4$**

$[\text{Line LL (Wt. of Aggregate)} / (\text{Line NN (Wt. of Pyc. + Water)} -$

$\text{Line OO (Wt. of Pyc. + Water + Aggregate)})] \times 62.4$

(EX. See 10-1B-95:  $G = [500 / (1009 - 815)] = 2.58 \times 62.4 = 160.99 = 161.0$ )

Note: If there is not 5.0% or more of +3/4 material, then Coarse Aggregate Correction, Test Method Nev. T104 boxes will be left blank (See 10-1B-95R1 for an example)

$[A / (M - M_1)]$  is calculating the apparent specific gravity to the .01 per Test Method Nev. T104, taking the apparent specific gravity and multiplying it by 62.4 is converting it to  $\text{lbs/ft}^3$ .

RR

**If  $M_1 - M_2 > 14$  g, use formula  $G = A / [(M - M_1) + 0.5 (M_1 - M_2 - 14)] \times 62.4$**

$[\text{Line LL (Wt. of Aggregate)} / ((\text{Line NN (Wt. of Pyc. + Water)} -$

$\text{Line OO (Wt. of Pyc. + Water + Aggregate)}) +$

$0.5 (\text{Line OO (Wt. of Pyc. + Water + Aggregate)} -$

$\text{Line PP (Wt. of Water Recovered from Pyc.)} - 14 \text{ g})] \times 62.4$

(EX. See 9-1B-95:

$G = [504 / ((1009 - 817) + 0.5(817 - 800 - 14))] = 2.60 \times 62.4 = 162.24 = 162.2$ )

Note: If there is not 5.0% or more of +3/4 material, then Coarse Aggregate Correction, Test Method Nev. T104 boxes will be left blank (See 10-1B-95R1 for an example)

$A / [(M - M_1) + 0.5 (M_1 - M_2 - 14)]$  is calculating the apparent specific gravity to the .01 per Test method Nev. T104, taking the apparent specific gravity and multiplying it by 62.4 is converting it to  $\text{lbs/ft}^3$ .

MOISTURE-DENSITY DETERMINATION, COMPACTION REPORT

LINE

EXPLANATION OF NEEDED MATERIAL

**SS -**

Decimal Equivalent of % + 3/4", (1-P) = Line U (Dry weight of + 3/4) / Line R (Dry Wt.)  
(EX. (117 / 1816 = 0.064)

**NOTE:** When ONLY performing Test Method Nev. T108 for a check test or informational purposes, this value will can be determined using manual calculation by the following method. Line Z ( Wt. of +3/4) / Line Y (Total Sample Wt.)  
(Ex. (804 / 11748 = 0.068)

**TT -**

Decimal Equivalent of % -3/4", P = Line V (Dry Wt. of -3/4) / Line R (Dry Wt.)  
(EX. (1699 / 1816 = 0.936) Line SS + Line TT will always = 1

**NOTE:** When ONLY performing Test Method Nev. T108 for informational purposes This value can be determined using manual calculation by the following method: (1 - Line SS (Decimal Equivalent of +3/4", (1-P))  
(Ex. (1 - 0.068 = 0.932)

**UU -**

Maximum Dry Density = d, value is indicated on Line AAA (As Plotted, Max. Dry Density) (ex. 136.9)

**NOTE:** This is the highest point on the plotted curve.

**VV -**

Corrected Max. Dry Density,  $D = dG / [(d)(1-P) + (G)(P)]$   
 $D = \text{Line AAA (As Plotted, Max. Dry Density)} \times (\text{Line QQ (G) or Line RR (G)}) /$   
 $\text{Line AAA (As Plotted, Max. Dry Density)} \times (\text{Line SS (Decimal Equivalent of \% + 3/4")}) +$   
 $(\text{Line QQ (G) or Line RR (G)}) \times \text{Line TT (Decimal Equivalent of \% -3/4")}$   
(ex. (136.9 x 162.2) / [(136.9 x 0.064) + (162.2 x 0.936)] = 138.3)

**NOTE:** Corrected Max. Dry Density will only be filled in if there is a Coarse Aggregate Correction from Nev. Test Method T104.

**WW -**

**Corrected Optimum Moisture Calculation:**

$[(\text{Line SS (Decimal Equivalent of \% + 3/4")}) \times 2] +$   
 $(\text{Line TT (Decimal Equivalent of \% -3/4")}) \times \text{Line AAA (As Plotted Opt. Moisture)}]$   
EX.  $[(0.064 \times 2) + (0.936 \times 7.9)] = 7.5\%$

**MOISTURE-DENSITY DETERMINATION, COMPACTION REPORT**

<u>LINE</u>	<u>EXPLANATION OF NEEDED MATERIAL</u>
<b>XX -</b>	<p>If oversized aggregate correction is required, calculate as follows: Line X (Field Dry Density) / Line VV (Corrected Max. Dry Density) x 100 = % Compaction. (ex. See 9-1B-95: (131.3 / 138.3) x 100 = 94.9 = 95)</p> <p>If no oversized aggregate correction is required (ex. Line SS x 100 = less than 5%), calculate as follows: Line X (Field Dry Density) / Line UU (Maximum Dry Density) x 100 (ex. See 10-1B-95R1: (129.5 / 136.9) x 100 = 94.6 = 95)</p>
<b>YY -</b>	<p>Plot all points from: Line GG (Dry Density) (minimum of 4 points) and its corresponding Line KK (% Moisture) (minimum of 4 points). The oven-dry densities of the soils shall be plotted as ordinates (y-axis) and corresponding moisture content as abscissa (x-axis) (ex. Point 1: 128.4 @ 4.2%, Point 2: 133.0 @ 6.3%, Point 3: 136.9 @ 8.0%, Point 4: 132.9 @ 9.2%)</p>
<b>ZZ -</b>	<p>Proctor Test No. Reference, Actual test number for the proctor being utilized to determine percent compaction. (EX. 9-1B-95).</p>
<b>AAA -</b>	<p>As Plotted Max. Dry Density is the highest point on the curve and Optimum Moisture is the corresponding number from the highest point on the curve. This number is usually different than the highest point on the curve. (ex. 136.9, 7.9)</p>
<b>BBB -</b>	<p>Enter When Referencing Curve, Maximum dry density and optimum moisture values can be utilized from a previous curve done on the same material for up to 25 field compaction tests. Enter the values from Line AAA (As Plotted) from the original test report referenced on Line ZZ (Proctor Test No. Reference).</p>
<b>CCC -</b>	<p>Remarks, anything pertinent that should be documented (ex. Test performed on corrugated metal pipe 9-1B-95 and 10-1B-95R1 met specs. 10-1B-95 failed to meet specs, contractor reworked the area and the material was re-tested. Contractor and R.E. notified of all test results.)</p>
<b>DDD -</b>	<p>Tested By, full printed name of the tester or testers who completed the test (ex. Leonard Cooper)</p>
<b>EEE -</b>	<p>Resident Engineer, RE or ARE signature verifying the accuracy of the reported results (ex. Howard Koothrappali)</p>

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION  
**CONCRETE FIELD SUMMARY REPORT**

Date: \_\_\_\_\_ Contract No.: \_\_\_\_\_ Projected Size of Pour: \_\_\_\_\_ Actual: \_\_\_\_\_ Tester(s): \_\_\_\_\_

Producer: \_\_\_\_\_ Mix Design No.: \_\_\_\_\_ Strength: \_\_\_\_\_ Contractor: \_\_\_\_\_

Item to be Constructed: \_\_\_\_\_

Aggregate Moistures from Tester(s):  
(time is when plant operator received the moistures)

Agg. Type	%	Time	Agg. Type	%	Time

Specifications and Design Criteria : Slump \_\_\_\_\_ Air \_\_\_\_\_ U.W. \_\_\_\_\_ Temp \_\_\_\_\_

Location/Station	Load No. Truck No.	Time	Slump/Flow		% Air	Unit Weight	Air Temp Conc. Temp		Cylinder/ Beam Set #	Remarks(when taking cylinders/beams include cylinder size and method of field curing)
			1st	2nd						
			1st							
			2nd							
			1st							
			2nd							
			1st							
			2nd							
			1st							
			2nd							
			1st							
			2nd							
			1st							
			2nd							
			1st							
			2nd							
			1st							
			2nd							

Additional Remarks: \_\_\_\_\_

Resident Engineer: \_\_\_\_\_

(Signature)

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION  
**CONCRETE FIELD SUMMARY REPORT**

A. Date: 5/13/2017 B. Contract No.: 3650 C. Projected Size of Pour: 256yd<sup>3</sup> D. Actual: 263 yd<sup>3</sup> E. Tester(s) Adam West

F. Producer: Burt Ward Ready Mix Inc. G. Mix Design No. FA 1372 N H. Strength: 4000 psi I. Contractor: Martinson & Leslie Inc.

J. Item to be Constructed: Abutment #2 Aggregate Moistures from Tester(s): Time is when plant operator received the moistures

K. Agg. Type	L. %	M. Time	Agg. Type	%	Time
#67	1.2	6:45am			
WS	3.4	6:45am			

Specifications and Design Criteria N. Slump 1" - 4" O. Air 4 - 7 P. UW 152.6 ± 3lbs Q. Temp 50°F - 90°F

R. Location/Station	S. Load No.	U. Time	V.W. Slump/Flow		X. % Air	Y. Unit Weight	Z. Air Temp	BB. Cylinder Beam Set #	CC. Remarks (when taking cylinders/beams include cylinder size and method of field curing)
	T. Truck No.		1st	2nd			AA. Conc. Temp		
Structure B-1237	#3	8:00am	1st	4	5	151.3	67°F	19	Set #19 stored in insulated box onsite 6" x 12" Cylinders
	#4236		2nd				72°F		
Structure B-1237	#12	10:00am	1st	4	5.5	151.8	73°F	20	Set #20 stored in insulated box onsite 6" x 12" Cylinders
	#237		2nd				74°F		
Structure B-1237	#21	11:32am	1st	4	5	152.3	82°F	21	Set #21 stored in insulated box onsite 6" x 12" Cylinders
	#4250		2nd				76°F		
			1st						
			2nd						
			1st						
			2nd						
			1st						
			2nd						
			1st						
			2nd						
			1st						
			2nd						

DD. Additional Remarks: All cylinders made this day include 1/7, 1/14, 3/28 day breaks. All test performed at the placement site.

All test this day met the required tolerances.

EE. Resident Engineer: Cesar Romero  
(Signature)

**CONCRETE FIELD SUMMARY REPORT**

**LINE**

**EXPLANATION OF NEEDED INFORMATION**

- A -** Date that the testing was performed (Ex. 5/13/2017)
- B -** Contract number for the material being tested, found in the Contract Plans or Special Provisions (Ex. 3625)
- C -** Estimated cubic yards of concrete from field measurements (Ex. 256 yd<sup>3</sup>)
- D -** Total cubic yards placed into the structure (Ex. 263 yd<sup>3</sup>)  
**NOTE:** Actual yards placed could be different than quantities ordered on tickets
- E -** Print first and last name of the tester(s) who actually tested the fresh concrete (Ex. Adam West)
- F -** Producer of the concrete mix being placed (Ex. Burt Ward Ready Mix Inc.)
- G -** Mix Design number that the sample represents. Mix Design approved by the Materials Division (Ex. FA 1372 N)
- H -** Project specified strength, found in the Standard Specifications, Special Provisions, or Contract Plans and indicated as Mpa if the contract is metric or psi if the contract is english (Ex. 4000 psi)  
**NOTE:** If the mix design specifies 4000 psi then the specified strength has to meet 4000 psi even if the barrier rail only has to meet a 3000 psi
- I -** Prime contractor awarded the contract (Ex. Martinson & Leslie Inc.)
- J -** Item being constructed from the Contract Plans (Ex. Abutment #2)
- K -** Size of the aggregate being used in the approved mix design (Ex. #67)
- L -** Moisture content result of the aggregate type in percent form per Test Method Nev. T112  
**NOTE:** Moisture percentages of the aggregates at the batch plant are not required to be performed by the State testers when a Concrete Quality Control Plan is required per Section 501.01.01 of the contract special provisions. If so required in the Specials then it is the duty of the Contractors Quality Control Supervisor to supply the plant inspector (if there is one) with the aggregate moisture percentages. (Ex. 1.2)
- M -** Time the moisture percentage was completed per Test Method Nev. T112 (EX. 6:45am)



**CONCRETE FIELD SUMMARY REPORT**

<u>LINE</u>	<u>EXPLANATION OF NEEDED INFORMATION</u>
<b>N -</b>	Slump specification as specified on the approved Mix Design from the Materials Division (Ex. 1" - 4")
<b>O -</b>	Air content specification as specified on the approved Mix Design from the Materials Division (Ex. 4 - 7)
<b>P -</b>	Specified unit weight specification limits of the concrete mix as stated on the approved Mix Design approved by the Materials Division (152.6 ± 3 lbs)
<b>Q -</b>	Specification range for the fresh concrete temperature on the approved Mix Design approved by the Materials Division (Ex. 50°F - 90°F)
<b>R -</b>	Approximate sample location found in the Contract Plans or job site survey stakes (Ex. Structure B-1237)
<b>S -</b>	Consecutive load delivery number as stated on the load ticket (Ex. #3)
<b>T -</b>	Delivery vehicle number found on the delivery vehicle and batch ticket (Ex. 4236) <b>NOTE:</b> Vehicle number and batch ticket vehicle number should match
<b>U -</b>	Actual time that the sample was taken. (Ex. 8:00am)
<b>V -</b>	Slump results from Test Method Nev. T438 performed at time of sampling (Ex. 4) <b>NOTE:</b> If slump test is required on before and after admixtures are added use 1st for the before slump and 2nd for the after slump
<b>W -</b>	Slump flow results per Test Method Nev. T417 and T418 use 1st for the first test result and 2nd for the second test result
<b>X -</b>	Air results from Test Method Nev. T431 or T432, performed at time of sampling. (Ex. 5)
<b>Y -</b>	Unit weight results from Test Method Nev. T435, performed at the time of sampling (Ex. 151.3)
<b>Z -</b>	Ambient air temperature (Ex. 67°F)
<b>AA -</b>	Temperature of the concrete, per Test Method Nev. T440. (Ex. 72°F)
<b>BB -</b>	Successive cylinder/beam set numbers for each mix design (Ex. 19)

**CONCRETE FIELD SUMMARY REPORT**

**LINE**

**EXPLANATION OF NEEDED INFORMATION**

- CC -** Anything that needs to be documented (Ex. Set #19 stored in insulated box onsite 6" x 12" cylinders)
  
- DD -** Anything that needs to be documented (Ex. All cylinders made this day include for 1/7, 1/14, 3/28 day breaks. All test performed at the placement site. All test this day meet the required tolerances)
  
- EE -** The Resident Engineers or Assistant Resident Engineer signature on that specific crew (Ex. Cesar Romero)

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION  
**CALIBRATION OF UNIT WEIGHT MEASURE**

Contract No. \_\_\_\_\_

Temperature of Water \_\_\_\_\_

Date \_\_\_\_\_

Unit Weight Measure

Air Meter - Type B Measuring Bowl

Weight of Dry Measure and Strike-Off Plate (Tare Weight) \_\_\_\_\_ lb  
(Carry to nearest 0.1)

Weight of Measure, Strike-Off Plate & Water (Total Weight) \_\_\_\_\_ lb  
(Carry to nearest 0.1)

Total Weight - Tare Weight = Weight of Water \_\_\_\_\_ lb

Calibration Factor in  $\text{ft}^3 = 62.4 / \text{Weight of Water}$  \_\_\_\_\_  
(Carry to nearest 0.001)

Calibration Factor in  $\text{m}^3 = 999.6 / \text{Weight of Water}$  \_\_\_\_\_  
(Carry to nearest 0.1)

Remarks: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Tested By: \_\_\_\_\_

Resident Engineer: \_\_\_\_\_

STATE OF NEVADA  
DEPARTMENT OF TRANSPORTATION  
**CALIBRATION OF UNIT WEIGHT MEASURE**

A. Contract No. 3925

B. Temperature of Water 78°F

C. Date 7/12/2020

D. Unit Weight Measure

E. Air Meter - Type B Measuring Bowl

F. Weight of Dry Measure and Strike-Off Plate (Tare Weight) 17.4 lb  
(Carry to nearest 0.1)

G. Weight of Measure, Strike-Off Plate & Water (Total Weight) 48.6 lb  
(Carry to nearest 0.1)

H. Total Weight - Tare Weight = Weight of Water 31.2 lb

I. Calibration Factor in  $\text{ft}^3 = 62.4 / \text{Weight of Wa}$  2.000  
(Carry to nearest 0.001)

J. Calibration Factor in  $\text{m}^3 = 999.6 / \text{Weight of Water}$  32.0  
(Carry to nearest 0.1)

K. Remarks: Performed at the Elko I.A. Lab, with the supervision of the I.A. Tester.  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

L. Tested By: Jane Gethro

M. Resident Engineer: Ray Geles

**CALIBRATION OF UNIT WEIGHT MEASURE**

**LINE**

**EXPLANATION OF NEEDED INFORMATION**

- A -** Contract number for the material being tested, found in the Contract Plans or Special Provisions (3925)
- B -** Temperature of the water used to determine the volume of the apparatus calibrated per Test Method Nev. T761 (EX. 78°)
- C -** Date the calibration was performed (EX. 7/12/2020)
- D -** Check the Unit Weight Measure box if this piece of equipment is being calibrated (EX. X - Unit Weight Measure)
- E -** Check the Air Meter - Type B Measuring Bowl box if this piece of equipment is being calibrated
- F -** Tare Weight of the Dry Measure and the Strike-Off Plate weighed to the nearest 0.1 lb. Per Test Method Nev. T435 (EX. 17.4)
- G -** Total Weight of Measure, Strike-Off Plate and Water (correct temperature) weighed to the nearest 0.1 lb. Per Test Method Nev. T435 (EX. 48.6)
- H -** Line G (Total Weight) - Line F (Tare Weight) = Line H (Weight of Water)  
(EX. 48.6 - 17.4 = 31.2 )
- I -**  $62.4 / \text{Line H (Weight of Water)} = \text{Calibration Factor in ft}^3$  (to the nearest 0.001)  
(EX.  $62.4 / 31.2 = 2.000$ )
- J -**  $999.6 / \text{Line H (Weight of Water)} = \text{Calibration Factor in m}^3$  (to the nearest 0.1)  
(EX.  $999.6 / 31.2 = 32.0$ )  
NOTE: Only fill this line out if work is being performed on a metric contract
- K -** Any remarks that need to be documented (EX. Performed at the Elko I.A. Lab, with the supervision of the I.A. tester)
- L -** Tested by, print first and last name of the tester or testers who completed the test  
(EX. Jane Gethro)
- M -** Resident Engineer or Assistant Resident Engineer signature on that specific crew  
(EX. Ray Geles)